

SCHEDULE OF PARTIAL DEPTH PATCHING (CONT'D)

STATION	DIRECTION	LENGTH (FOOT)	WIDTH (FOOT)	PARTIAL DEPTH REMOVAL 8 1/2" 44022051 (SQ YD)	PARTIAL DEPTH PATCHING X4421000 (TONS)	
390+12.00	WB	15	12	20.0	9.5	
390+57.00	WB	15	12	20.0	9.5	
391+11.00	EB	6	12	8.0	3.8	
391+11.00	WB	6	12	8.0	3.8	
403+24.00	EB	6	12	8.0	3.8	
403+24.00	WB	6	12	8.0	3.8	
407+24.00	EB	6	12	8.0	3.8	
407+24.00	WB	6	12	8.0	3.8	
408+24.00	EB	6	12	8.0	3.8	
408+24.00	WB	6	12	8.0	3.8	
409+28.00	EB	12	12	16.0	7.6	
409+28.00	WB	12	12	16.0	7.6	
409+74.00	EB	10	12	13.3	6.3	
409+74.00	WB	10	12	13.3	6.3	
410+74.00	EB	6	12	8.0	3.8	
410+74.00	WB	6	12	8.0	3.8	
411+24.00	EB	10	12	13.3	6.3	
411+24.00	WB	10	12	13.3	6.3	
412+74.00	EB	6	12	8.0	3.8	
412+74.00	WB	6	12	8.0	3.8	
				SUB-TOTAL =	221.3	105.4
				TOTAL =	4,017.3	1,912.3
				USE =	4,018.0	1,913.0