

SCHEDULE OF MAINLINE RESURFACING						LEVEL BINDER THICKNESS INCHES	BINDER THICKNESS INCHES	SURFACE COURSE THICKNESS INCHES	40600100 BIT MATLS PR CT GALLONS	40600300 AGG PR CT TONS	40600627 LB (MM) IL 9.5 FG, N50 TON	40603082 HMA BDR CSE IL 19.0FG, N50 TON	40603335 HMA SC "D", N50 TON
STATION	ID	STATION	LENGTH	WIDTH	SO YD								
URBAN													
97+55.22		102+00.00	444.8	24.0	1,186.1	0.75		1.5	118.6	2.4	49.8		99.6
102+00.00		108+00.00	600.0	24.0	1,600.0	0.75		1.5	160.0	3.2	67.2		134.4
108+00.00		114+00.00	600.0	24.0	1,600.0	0.75		1.5	160.0	3.2	67.2		134.4
114+00.00		117+00.00	300.0	24.0	800.0	-	5.25	1.5	80.0	1.6	-	235.2	67.2
120+00.00		126+00.00	600.0	24.0	1,600.0	-	5.25	1.5	160.0	3.2	-	470.4	134.4
126+00.00		132+00.00	600.0	24.0	1,600.0	-	5.25	1.5	160.0	3.2	-	470.4	134.4
132+00.00		138+00.00	600.0	24.0	1,600.0	-	5.25	1.5	160.0	3.2	-	470.4	134.4
138+00.00		142+00.00	400.0	24.0	1,066.7	-	5.25	1.5	106.7	2.1	-	313.6	89.6
RURAL													
142+00.00		144+00.00	200.0	24.0	533.3	-	5.25	1.5	53.3	1.1	-	156.8	44.8
144+00.00		150+00.00	600.0	24.0	1,600.0	-	5.25	1.5	160.0	3.2	-	470.4	134.4
150+00.00		156+00.00	600.0	24.0	1,600.0	-	5.25	1.5	160.0	3.2	-	470.4	134.4
156+00.00		162+00.00	600.0	24.0	1,600.0	-	5.25	1.5	160.0	3.2	-	470.4	134.4
162+00.00		168+50.00	650.0	24.0	1,733.3	-	5.25	1.5	173.3	3.5	-	509.6	145.6
168+50.00		174+00.00	550.0	24.0	1,466.7	0.75	-	1.5	146.7	2.9	61.6	-	123.2
174+00.00		180+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
180+00.00		186+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
186+00.00		192+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
192+00.00		198+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
198+00.00		204+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
204+00.00		210+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
210+00.00		216+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
216+00.00		222+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
222+00.00		228+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
228+00.00		234+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
234+00.00		240+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
240+00.00		246+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
246+00.00		252+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
252+00.00		258+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
258+00.00		264+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
264+00.00		270+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
270+00.00		276+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
276+00.00		282+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
282+00.00		288+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
288+00.00		294+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
294+00.00		300+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
300+00.00		306+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
306+00.00		312+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
312+00.00		318+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
318+00.00		324+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
324+00.00		330+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
330+00.00		336+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
336+00.00		342+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
342+00.00		348+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
348+00.00		354+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
354+00.00		360+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
360+00.00		366+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
366+00.00		372+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
372+00.00		378+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
378+00.00		384+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
384+00.00		390+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
390+00.00		396+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
396+00.00		398+21.52	221.5	24.0	590.7	0.75	-	1.5	59.1	1.2	24.8	-	49.6
401+15.67		402+00.00	84.3	24.0	224.9	0.75	-	1.5	22.5	0.4	9.4	-	18.9
402+00.00		408+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
408+00.00		414+00.00	600.0	24.0	1,600.0	0.75	-	1.5	160.0	3.2	67.2	-	134.4
414+00.00		417+19.15	319.2	24.0	851.1	0.75	-	1.5	85.1	1.7	35.7	-	71.5
SUB-TOTAL =			31,369.8	-	83,652.7	-	-	-	8,365.3	167.3	2,936.6	4,037.6	7,026.8

SCHEDULE OF SIDEROAD RESURFACING						LEVEL BINDER THICKNESS INCHES	BINDER THICKNESS INCHES	SURFACE COURSE THICKNESS INCHES	40600100 BIT MATLS PR CT GALLONS	40600300 AGG PR CT TONS	40600627 LB (MM) IL 9.5 FG, N50 TON	40603082 HMA BDR CSE IL 19.0FG, N50 TON	40603335 HMA SC "D", N50 TON
STATION	ID	STATION	LENGTH	WIDTH	SO YD								
URBAN													
COTTONWOOD DR.	86+00.00	98+00.00	1200.0	20.0	2,666.7	2.0	-	1.5	266.7	5.3	298.7	-	224.0
COTTONWOOD DR.	98+00.00	99+88.00	188.0	VAR.	811.4	2.0	-	1.5	81.1	1.6	90.9	-	68.2
COTTONWOOD DR.	100+12.00	102+00.00	188.0	VAR.	878.9	-	3.25	1.5	87.9	1.8	-	160.0	73.8
COTTONWOOD DR.	102+00.00	108+50.00	650.0	22.0	1,588.9	-	3.25	1.5	158.9	3.2	-	289.2	133.5
RURAL													
TR 1900 E	298+59.43	299+88.00	128.6	VAR.	580.0	2.0	-	1.5	58.0	1.2	65.0	-	48.7
TR 1900 E	300+12.00	301+51.11	139.1	VAR.	723.0	-	3	1.5	72.3	1.4	-	121.5	60.7
SUB-TOTAL =			2,493.7	-	7,248.9	-	-	-	724.9	14.5	454.5	570.6	608.9
TOTAL =			33,863.5	-	90,901.6	-	-	-	9,090.2	181.8	3,391.1	4,608.2	7,635.7
USE =			33,864.0	-	90,902.0	-	-	-	9,090.0	182.0	3,391.0	4,608.0	7,636.0