

48203100 HOT-MIX ASPHALT SHOULDERS

| STATION         | IQ | STATION      | LENGTH | WIDTH | THICKNESS | SQ YDS | 40600100<br>BIT MATLS PR CT | 40600300<br>AGG PR CT | GALLONS | TONS | TONS  |
|-----------------|----|--------------|--------|-------|-----------|--------|-----------------------------|-----------------------|---------|------|-------|
| URBAN           |    |              |        |       |           |        |                             |                       |         |      |       |
| LT 99+51.21     |    | LT 102+00.00 | 248.8  | 5.0   | 1.5"      | 138.2  |                             |                       | 13.8    | 0.3  | 11.6  |
| LT 102+00.00    |    | LT 108+00.00 | 600.0  | 5.0   | 1.5"      | 333.3  |                             |                       | 33.3    | 0.7  | 28.0  |
| LT 108+00.00    |    | LT 114+00.00 | 600.0  | 5.0   | 1.5"      | 333.3  |                             |                       | 33.3    | 0.7  | 28.0  |
| LT 114+00.00    |    | LT 115+00.00 | 100.0  | 5.0   | 1.5"      | 55.6   |                             |                       | 5.6     | 0.1  | 4.7   |
| RURAL           |    |              |        |       |           |        |                             |                       |         |      |       |
| LT 231+85.68    |    | LT 234+00.00 | 214.3  | 5.0   | 1.5"      | 119.1  |                             |                       | 11.9    | 0.2  | 10.0  |
| LT 234+00.00    |    | LT 240+00.00 | 600.0  | 5.0   | 1.5"      | 333.3  |                             |                       | 33.3    | 0.7  | 28.0  |
| LT 240+00.00    |    | LT 246+00.00 | 600.0  | 5.0   | 1.5"      | 333.3  |                             |                       | 33.3    | 0.7  | 28.0  |
| LT 246+00.00    |    | LT 249+56.10 | 356.1  | 5.0   | 1.5"      | 197.8  |                             |                       | 19.8    | 0.4  | 16.6  |
| RT 396+04.43    |    | RT 398+21.52 | 217.1  | 4.0   | 1.5"      | 96.5   |                             |                       | 9.6     | 0.2  | 8.1   |
| LT 396+04.28    |    | LT 398+21.52 | 217.2  | 4.0   | 1.5"      | 96.6   |                             |                       | 9.7     | 0.2  | 8.1   |
| RT 401+15.67    |    | RT 402+00.00 | 84.3   | 4.0   | 1.5"      | 37.5   |                             |                       | 3.7     | 0.1  | 3.1   |
| LT 401+15.67    |    | LT 402+00.00 | 84.3   | 4.0   | 1.5"      | 37.5   |                             |                       | 3.7     | 0.1  | 3.1   |
| TOTAL = 2,112.0 |    |              |        |       |           |        |                             |                       | 211.2   | 4.2  | 177.4 |
| USE = 2,112.0   |    |              |        |       |           |        |                             |                       | 212.0   | 5.0  | 178.0 |

60600095 CLASS SI CONCRETE OUTLET

| STATION       | IQ           | STATION      | CU YD |
|---------------|--------------|--------------|-------|
| RURAL         |              |              |       |
| LT 198+88.00  |              | LT 198+93.00 | 1.8   |
| LT 203+07.00  |              | LT 203+12.00 | 1.8   |
| RT 226+88.00  |              | RT 227+00.05 | 1.8   |
| RT 234+23.85  |              | RT 234+73.13 | 11.0  |
| RT 237+00.00  |              | RT 237+12.01 | 1.8   |
| LT 291+38.00  |              | LT 291+50.00 | 1.8   |
| LT 291+88.37  |              | LT 292+36.40 | 10.7  |
| LT 293+06.31  |              | LT 293+45.84 | 8.2   |
| LT 293+45.84  |              | LT 294+14.02 | 16.5  |
| LT 294+50.00  |              | LT 294+62.00 | 1.8   |
| TR 1900 E     | LT 299+80.00 | LT 299+82.84 | 0.6   |
| TR 1900 E     | LT 298+59.19 | LT 298+64.19 | 0.6   |
| TR 1900 E     | RT 299+17.86 | RT 299+22.76 | 0.6   |
| TR 1900 E     | RT 299+77.96 | RT 299+79.10 | 0.6   |
| TR 1900 E     | LT 300+82.44 | LT 300+87.44 | 0.6   |
| TR 1900 E     | RT 300+18.22 | LT 300+20.84 | 0.6   |
| TR 1900 E     | RT 301+46.10 | RT 301+51.10 | 0.6   |
| URBAN         |              |              |       |
| COTTONWOOD DR | LT 100+19.41 | LT 100+20.78 | 0.6   |
| COTTONWOOD DR | LT 101+03.45 | LT 101+08.45 | 0.6   |
| COTTONWOOD DR | LT 99+77.79  | LT 99+80.80  | 0.6   |
| COTTONWOOD DR | LT 98+18.09  | LT 98+22.99  | 0.6   |
| COTTONWOOD DR | RT 101+54.24 | RT 101+59.24 | 0.6   |
| COTTONWOOD DR | RT 100+18.89 | RT 100+21.39 | 0.6   |
| COTTONWOOD DR | RT 99+18.67  | RT 99+23.67  | 0.6   |
| COTTONWOOD DR | RT 99+80.35  | RT 99+81.66  | 0.6   |
| TOTAL =       |              |              | 61.4  |
| USE =         |              |              | 66.0  |

42300200 PCC DRIVEWAY PAVEMENT - 6"

X0325279 CLASS SI CONCRETE (MISC)

50901760 PIPE HANDRAIL

| STATION      | SQ YD | STATION      | CU YD | STATION      | FOOT |
|--------------|-------|--------------|-------|--------------|------|
| RURAL        |       |              |       |              |      |
| LT 266+92.90 | 13.0  | LT 293+79.83 | 2.1   | LT 293+79.83 | 12.0 |
| TOTAL = 13.0 |       | TOTAL = 2.0  |       | TOTAL = 12.0 |      |

X6060097 CLASS SI CONCRETE OUTLET (SPECIAL)

| STATION       | CU YD        |     |
|---------------|--------------|-----|
| URBAN         |              |     |
| COTTONWOOD DR | LT 99+00.00  | 1.0 |
| COTTONWOOD DR | RT 100+50.00 | 1.0 |
| RURAL         |              |     |
| TR 1900 E     | LT 300+22.38 | 1.8 |
| TR 1900 E     | LT 300+75.00 | 1.0 |
| TOT           |              | 4.8 |
| USE =         |              | 5.0 |

60602500 CONCRETE GUTTER, TYPE A

60605000 COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.24

| STATION        | IQ | STATION      | FOOT  | STATION       | IQ | STATION      | FOOT  |
|----------------|----|--------------|-------|---------------|----|--------------|-------|
| RURAL          |    |              |       |               |    |              |       |
| RT 227+00.05   |    | RT 228+00.00 | 100.0 | LT 98+22.99   |    | LT 99+77.79  | 159.0 |
| RT 228+00.00   |    | RT 234+00.00 | 600.0 | RT 99+23.67   |    | RT 99+80.35  | 81.0  |
| RT 234+00.00   |    | RT 234+23.85 | 23.8  | LT 100+20.78  |    | LT 101+03.45 | 109.0 |
| RT 234+73.13   |    | RT 237+00.00 | 226.9 | RT 100+21.39  |    | RT 101+54.24 | 143.0 |
| LT 249+76.92   |    | LT 249+98.62 | 21.7  | RURAL         |    |              |       |
| LT 291+50.00   |    | LT 291+88.37 | 38.4  | LT 298+64.19  |    | LT 299+80.00 | 121.0 |
| LT 292+36.40   |    | LT 293+06.31 | 69.9  | RT 299+22.76  |    | RT 299+77.96 | 76.0  |
| LT 294+14.02   |    | LT 294+50.00 | 36.0  | LT 300+20.70  |    | LT 300+82.44 | 88.5  |
| TOTAL = 1116.6 |    |              |       | RT 300+20.84  |    | RT 301+46.10 | 133.5 |
| USE = 1117.0   |    |              |       | TOTAL = 911.0 |    |              |       |

X6060078 COMBINATION CONCRETE CURB AND GUTTER, TYPE M-4.24 (SPECIAL)

| STATION      | IQ | STATION      | FOOT  |
|--------------|----|--------------|-------|
| RURAL        |    |              |       |
| LT 198+93.00 |    | LT 203+07.00 | 414.0 |
| TOTAL =      |    |              | 414.0 |