PATRICK ENGINEERING INC.

BORING NUMBER B-3-97 SHEET 1 OF 2
CLIENT Illinois Department of Natural Resources
PROJECT & NO. Lake Michigan Leakage Control - L609.A0-2
LOCATION US North Pier. See boring location plan, 94 Streeter Dr., Chicago, IL N 1,903,052.5 E 696,717.4

LOGGED BY PJC
GROUND ELEVATION 10.1

ELEVATION	DEPTH (FT)	SOIL/ROCK DESCRIPTION	SAMPLE TYPE & NO.	DEPTH (FT)	RECOVERY(IN)	BLOWS/6 INCHES	Water Content (PL ○ 20 30 40 50 LL) / Unconfined Compressive Strength (TSF)	NOTES & TEST RESULTS
10.1	0.0	Black silty clay, trace organics, little coarse to fine sand, trace brick fragments, medium stiff, medium to high plasticity, moist to wet	SS-1	0.0-2.0	19"R	2 3 7 4	27.5	PID=Photo-Ionization device results in parts per million (ppm)
		-FILL-	SS-2	2.0-4.0	18"R	7 16 9 8	8.8	SS-1: PID=5.5ppm
		2.0' medium to fine gravel with little coarse to fine sand at 3.4'	SS-3	4.0-6.0	18"R	4 5 5 8	26.3	PID=6.7ppm
		Black and brown at 4.0'						PID=6.3ppm Auger grinding
3.6	6.5		SS-4	6.0-6.4	4"R	50+/5"	6.6	PID=6.2ppm
		Apparent 4.6' thick concrete slab with rebar reinforcement from 6.5' to 11.1'. Fragments of concrete slab inside augers. Coarse to fine gravel in cuttings, auger tights catching on rebar. -FILL-	SS-5	8.0	0"R	50/0"		Auger grinding
-0.1	10.2							PID=7.0ppm Auger grinding
-1.0	11.1	White and black coarse to fine gravel, some coarse to fine sand, little silt, trace cinders, dense, saturated, possible cobbles and boulders	SS-6	11.1-12.0		2 2/5"	18.8	SS-6: 4"R
			SS-7	12.0-14.0	10"R	3 2 3 4	22.8	PID=8.1ppm Auger grinding
		-FILL- GM	SS-8	14.0-15.3	12"R	3 17 50+/4"	24.4	PID=8.0ppm
			SS-9	16.0-18.0	9"R	4 8 8 13	22.8	PID=6.3ppm Auger grinding
			SS-10	18.0-20.0	6"R	9 8 9 8	10.3	PID=7.3ppm
-9.9	20.0							

DRILLING CONTRACTOR Patrick Drilling
DRILLING METHOD 4 1/4" I.D. HSA
DRILLING EQUIPMENT CME 75 ATV
DRILLING STARTED 4/4/97 ENDED 4/4/97

REMARKS
Piezometer P-3-97 constructed in completed borehole. See Installation

WATER LEVEL (ft.)
▽ 11.1' during drilling
▼ 10.6' 1mm. after drilling
▼ 10.2 4/18/97

PATRICK ENGINEERING INC.

BORING NUMBER B-3-97 SHEET 2 OF 2
CLIENT Illinois Department of Natural Resources
PROJECT & NO. Lake Michigan Leakage Control - L609.A0-2
LOCATION US North Pier. See boring location plan, 94 Streeter Dr., Chicago, IL N 1,903,052.5 E 696,717.4

LOGGED BY PJC
GROUND ELEVATION 10.1

ELEVATION	DEPTH (FT)	SOIL/ROCK DESCRIPTION	SAMPLE TYPE & NO.	DEPTH (FT)	RECOVERY(IN)	BLOWS/6 INCHES	Water Content (PL ○ 20 30 40 50 LL) / Unconfined Compressive Strength (TSF)	NOTES & TEST RESULTS
-9.9	20.0	White and black coarse to fine gravel, some coarse to fine sand, little silt, trace cinders, dense, saturated, possible cobbles and boulders	SS-11	20.0-22.0	4"R	2 7 12 5	26.1	PID=7.0ppm Auger grinding
		-FILL- GM	SS-12	22.0-22.5	6"R	85/6"	23.2	PID=6.8ppm Auger grinding. Removed auger, replaced auger teeth. Continued drilling. Auger grinding on boulder.
		Cinders and wood fragments at 26.0'	SS-13	24.0-26.0	14"R	13 22 10 11	14.2	
-17.5	27.6		SS-14	26.0-27.4	13"R	18 29 50/5"	11.7	
		Black coarse to fine sand and silt, little coarse to fine gravel, dense, saturated -FILL- SM	SS-15A/B	28.0-30.0	20"R	18 11 3 4	8.5 / 26.9	SS-15A: PID=5.9ppm SS-15B: PID=6.0ppm qu**=0.7tsf
-19.1	29.2							
-19.9	30.0	Gray silty clay, trace coarse to fine sand, soft, medium plasticity, wet CL						
		End of Boring at 30.0'.						

DRILLING CONTRACTOR Patrick Drilling
DRILLING METHOD 4 1/4" I.D. HSA
DRILLING EQUIPMENT CME 75 ATV
DRILLING STARTED 4/4/97 ENDED 4/4/97

REMARKS
Piezometer P-3-97 constructed in completed borehole. See Installation

WATER LEVEL (ft.)
▽ 11.1' during drilling
▼ 10.6' 1mm. after drilling
▼ 10.2 4/18/97

PATRICK ENGINEERING INC.

BORING NUMBER B-4-97 SHEET 1 OF 2
CLIENT Illinois Department of Natural Resources
PROJECT & NO. Lake Michigan Leakage Control - L609.A0-2
LOCATION US North Pier. See boring location plan, 94 Streeter Dr., Chicago, IL N 1,903,051.4 E 697,001.7

LOGGED BY PJC
GROUND ELEVATION 9.9

ELEVATION	DEPTH (FT)	SOIL/ROCK DESCRIPTION	SAMPLE TYPE & NO.	DEPTH (FT)	RECOVERY(IN)	BLOWS/6 INCHES	Water Content (PL ○ 20 30 40 50 LL) / Unconfined Compressive Strength (TSF)	NOTES & TEST RESULTS
9.9	0.0	Gray coarse to fine gravel, little coarse to fine sand, little silt, moist IDOT CA-6 -FILL- GM	AU-1	0.0-2.0			4.2	PID=Photo-Ionization device results in parts per million (ppm)
7.4	2.5	Black silty clay, trace cinders, little coarse to fine sand, trace fine gravel, medium stiff, medium plasticity, moist -FILL- CL	SS-2	2.0-4.0	10"R	3 4 5 5	10.3	AU-1: PID=6.5ppm
4.9	5.0		SS-3	4.0-6.0	18"R	4 2 3 4	19.1	Auger grinding at 3.0'. PID=7.0ppm PID=5.3ppm
3.3	6.6	Gray silty clay, little coarse to fine sand, trace medium to fine gravel, stiff, low plasticity, moist	SS-4	6.0-6.7	6"R	2 50+/2"	17.1	PID=6.2ppm Auger grinding
		Brown saturated coarse to fine sand 6.4' - 6.6' -FILL- CL	SS-5	8.0	0"R	50+/0"		No recovery possible, concrete footing.
		Apparent 3.0' thick concrete slab from 6.6' to 9.6' Fragments of concrete slab inside augers. Coarse to fine gravel in cuttings. -FILL-	SS-6	10.0-10.2	2"R	50+/3"	19.3	PID=6.8ppm Auger grinding
0.3	9.6	Black and white coarse to fine gravel with apparent cobbles, little coarse to fine sand, little silt, trace cinders, dense, saturated -FILL- GM	SS-7	12.0-14.0	10"R	3 10 12 10	15.6	PID=7.0ppm
			SS-8	14.0-16.0	12"R	12 10 8 8	9.8	PID=6.9ppm Auger grinding
			SS-9	16.0-18.0	13"R	5 4 6 6	4.5	PID=7.2ppm
		Little clayey silt in sample at 17.5' Some black and brown coarse to fine sand and silt at 18.0'	SS-10	18.0-20.0	12"R	5 11 10	15.6	PID=6.5ppm
-9.6	19.5							

DRILLING CONTRACTOR Patrick Drilling
DRILLING METHOD 4 1/4" I.D. HSA
DRILLING EQUIPMENT CME 75 ATV
DRILLING STARTED 4/7/97 ENDED 4/7/97

REMARKS
Piezometer P-4-97 constructed in completed borehole. See Installation

WATER LEVEL (ft.)
▽ 10.0' during drilling
▼ 10.5' 1mm. after drilling
▼ 9.7 4/18/97

PATRICK ENGINEERING INC.

BORING NUMBER B-4-97 SHEET 2 OF 2
CLIENT Illinois Department of Natural Resources
PROJECT & NO. Lake Michigan Leakage Control - L609.A0-2
LOCATION US North Pier. See boring location plan, 94 Streeter Dr., Chicago, IL N 1,903,051.4 E 697,001.7

LOGGED BY PJC
GROUND ELEVATION 9.9

ELEVATION	DEPTH (FT)	SOIL/ROCK DESCRIPTION	SAMPLE TYPE & NO.	DEPTH (FT)	RECOVERY(IN)	BLOWS/6 INCHES	Water Content (PL ○ 20 30 40 50 LL) / Unconfined Compressive Strength (TSF)	NOTES & TEST RESULTS
-9.6	9.5	Black coarse to fine sand and silty clay, trace coarse to fine gravel, trace cinders, possible cobbles, dense, saturated -FILL- SM	SS-11	20.0-22.0	10"R	7 4 4 10 10	19.2	PID=4.0ppm
			SS-12	22.0-24.0	13"R	5 4 6 7	24.9	PID=2.3ppm
			SS-13	24.0-26.0	10"R	5 5 2 2	22.3	PID=3.2ppm
			SS-14	26.0-28.0	12"R	11 7 5 5	12.1	PID=2.7ppm
			SS-15	28.0-30.0	14"R	17 16 15 19	24.9	PID=2.5ppm Possible boulder or cobbles, auger grinding
		Limestone chips in sample at 30.7'	SS-16	30.0-30.8	8"R	9 50/3"	57.6	PID=2.9ppm
-22.6	32.5	Parts of timber in sample at 32.1' Brown and gray silty clay, little coarse to fine sand, soft, low plasticity, moist to wet CL	SS-17	32.0-34.0	19"R	19 2 3 4	15.2	PID=3.4ppm qu**=0.5tsf
-24.1	34.0	End of Boring at 34.0'.						

DRILLING CONTRACTOR Patrick Drilling
DRILLING METHOD 4 1/4" I.D. HSA
DRILLING EQUIPMENT CME 75 ATV
DRILLING STARTED 4/7/97 ENDED 4/7/97

REMARKS
Piezometer P-4-97 constructed in completed borehole. See Installation

WATER LEVEL (ft.)
▽ 10.0' during drilling
▼ 10.5' 1mm. after drilling
▼ 9.7 4/18/97

PATRICK ENGINEERING INC.

BORING NUMBER B-5-97 SHEET 1 OF 2
CLIENT Illinois Department of Natural Resources
PROJECT & NO. Lake Michigan Leakage Control - L609.A0-2
LOCATION US North Pier. See boring location plan, 94 Streeter Dr., Chicago, IL N 1,903,052.3 E 696,815.8

LOGGED BY PJC
GROUND ELEVATION 10.1

ELEVATION	DEPTH (FT)	SOIL/ROCK DESCRIPTION	SAMPLE TYPE & NO.	DEPTH (FT)	RECOVERY(IN)	BLOWS/6 INCHES	Water Content (PL ○ 20 30 40 50 LL) / Unconfined Compressive Strength (TSF)	NOTES & TEST RESULTS
10.1	0.0	Gray coarse to fine gravel, some coarse to fine sand, little black silty clay, trace cinders, moist -FILL- GC	AU-1	0.0-2.0			8.6	PID=Photo-Ionization device results in parts per million (ppm)
8.1	2.0	Gray and brown silty clay, trace coarse to fine sand, stiff, medium to low plasticity, moist -FILL- CL	SS-2	2.0-4.0	16"R	21 3 5 4	15.8	AU-1: PID=3.8ppm PID=4.7ppm
		Little brick fragments in sample at 5.0'.	SS-3	4.0-6.0	14"R	2 5 4 3	15.6	Auger grinding PID=5.7ppm
3.6	6.5	Apparent 4.8' thick concrete slab from 6.5' to 11.3'. Fragments of concrete slab inside augers. Coarse to fine gravel in cuttings -FILL-	SS-4	6.0-6.5	0"R	1 50/0"	17.7	PID=5.6ppm qu**=1.3tsf Spoon refusal Auger grinding
0.0	10.1		SS-5	8.0	0"R	50/0"		
-1.2	11.3		SS-6	10.0	0"R	50/0"		
		Gray coarse to fine gravel, little coarse to fine sand, little silt, trace cinders, possible cobbles, dense, saturated -FILL- GM	SS-7	12.0-14.0	15"R	22 25 6 5	9.8	PID=7.9ppm
			SS-8	14.0-16.0	9"R	7 10 7 4	24.6	PID=7.5ppm
			SS-9	16.0-18.0	12"R	7 10 13 10	8.3	PID=7.2ppm
-8.4	18.5	Black clayey silt to silt, little coarse to fine sand, little coarse to fine gravel, dense, saturated -FILL- CL-ML	SS-10	18.0-20.0	12"R	15 13 7 9	11.8	PID=6.9ppm
			SS-11	20.0-22.0	14"R	13 14 7 7	7.6	PID=9.4ppm
-8.5	20.6							

DRILLING CONTRACTOR Patrick Drilling
DRILLING METHOD 4 1/4" I.D. HSA
DRILLING EQUIPMENT CME 75 ATV
DRILLING STARTED 4/15/97 ENDED 4/15/97

REMARKS
Piezometer P-5-97 constructed in completed borehole. See Installation

WATER LEVEL (ft.)
▽ 11.3' during drilling
▼ 10.0' after drilling
▼ 10.1 4/18/97

PATRICK ENGINEERING INC.

BORING NUMBER B-5-97 SHEET 2 OF 2
CLIENT Illinois Department of Natural Resources
PROJECT & NO. Lake Michigan Leakage Control - L609.A0-2
LOCATION US North Pier. See boring location plan, 94 Streeter Dr., Chicago, IL N 1,903,052.3 E 696,815.8

LOGGED BY PJC
GROUND ELEVATION 10.1

ELEVATION	DEPTH (FT)	SOIL/ROCK DESCRIPTION	SAMPLE TYPE & NO.	DEPTH (FT)	RECOVERY(IN)	BLOWS/6 INCHES	Water Content (PL ○ 20 30 40 50 LL) / Unconfined Compressive Strength (TSF)	NOTES & TEST RESULTS
-11.5	21.6	Black coarse to fine gravel, little coarse to fine sand, trace silt, dense, saturated -FILL- GC	SS-12	22.0-24.0	10"R	8 4 6 8 7	8.8	PID=9.5ppm
-13.3	23.4	Black clayey silt to silt, little coarse to fine sand, trace coarse to fine gravel, dense, saturated -FILL- CL-ML	SS-13	24.0-26.0	8"R	10 8 11 11	8.8	PID=9.1ppm
		No gravel in sample at 28.0'	SS-14	26.0-28.0	14"R	1 8 10 9	14.3	PID=10.0ppm
-19.7	29.8		SS-15	28.0-30.0	19"R	9 8 3 3	24.6	PID=9.1ppm
		Black medium to fine sand, little silt, timber fragments, loose, saturated -FILL- SM	SS-16	30.0-30.7	8"R	2 50/2"	28.0	PID=8.1ppm
-21.2	31.3	Timber fragments in sample at 30.0'.	SS-17	32.0-32.2	3"R	50/3"	20.0	Possible boulder, auger grinding. PID=10.4ppm PID=7.5ppm qu**=0.6tsf
-23.0	33.1	Black and brown coarse to fine sand, dense, saturated Limestone chips in sample -FILL- SM	SS-18	34.0-36.0	24"R	2 2 2 4	29.3	
-25.9	36.0	Gray silty clay, trace coarse to fine sand, soft, medium to low plasticity, wet CL						
		End of Boring at 36.0'.						

DRILLING CONTRACTOR Patrick Drilling
DRILLING METHOD 4 1/4" I.D. HSA
DRILLING EQUIPMENT CME 75 ATV
DRILLING STARTED 4/15/97 ENDED 4/15/97

REMARKS
Piezometer P-5-97 constructed in completed borehole. See Installation

WATER LEVEL (ft.)
▽ 11.3' during drilling
▼ 10.0' after drilling
▼ 10.1 4/18/97

PATRICK ENGINEERING INC.

BORING NUMBER B-1-96 SHEET 1 OF 1
CLIENT Illinois Department of Natural Resources
PROJECT & NO. Lake Michigan Leakage Control - L609.A0-2
LOCATION US North Pier. See boring location plan, 94 Streeter Dr., Chicago, IL N 1,903,056.6 E 696,729.2

LOGGED BY PJC
GROUND ELEVATION 10.1

ELEVATION	DEPTH (FT)	SOIL/ROCK DESCRIPTION	SAMPLE TYPE & NO.	DEPTH (FT)	RECOVERY(IN)	BLOWS/6 INCHES	Water Content (PL ○ 20 30 40 50 LL) / Unconfined Compressive Strength (TSF)	NOTES & TEST RESULTS
10.1	0.0							Blind drilled to 16.5'. See boring log CBB-1-86 for soil conditions in the vicinity.
-0.1	10.2	Soil cuttings 0.0' - 16.5': Brown, gray and black silty clay, with coarse to fine sand, coarse to fine gravel, cinders, rubble, wood, low plasticity, wet -FILL- CL						Auger grinding on possible concrete from 7.5' to 10.5'.
-21.4	31.5							Piezometer P-10-96 installed in borehole. See Installation report for more details. Piezometer P-15-96 installed in offset borehole approximately 5.0' west. Offset borehole encountered

DRILLING CONTRACTOR Patrick Drilling
DRILLING METHOD 4 1/4" I.D. HSA
DRILLING EQUIPMENT CME 55 TM
DRILLING STARTED 12/13/96 ENDED 12/15/96

REMARKS
Piezometer P-10-96 constructed in completed borehole. See Installation

WATER LEVEL (ft.)
▽ 12.0' during drilling
▼ 10.2' 1/14/97
▼ 10.2 4/15/97

PATRICK ENGINEERING INC.

BORING NUMBER B-2-96 SHEET 1 OF 2
CLIENT Illinois Department of Natural Resources
PROJECT & NO. Lake Michigan Leakage Control - L609.A0-2
LOCATION US North Pier. See boring location plan, 94 Streeter Dr., Chicago, IL N 1,903,052.2 E 696,882.1

LOGGED BY PJC
GROUND ELEVATION 10.2

ELEVATION	DEPTH (FT)	SOIL/ROCK DESCRIPTION	SAMPLE TYPE & NO.	DEPTH (FT)	RECOVERY(IN)	BLOWS/6 INCHES	Water Content (PL ○ 20 30 40 50 LL) / Unconfined Compressive Strength (TSF)	NOTES & TEST RESULTS
10.2	0.0	Black silty clay, IDOT CA-7 from 3" to 10' -FILL- CL	AU-1	0.0-1.0			11.1	PID=Photo-Ionization device results in parts per million (ppm). AU-1: PID=3.2ppm
9.2	1.0	Black silty clay, some coarse to fine sand, little medium to fine gravel, stiff, moist -FILL- CL	SS-2	1.0-3.0	7"R	5 4 5 5	12.0	SS-2: PID=2.6ppm No recovery in SS-3. Took auger sample
6.9	3.3	Black and brown silty clay, little coarse to fine sand, trace coarse to fine gravel, soft to medium stiff, medium plasticity, moist to wet -FILL- CL	SS-3	3.0-5.0	0"R	8 6 6 5	13.5	AU-3: PID=1.2ppm
			SS-4	5.0-7.0	18"R	5 6 4 3	20.8	Auger grinding SS-4: PID=1.9ppm
3.2	7.0	Apparent 3' thick concrete slab from 7.0' to 10.0' Fragments of concrete slab inside augers Coarse to fine gravel in cuttings -FILL-	SS-5	7.0-7.1	0"R	50/1"		Spoon refusal on apparent concrete.
0.2	10.0	White coarse to fine gravel, little coarse to fine sand, little silt, dense, saturated -FILL- GM	SS-6	10.0-11.0		17 11	5.2	Auger grinding through 3' concrete slab SS-6: 4" Recovery PID=1.3ppm
-2.5	12.7		SS-7	11.0-13.0	16"R	4 16 14 7	23.1	Auger grinding SS-7: PID=2.0ppm
		Dark gray coarse to fine gravel with apparent cobbles, some coarse to fine sand, some silty clay, little cinders, medium dense, saturated -FILL- GC	SS-8	13.0-15.0	17"R	10 11 5 14	21.6	Auger grinding PID=4.2ppm
			SS-9	15.0-17.0	0"R	W O R	6.2	Auger grinding 15.0' - 17.0'
			SS-10	17.0-19.0	24"R	11 17 5 16		PID=5.1ppm Gravel= 43% Sand = 28% Fines = 29%

DRILLING CONTRACTOR Patrick Drilling
DRILLING METHOD 4 1/4" I.D. HSA
DRILLING EQUIPMENT CME 55 TM
DRILLING STARTED 12/19/96 ENDED 12/19/96

REMARKS
Piezometer P-2-96 constructed in completed borehole. See Installation

WATER LEVEL (ft.)
▽ 10.0' during drilling
▼ 10.2' 1/14/97
▼ 10.1 4/15/97

PATRICK ENGINEERING INC.

BORING NUMBER B-2-96 SHEET 2 OF 2
CLIENT Illinois Department of Natural Resources
PROJECT & NO. Lake Michigan Leakage Control - L609.A0-2
LOCATION US North Pier. See boring location plan, 94 Streeter Dr., Chicago, IL N 1,903,052.2 E 696,882.1

LOGGED BY PJC
GROUND ELEVATION 10.2

ELEVATION	DEPTH (FT)	SOIL/ROCK DESCRIPTION	SAMPLE TYPE & NO.	DEPTH (FT)	RECOVERY(IN)	BLOWS/6 INCHES	Water Content (PL ○ 20 30 40 50 LL) / Unconfined Compressive Strength (TSF)	NOTES & TEST RESULTS
-8.8	19.0	Dark gray coarse to fine gravel with apparent cobbles, some coarse to fine sand, some silty clay, little cinders, medium dense, saturated -FILL- GC	SS-11A/B	19.0-21.0	20"R	7 3 9 26	29.5	SS-11A: PID=2.9ppm SS-11B: PID=3.3ppm
-10.4	20.6	Dark gray coarse to fine sand, some coarse to fine gravel, some clayey silt, medium dense to dense, saturated -FILL- SM	SS-12	21.0-21.3	2"R	50/4"	19.1	Auger grinding SS-12: PID=4.8ppm
			SS-13	23.0-25.0	14"R	10 13 14 16	35.5	Auger grinding at 23.2'. SS-13: PID=2.4ppm Gravel= 3% Sand = 47% Fines = 22%
			SS-14	25.0-27.0	16"R	15 13 27 19	30.6	SS-14: PID=2.4ppm
-16.8	27.0	Apparent wood -FILL-	SS-15	27.0-27.4	0"R	50/5"	8.8	Auger grinding through Interval 27.0' - 29.0'. Auger's become out of plumb after encountering possible wood. Wood in cuttings
-18.8	29.0	Gray silty clay, trace to little coarse to fine sand, soft, medium plasticity, wet CL	SS-16	29.0-31.0	18"R	10 12 8 9	19.1	SS-16: PID=6.3ppm
-22.5	32.7	End of Boring at 32.7'.						

DRILLING CONTRACTOR Patrick Drilling
DRILLING METHOD 4 1/4" I.D. HSA
DRILLING EQUIPMENT CME 55 TM
DRILLING STARTED 12/19/96 ENDED 12/19/96

REMARKS
Piezometer P-2-96 constructed in completed borehole. See Installation

WATER LEVEL (ft.)
▽ 10.0' during drilling
▼ 10.2' 1/14/97
▼ 10.1 4/15/97

O:\DwrProjImpl\Projects\Lake Michigan Chicago River Leakage Control\Final Plans\Sheet 8 9 10_e_slbrgs.dgn
1/25/2010 3:47:59 PM
Designed By TMM Checked By JJF
Drawn By TMM Checked By GMS