



<p> REINSTALL BLUESTONE PAVING (W/O UNDERLAYMENT), TYP. (SEE DETAIL 2&4 / 17)</p> <p> REINSTALL BLUESTONE PAVING (W/ UNDERLAYMENT), TYP. (SEE DETAIL 2&4 / 17)</p> <p> BENCH, TYP. (SEE DETAIL 4 / 19)</p> <p> TRASH RECEPTACLE, TYP. (SEE DETAIL 5 / 19)</p>	<p> PORTLAND CEMENT CONCRETE SIDEWALK, TYP. (SEE DETAIL 2&3 / 17) NOTE: CONCRETE TO BE PLACED FROM BACK OF CURB TO PLANTER FACE IN VOID LEFT BY REMOVING THE PLANTING STRIP, EXCEPT AS NOTED.</p> <p> PORTLAND CEMENT CONCRETE PLANTER CURB AND WALL UNDERLAYMENT, TYP. (SEE DETAIL 3 / 16) NOTE: CONCRETE PLACED FROM BACK OF CURB TO PLANTER FACE ALONG THE ENTIRE LENGTH OF THE PLANTER</p>	<p> PORTLAND CEMENT CONCRETE UNDERLAYMENT, TYP. (SEE DETAIL 2&3 / 17) NOTE: 5" THICK CONCRETE UNDERLAYMENT TO BE PLACED OVER EXISTING FOUNDATION, TYPICAL</p> <p> APPROXIMATE UTILITY VALVE LOCATION THAT NEEDS HEIGHT ADJUSTMENT NOTE: ADJUST UTILITIES ACCORDING TO VILLAGE OF WEST DUNDEE STANDARDS AND REGULATIONS.</p>
---	--	---