

**HOT MIX ASPHALT SURFACE REMOVAL SCHEDULE
(MAINLINE 1 1/4" AND 2 1/4")**

STATION	TO	STATION	LENGTH	WIDTH	HMA SURFACE REMOVAL, 1 1/4" (SQ YD) (44000154)	HMA SURFACE REMOVAL, 2 1/4" (SQ YD) (44000158)
76+02.00		76+61.81	59.81	40.00	265.82	
EQ. Sta. 76+61.81 BK = 0+00.0 AH						
0+00.00		1+85.00	185.00	40.00	822.22	
1+85.00		2+93.00	108.00	33.00	396.00	
2+93.00		31+18.60	2825.60	26.00	8,162.84	
EQ. Sta. 31+18.60 BK = 31+18.68 AH						
31+28.68		31+73.68	45.00	26.00	130.00	
OLD US 51 SOUTH						
93+70	LT	106+26	1256.00	8.00	1,116.44	
93+02	RT	106+26	1324.00	8.50	1,250.44	
OLD US 51 NORTH						
107+40	LT	108+90	150.00	9.50	158.33	
107+40	RT	108+90	150.00	9.50	158.33	
108+90	LT	110+09	119.00	5.20	68.76	
108+90	RT	110+09	119.00	5.20	68.76	
					12,598.0	
31+73.68		521+80.00	49006.32	26.00		141,573.81
EQ. Sta. 521+80.00 BK = 521+92.10 AH						
521+92.10		540+15.00	1822.90	26.00		5,266.16
540+27.00		615+60.00	7533.00	26.00		21,762.00
618+30.00		652+60.00	3430.00	26.00		9,908.89
652+90.00		704+85.00	5195.00	26.00		15,007.78
707+80.00		738+98.00	3118.00	26.00		9,007.56
739+10.00		774+37.90	3527.90	26.00		10,191.71
TOTAL					12,598.0	212,717.9

**HOT MIX ASPHALT SURFACE REMOVAL SCHEDULE
SHOULDERS (1 1/2")**

	STATION	TO	STATION	LENGTH	WIDTH LEFT	WIDTH RIGHT	HMA SURFACE REMOVAL, 1 1/2" (SQ YD) (44000155)
	21+79.00		30+76.00	897.0	3.0	3.0	598.0
CONSTITUTION DR	31+73.68		42+50.00	1,076.3	3.0	3.0	717.5
TROTTER DR	42+50.00		43+20.00	70.0	0.0	3.0	23.3
	43+20.00		56+40.00	1,320.0	3.0	3.0	880.0
1600 E	56+40.00		58+10.00	170.0	3.0	0.0	56.7
	58+10.00		113+02.00	5,492.0	3.0	3.0	3,661.3
1700 E	113+02.00		113+70.00	68.0	0.0	3.0	22.7
	113+70.00		152+75.00	3,905.0	3.0	3.0	2,603.3
1775 E	152+75.00		153+60.00	85.0	0.0	3.0	28.3
	153+60.00		166+20.00	1,260.0	3.0	3.0	840.0
1800 E	166+20.00		167+00.00	80.0	3.0	0.0	26.7
	167+00.00		221+18.00	5,418.0	3.0	3.0	3,612.0
GILLUM RD (S)	221+18.00		221+90.00	72.0	3.0	0.0	24.0
	221+90.00		223+20.00	130.0	3.0	3.0	86.7
GILLUM RD (N)	223+20.00		224+35.00	115.0	0.0	3.0	38.3
	224+35.00		274+29.00	4,994.0	3.0	3.0	3,329.3
2000 E (S)	274+29.00		275+00.00	71.0	3.0	0.0	23.7
	275+00.00		276+50.00	150.0	3.0	3.0	100.0
2000 E (N)	276+50.00		276+95.00	45.0	0.0	3.0	15.0
	276+95.00		327+92.00	5,097.0	3.0	3.0	3,398.0
2100 E (S)	327+92.00		328+81.00	89.0	3.0	0.0	29.7
	328+81.00		329+48.00	67.0	3.0	3.0	44.7

**HOT MIX ASPHALT SURFACE REMOVAL SCHEDULE
SHOULDERS (1 1/2") CONTINUED**

	STATION	TO	STATION	LENGTH	WIDTH LEFT	WIDTH RIGHT	HMA SURFACE REMOVAL, 1 1/2" (SQ YD) (44000155)
2100 E (N)	329+48.00		329+98.00	50.0	0.0	3.0	16.7
	329+98.00		382+00.00	5,202.0	3.0	3.0	3,468.0
2200 E (S)	382+00.00		382+59.00	59.0	3.0	0.0	19.7
2200 E (N)	382+59.00		383+30.00	71.0	0.0	3.0	23.7
	383+30.00		462+38.00	7,908.0	3.0	3.0	5,272.0
2350 E	462+38.00		463+00.00	62.0	0.0	0.0	0.0
	463+00.00		520+12.00	5,712.0	3.0	3.0	3,808.0
	520+12.00		520+60.00	48.0	0.0	0.0	0.0
	520+60.00		521+80.00	120.0	0.0	3.0	40.0
Eq. STA.	521+92.10		523+10.00	117.9	0.0	3.0	39.3
	523+10.00		540+08.00	1,698.0	3.0	3.0	1,132.0
SN 057-0151	540+53.00		546+89.00	636.0	3.0	3.0	424.0
	546+89.00		547+60.00	71.0	3.0	0.0	23.7
	547+60.00		547+75.00	15.0	0.0	0.0	0.0
	547+75.00		548+30.00	55.0	0.0	3.0	18.3
	548+30.00		615+40.00	6,710.0	3.0	3.0	4,473.3
SN 057-0185	618+58.00		652+55.00	3,397.0	3.0	3.0	2,264.7
SN057-0096	653+03.00		689+80.00	3,677.0	3.0	3.0	2,451.3
I-74 OMISSION	722+55.00		738+96.00	1,641.0	3.0	3.0	1,094.0
CRC RR X-ING	739+04.00		749+40.00	1,036.0	3.0	0.0	345.3
LEROY PIONEER	752+40.00		774+37.60	2,197.6	3.0	3.0	1,465.1
TOTAL				71,154.8			46,538.2