



BLR 10-6 P.C.C. PAVEMENT SPECIAL, 8"		SUB-BASE --- GRANULAR MATERIAL, TYPE A, 4"		LOCATION	CONCRETE SIDEWALK TO BE REMOVED	P.C. CONCRETE SIDEWALK 4"	LOCATION	DRIVEWAY PAVEMENT TO BE REMOVED	P.C. CONCRETE DRIVEWAY PAVEMENT, 6"
STATION TO STATION	SQ. YDS.	STATION TO STATION	SQ. YDS.						
2+30.7 - 6+25	1,394.28	2+30.7 - 6+25	1,588.56	①	1,018.16	1,260.49	⊠	50.14	37.20
SHEET TOTAL	1,394.28	SHEET TOTAL	1,588.56	②	74.36	118.46	⊠	52.33	37.24
COMBINATION CURB & GUTTER REMOVAL		COMB. CONCRETE CURB & GUTTER TYPE B6.18		③	-	620.21	⊠	-	15.33
STATION TO STATION	FT.	STATION TO STATION	FT.	④	77.44	63.09	SHT. TOTAL	102.47	89.77
2+30.7 - 5+24	368.75	2+30.7 - 6+25	807.00	⑤	40.47	45.89	INLETS TO BE REMOVED		
SHEET TOTAL	368.75	SHEET TOTAL	807.00	⑥	44.31	51.75	LOCATIONS		
PAVEMENT REMOVAL		TREE REMOVAL OVER 15 INCH		⑦	39.00	47.03	2+40.31	18.14', RIGHT	
STATION TO STATION	SQ. YDS.	STATION	IN. DIA.	TOTAL	1,293.74	2,159.89	2+76.39	17.46', LEFT	
2+30.7 - 6+25	1,293.28	3+30.7, 29.7' LT.	27				2+99.75	23.32', RIGHT	
SHEET TOTAL	1,293.28	4+78.5, 21.6' LT.	20				SHT. TOTAL	3 EACH	
		5+49.2, 25' LT.	21						
		SHEET TOTAL	68						

