INDEX OF SHEETS

STATE STANDARDS

SHEET NO.	DESCRIPTION	STANDARD NO.	DESCRIPTION
1	TITLE SHEET	000001-05	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
2	INDEX OF SHEETS, STATE STANDARDS & GENERAL NOTES	442201-03	CLASS C AND D PATCHES
3	SUMMARY OF QUANTITIES	701411-05	LANE CLOSURE, MULTILANE, AT ENTRANCE OR EXIT RAMPS, FOR SPEEDS > 45 MPH
4-5 6	EXISTING AND PROPOSED TYPICAL SECTIONS ROADWAY AND PAVEMENT MARKING PLAN	701426-03	LANE CLOSURE, MULTILANE, INTERMITTENT OR MOVING OPERATION FOR SPEEDS > 45 MPH
7	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT, BD 400-04 (BD-22)	701601-06	URBAN LANE CLOSURE, MULTILANE, 1W OR 2W WITH NONTRAVERSABLE MEDIAN
8	BUTT JOINT AND HMA TAPER, BD 400-05 (BD-32)	701901-01	TRAFFIC CONTROL DEVICES
9	SINGLE LANE WEAVE AND MULTI-LANE WEAVE, TC-09		
10-11	MULTI-LANE FREEWAY PAVEMENT MARKING DETAIL, TC-12		
-12	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING, TC-16	- NOT USED	

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "C.U.A.N." (CHICAGO UTILITY ALERT NETWORK) AT (312) 744-7000 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS UTILITIES 48 HOUR NOTIFICATION IS REQUIRED).

THE CONTRACTOR WILL NOT BE ABLE TO SET UP A YARD OR FIELD OFFICE ON STATE (OR TOLLWAY) PROPERTY WITHOUT THE WRITTEN PERMISSION OF THE DEPARTMENT (OR ISTHA).

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT) IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS UNLESS OTHERWISE SPECIFIED.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC, THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1½INCHES WHERE THE SPEED LIMIT IS 45 MPH OR LESS, AND 1 INCH WHERE THE SPEED LIMIT IS OVER 45 MPH. WITH WRITTEN APPROVAL FROM THE RESIDENT ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM OF 1:3 (V:H).

WHEN ARTIFICIAL LIGHTING IS UTILIZED IN NIGHT OPERATIONS, THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISABILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.

ALL PAVEMENT PATCHING LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES (AND RAISED REFLECTIVE PAVEMENT MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING. EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

ALL PAVEMENT MARKINGS AND RAISED REFLECTIVE PAVEMENT MARKERS OBLITERATED BY MILLING AND RESURFACING OPERATIONS ON SIDE STREETS ADN ENTRANCES SHALL BE REPLACED AND PAID FOR IN KIND.

THE RESIDENT ENGINEER SHALL CONTACT EXPRESSWAY OPERATIONS AT (847) 705-4151 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF FINAL PAVEMENT MARKINGS.

THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4155 A MINIMUM OF 72 HOURS PRIOR TO THE INSTALLATION OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.

FILE NAME =	USER NAME = mossse	DESIGNED -	REVISED	_
c:\pw_work\PWIDOT\MOSSSE\dØ104195\sh_rd		DRAWN -	REVISED	-
	PLOT SCALE = 50.0000 '/ IN.	CHECKED -	REVISED	-
	PLOT DATE = 1/27/2009	DATE -	REVISED	-

FREEWAY SHOULDER CLOSURES AND PARTIAL RAMP CLOSURES, TC-17

STATE	: OF	ILLINOIS	
DEPARTMENT	OF	TRANSPORTATION	

I-90/94 AT OHIO ST. RAMPS	F.A.I. RTE.	SEC	TION	COUNTY	TOTAL	SHEE NO.
		90/94 2008-070 RS		COOK	13	2
					NO. 6	50F68
SHEET NO. OF SHEETS STA. TO STA.	FED. R	ROAD DIST. NO. 1	ILLINOIS FED. A	ID PROJECT	***************************************	