NN SURVEYED PLOTINE BOOK ALCOWENT CHECKED RT. OF WAY CHECKED		λe	_	DATE
BOOK ALGNARD CHECKED RT. OF WAY CHECKED	FAN	SURVEYED		
NOTE BOOK ALIGNMENT CHECKED		PLOTTED		
RT. OF WAY CHECKED	HOOK :	ALIGNMENT CHECKED	-	
		RT. OF WAY CHECKED	L	
CADD FILE NAME		CADD FILE NAME		



2010 2020 2110 2500	00110	PAY ITEM	UNIT	OLIAN	ł		CONSTR	HICTION TYP	E CODE		
2010 2020 2110 2500	00110	IAITIU	I UNII	QUAN	CONSTRUCTION TYPE CODE						
2020 2110 2500				QUAIN	SFTY-1B	SFTY-1D	Y002-1C	Y003	Y030-1E	Y031	Y080
2110 2500	00100	TREE REMOVAL (6 TO 15 UNITS DIAMETER)	UNIT	30	30						
2500		EARTH EXCAVATION	CU YD	351	351						l
	01615	TOPSOIL, FURNISH AND PLACE, 4"	SQ YD	819	819						<u> </u>
2500	00400	NITROGEN FERTILIZER NUTRIENTS	POUND	10	/0						<u> </u>
2300	00500	PHOSPHORUS FERTILIZER NUTRIENTS	POUND	10	10		<u>.</u>				i
2500	00600	POTASSIUM FERTILIZER NUTRIENTS	POUND	10	10						<u> </u>
2520	00100	SODDING	SQ YD	819	819						
2520	00200	SUPPLEMENTAL WATERING	UNIT	5	5						
3110	01200	SUB-BASE GRANULAR MATERIAL, TYPE B 4"	SQ YD	1131	1131						ĺ
4020	01000	AGGREGATE FOR TEMPORARY ACCESS	TON	50	50						ĺ
4230	00300	PORTLAND CEMENT CONCRETE DRIVEWAY PAVEMENT, 7 INCH	SQ YD	7	7						1
4240	00200	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH	SQ FT	9125	9125						İ
4240	00400	PORTLAND CEMENT CONCRETE SIDEWALK 7 INCH	SQ FT	1050	1050						1
4240	00800	DETECTABLE WARNINGS	SQ FT	48	48						1
4400	00200	DRIVEWAY PAVEMENT REMOVAL	SQ YD	140	140					,	
4400	00600	SIDEWALK REMOVAL	SQ FT	335	335						1
4400	01700	COMBINATION CURB AND GUTTER REMOVAL AND REPLACEMENT	FOOT	30	30						1.
4420	01725	CLASS D PATCHES, TYPE I, 7 INCH	SQ YD	5	5						1
5650	00600	DOMESTIC WATER SERVICE BOXES TO BE ADJUSTED	EACH	2	2						1
6025	55500	MANHOLES TO BE ADJUSTED	EACH	2	2						1
6026	66600	VALVE BOXES TO BE ADJUSTED	EACH	1	1						
6710	00100	MOBILIZATION	L SUM	1	1					,	1
7010	02620	TRAFFIC CONTROL AND PROTECTION, STANDARD 701501	L SUM	1	1						1
7010	02635	TRAFFIC CONTROL AND PROTECTION, STANDARD 701701	L SUM	1	.1						1
7010	02640	TRAFFIC CONTROL AND PROTECTION, STANDARD 701801	L SUM	1	1						
* 7800	00400	THERMOPLASTIC PAVEMENT MARKING - LINE 6"	FOOT	175	175	eget/fige.		2	*		
Z006	66600	STABILIZED DRIVEWAYS 8"	SQ YD	56	56						
X440	00220	CURB REMOVAL AND REPLACEMENT	FOOT	20	20						
- F F	04848	STONE DRIVEWAY REPLACEMENT	SQ YD	31	31	1 -			44		į

GENERAL NOTES:

- UTILITIES INDICATED ON THE PLANS ARE PROVIDED FOR THE CONTRACTORS USE AND ARE BASED UPON INFORMATION AVAILABLE AT THE TIME OF THE ADVERTISEMENT FOR BIDS. THE OWNER AND ENGINEER DO NOT GUARANTEE THE ACCURACY OF UTILITIES INFORMATION.
- IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS.
- ANY REFERENCE TO STANDARDS THROUGHOUT THE PLANS OR SPECIAL PROVISIONS SHALL BE INTERPRETED TO BE THE LATEST STANDARDS OF THE ILLINOIS DEPARTMENT OF TRANSPORTATION.
- 4. THE CONTRACTOR WILL BE REQUIRED TO PROVIDE AND MAINTAIN ACCESS TO ALL PRIVATE PROPERTY DURING THE CONSTRUCTION PERIOD. THIS WORK SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE, LUMP SUM, FOR CRUSHED STONE (TEMPORARY USE). IT HAS BEEN ESTIMATED THAT 2,000 TONS OF CRUSHED STONE (TEMPORARY USE) WILL BE NEEDED FOR THIS IMPROVEMENT. THIS ESTIMATED QUANTITY IS GYEVEN FOR THE BIDDER'S INFORMATION ONLY AND THE COUNTY TAKES NO RESPONSIBILITY FOR ITS ACCURACY. THE APPLICATION SHALL CONFORM TO THE SPECIAL PROVISION FOR CRUSHED STONE (TEMPORARY USE).
- 5. SODDING: ALL DISTURBED AREAS INDICATED ON LANDSCAPING PLANS (SHEETS 75-91) TO BE SODDED, SHALL INCLUDE FERTILIZER NUTRIENTS AND SUPPLEMENTAL WATERING, SUPPLEMENTAL WATERING WHICH IS TO BE USED AFTER THE INITIAL WATERING (AS SPECIFED AND AS DIRECTED BY THE ENGINEER) SHALL BE APPLIED AT THE RATE OF 10 GALLONS PER SQUARE YARD OF SODDING. SODDED SLOPES WHICH ARE 2:1 OR STEEPER SHALL BE STAKED. PROVIDE A THREE FOOT (3') SODDED STRIP AROUND CATCH BASINS IN SEEDED AREAS.
- BEFORE ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 1-800-892-0123 FOR FIELD LOCATIONS OF BURIED UTILITIES. (48 HOUR NOTIFICATION IS REQUIRED)
- 7. THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGE OF ALSIP.
- BARRICADES: THE CONTRACTOR SHALL PROVIDE AND INSTALL TWO (2)
 WEIGHTED SANDBAGS ON EACH TYPE I OR TYPE II BARRICADE. USE
 ONE (1) WEIGHTED SAND BAG ACROSS EACH BOTTOM RAIL.
- ALL PAVEMENT, CURB AND SIDEWALK REMOVALS SHALL BE MADE BY MEANS OF STRAIGHT SAW CUT JOINT. THE COST FOR SAW CUTTING SHALL BE INCIDENTAL TO THE CONTRACT.

FILE NAME == 08294_02-QUAN-01 - IDOT P01	USER NAME = DESIGNED — TRL REVISED —			119TH STREET	F.A.	SECTION	COUNTY	TOTAL SI	SHEET	
		CHECKED TRL	REVISED	STATE OF ILLINOIS	QUANTITIES	1505	08-00085-00-SW	соок	SHEETS!	<u>.0.</u>
	PLOT SCALE = N/A	DRAWN — MJD	REVISED	DEPARTMENT OF TRANSPORTATION	ALSIP, ILLINOIS	1363 00 00 00 00		CONTRACT NO. 631		3109
	PLOT DATE = 12-16-08	CHECKED — TRL	REVISED —		SCALE: N/A SHEET NO. 2 OF 11 SHEETS STA. 1+08 TO STA. 26+08	FED. ROAD DIST.	NO. 1 ILLINOIS FED. A	ND PROJECT M-900		

* - INDICATES SPECIALTY ITEMS