

PAVEMENT MARKING SCHEDULE		
STATION	TYPE	URETHANE PAV'T
		MARK. - LINE 5"
		WHITE
S.B. RT. 335+50 TO 345+72	EDGE LINE	1,012 FT
S.B. C.L. 349+32 TO 350+32	SKIP DASH	30 FT
S.B. RT. 349+32 TO 365+00	EDGE LINE	1,568 FT
S.B. RT. 371+80 TO 378+05	EDGE LINE	625 FT
S.B. RT. 451+36 TO 456+36	EDGE LINE	500 FT
N.B. RT. 348+38 TO 377+80	EDGE LINE	2,942 FT
TOTALS		6,677 FT

MIXTURE REQUIREMENTS	
THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT	
MIXTURE USE(S):	POLY. H.M.A. S.C., MIX E, N105
AC/PG	SBS PG 70-22
DESIGN AIR VOIDS:	4.0% @ N DESIGN = 105
MIXTURE COMP:	IL 9.5 OR 12.5
FRICITION AGG:	MIX "E"

FOAM, EXPANDING POLYURETHANE, HIGH-DENSITY	
STA. 349+32 S.B.D.L.	2,500 LBS

POLYMER CONCRETE JOINT REPLACEMENT	
STA. 345+72 S.B.C.L.	2.3 CU FT
STA. 349+32 S.B.D.L. & S.B.C.L.	10.7 CU FT

NOTES:

1. STATIONS ARE APPROXIMATE.

SCHEDULES
FAI 55 (I-55)
(84-2-1, 84-2-2)D-6 PATCHING-1
SANGAMON COUNTY