

EARTH EXCAVATION		
STATION TO STATION	EARTH EXCAVATION	EARTH EXCAVATION ADJ. FOR SHRINKAGE (25%)
	CU YD	CU YD
RT. 743+70 - 805+13	473.9	355.4
LT. 806+19 - 841+18.58	272.8	204.6
RT. 839+26 - 874+43.93	243.3	182.5
LT. 875+57 - 912+94	286.0	214.5
RT. 913+59 - 960+64	351.4	263.6
LT. 961+66 - 1031+00	522.1	391.6
TOTALS	2149.5	1612.2

THE EARTH EXCAVATION GENERATED BY THE PLACEMENT OF THE HMA SHOULDER (APPROXIMATELY 2149.5 CU YD) MAY BE USED AS FURNISHED EXCAVATION REQUIRED TO MEET THE 6:1 OR FLATTER SLOPE REQUIREMENT AS SHOWN IN THE PLANS. ADDITIONAL FURNISHED EXCAVATION REQUIRED BEYOND WHAT IS PROVIDED AS SHOWN ABOVE SHALL BE PAID FOR PER ARTICLE 109.04 OF THE STANDARD SPECIFICATIONS. ANY EXCESS EARTH EXCAVATION SHALL BE DISPOSED OF BY THE CONTRACTOR PER SECTION 202 OF THE STANDARD SPECIFICATIONS.

INLET AND PIPE PROTECTION			
CENTERLINE STATION	EACH	CENTERLINE STATION	EACH
750+45	1	911+35	1
770+90	1	922+00	1
784+00	1	932+25	1
796+70	1	947+00	1
806+00	1	960+95	1
820+00	1	969+50	1
832+60	1	980+50	1
841+35	1	986+50	1
856+90	1	987+00	1
865+50	1	993+00	1
875+20	1	999+30	1
882+10	1	1005+00	1
895+00	1	1016+30	1
906+00	1	1028+00	1
SUB-TOTAL	14	SUB-TOTAL	14
TOTAL			28

STATION TO STATION	SEEDING, CLASS 2A	NITROGEN FERTILIZER NUTRIENT	PHOSPHORUS FERTILIZER NUTRIENT	POTASSIUM FERTILIZER NUTRIENT	MULCH, METHOD 1	TEMPORARY EROSION CONTROL SEEDING	MULCH, METHOD 1 (FOR TEMP. SEEDING)
	ACRE	POUND	POUND	POUND	ACRE	POUND	ACRE
RT. 743+70 - 805+13	1.13	101.7	101.7	101.7	1.13	113	1.13
LT. 806+19 - 841+18.58	0.65	58.5	58.5	58.5	0.65	65	0.65
RT. 839+26 - 874+43.93	0.64	57.6	57.6	57.6	0.64	64	0.64
LT. 875+57 - 912+94	0.69	62.1	62.1	62.1	0.69	69	0.69
RT. 913+59 - 960+64	0.87	77.4	77.4	77.4	0.87	87	0.87
LT. 961+66 - 1031+00	1.27	114.3	114.3	114.3	1.27	127	1.27
TOTALS	5.25	471.6	471.6	471.6	5.25	525	5.25