

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
*	**	***	19	9
STA. _____ TO STA. _____		FED. ROAD DIST. NO. - ILLINOIS FED. AID PROJECT		

- * FAP 322 (US 51)
- ** 09 PAVEMENT PRESERVATION FY09-2
- *** UNION COUNTY

RESURFACING SCHEDULE

LOCATION - STATION TO STATION		LENGTH	ROADWAY WIDTH	ROADWAY AREA	SHOULDER WIDTH	MICRO-SURF. SINGLE PASS, TY. 2	MICRO-SURF. SINGLE PASS, TY. 2	BIT. MATLS. (PR. CT.) (SEE NOTE 2)	FIBER-MOD. ASPHALT CRK SEAL (SEE NOTE 1)	NOTES	
		FOR INFORMATIONAL PURPOSE ONLY									
		(FT)	(FT)	(SQ YD)		(FT)	(SQ YD)	(SQ YD)	(GAL)		(FOOT)
FAP 322 (US 51)											
1000+33	TO	1005+83	550	42	2567	4.0	489	2,567	275.0	2,200	BIT. SHLDS.
1000+33	TO	1010+23	990							990	LT. TURN LN. & MEDIAN ONLY
1005+83	TO	1010+23	440	33	1613	4.0	391	1,613	180.4	1,760	BIT. SHLDS.
1010+23	TO	1028+79	1856	24	4949	4.0	1650	4,949	593.9	7,424	BIT. SHLDS.
1028+79	TO	1031+10	231	30	770	4.0	205	770	87.8	924	BIT. SHLDS.
1031+10	TO	1041+73	1063	36	4252	4.0	945	4,252	467.7	4,252	BIT. SHLDS.
1041+73	TO	1044+78	305	24	813	4.0	271	813	97.6	1,220	BIT. SHLDS.
1044+78	TO	1047+56	278	24	741	4.0	247	741	89.0	1,112	
1028+79	TO	1044+78	1599							1,599	LT. TURN LN. & MEDIAN ONLY
EQ. STA. 1047+55.55 (BK) = STA. 52+01.25 (AH)											
52+01.25	TO	103+30.75	5130	24	13,679	4.0	4560	13,679	1641.4	20,520	BIT. SHLDS.
EQ. STA. 103+30.75 (BK) = STA. 103+86.85 (AH)											
103+86.85	TO	118+04.60	1418	24	3780.7	4.0	1260	3,781	453.7	5,672	BIT. SHLDS.
EQ. STA. 118+04.60 (BK) = STA. 2018+04.60 (AH)											
2018+04.60	TO	2081+73.95	6369	24	16,985	4.0	5662	16,985	2038.2	25,477	BIT. SHLDS.
EQ. STA. 2081+73.95 (BK) = STA. 187+61.39 (AH)											
187+61.39	TO	240+04.17	5243	24	13,981	4.0	4660	13,981	1677.7	20,356	BIT. SHLDS.
EQ. STA. 240+04.17 (BK) = STA. 3040+04.17 (AH)											
3040+04.17	TO	3073+50	3346	24	8922	4.0	2974	8922	1070.7	13,383	BIT. SHLDS.
SN 091-0071 OMISSION STA. 3073+50 TO STA. 3075+71											
3075+71	TO	3101+03.20	2532	24	6753	4.0	2251	6753	810.3	10129	BIT. SHLDS.
EQ. STA. 3101+03.2 (BK) = STA. 304+62.66 (AH)											
304+62.66	TO	365+98	6135	24	16,361			16,361	1472.5	24541	
365+98	TO	378+65	1267	32	4505			4505	405.4	2534	
365+98	TO	371+98	600	8	533			533	48.0	600	TURN LANES
371+98	TO	378+65	667	16	1186			1186	106.7	667	TURN LANES
304+63	TO	365+98	6135			4.0	5453		490.8	12270	4' BIT. SHLDS.
365+98	TO	378+65	1267			6.0	1689		47.1	2534	6' BIT. SHLDS.
SUB TOTALS											
TOTALS											
							32,707	102,391	12054	160,165	
							135,098				

Note 1: Fiber-Mod. Asphalt Cr. Seal is calculated using 1 lb. of material per 2.8 lineal foot. Four (4) strips on US 51 locations through the length of the project and one (1) strip through median-left turn areas, unless otherwise noted on plans.

Note 2: Bituminous Materials (Prime Coat) quantity includes shoulder and pavement area.