



GENERAL NOTES

- Build tops of headwalls parallel to grade line.
- * If embankment slope above headwall is flatter than 1:2, provide wings for 1:2 slope.
- When lapping sheets of welded wire fabric, the overlap measured between the outermost cross wires of each fabric sheet shall not be less than 202 mm (8").
- All slope ratios are expressed as units of vertical displacement to units of horizontal displacement (V:H).
- All dimensions are in millimeters (inches) unless otherwise shown.

END SECTION DIMENSIONS

LOCATION		CULVERT SKEW ANGLE			CULVERT		A	B	C	D	E	F	G	H	J	K	M	N	SKEW			2-END SECTIONS		
ROADWAY	STA	D	M	S	DIRECTION	TYPE	DIAMETER												D	M	S	CONCRETE (CU YD)	WIRE FABRIC (SQ YD)	
IL RTE 336	779+70	36	40	0	LT AHD	RCCP	66"	8'-1"	3'-0"	7'-0 1/2"	8'-2 1/2"	29'-1 1/2"	17'-8 1/2"	9'-0 1/2"	6'-7"	14'-4"	14'-9 1/2"	0'-4 3/4"	0'-2"	36	40	00	23.0	196
1350N (CH 14)	2019+75	30	0	0	LT AHD	RCCP	66"	7'-9"	3'-2"	7'-0 1/2"	7'-7 1/4"	26'-5"	15'-4"	8'-11 1/4"	6'-7"	13'-1 1/4"	13'-3 3/4"	0'-4 1/2"	0'-2 1/4"	30	00	00	19.9	173