

POLYMERIZED BITUMINOUS MATERIALS (PRIME COAT) RATES

Surface Type	Estimated Truck Application Rate	Residual Rate
Milled (HMA or PCC)	0.08 gal/sy (0.00034 ton/sy)	0.04 gal/sy
Existing Pavement	0.05 gal/sy (0.00022 ton/sy)	0.025 gal/sy
Fog Coat (between lifts)	0.05 gal/sy (0.00022 ton/sy)	0.025 gal/sy

Note: Estimated truck application rate is used for estimating quantities.

HOT-MIX ASPHALT MIXTURE REQUIREMENTS

Mixture Use(s):	POLYMER SURFACE COURSE 2"	BINDER COURSE 8.5"	HMA SHOULDER (SURFACE LIFT)	HMA SHOULDER (LOWER LIFTS)
RAP % (Max):	SBS OR SBR 70-22	PG 64-22	PG 64-22	PG 64-22
AC/PC:	10%	25%	15%	25%
Design Air Voids:	4.0% @ N=50	4.0% @ N=50	3.0% @ N=50	4.0% @ N=50
Mixture Composition: (Gradation Mixture)	IL 9.5 OR IL 12.5	IL 19.0	IL 9.5 OR 12.5	IL 19.0
Friction Aggregate	MIXTURE E	N/A	MIXTURE C	N/A

Notes: Individual lift thickness of each mix type will be no less than 3 times nominal maximum aggregate size and no more than 6 times nominal aggregate size.

ORDERING LENGTH CONFIRMATION – DRAINAGE ITEMS

The Contractor shall consult with the Engineer in regard to the exact length of the box/pipe culverts, storm sewers, and/or pipe drains required prior to ordering these items.

ENGINEERS FIELD OFFICE

Add the following sentence to the end of paragraph 670.02 (i) and 670.04 (e):
All of the telephone lines provided shall have unpublished numbers.

COMMITMENTS

Commitments are not to be altered without the written approval of all parties to which the commitment was made.

No Commitments have been made for this project.

FILE NAME : D:\60471\shp\plan.dgn	USER NAME : kerdhor	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	GENERAL NOTES/COMMITMENTS	F.A.P. RTE. 669	SECTION 11R1W-1	COUNTY PEORIA	TOTAL SHEETS 33	SHEET NO. 3
	PLOT SCALE : 200.0000' / in.	CHECKED -	REVISED -			CONTRACT NO. 68A71				
	PLOT DATE : 12/12/2012	DATE -	REVISED -			ILLINOIS FED. AID PROJECT				
SCALE: SHEET OF SHEETS STA. TO STA.										