

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
D-2	OVD SIN STR REPL 18-32	VARIOUS	38 +	1
ILLINOIS CONTRACT NO. 46470				

* 38 + 2 = 40 TOTAL SHEETS

INDEX OF SHEETS

- 1 COVER SHEET, INDEX OF SHEETS & STATE STANDARDS
- 2 SUMMARY OF QUANTITIES
- 3-9 OVERHEAD SIGN STRUCTURE DETAILS
- 10-15 CANTILEVER SIGN STRUCTURE DETAILS
- 16 PLAN VIEW SN 002
- 17 PLAN VIEW SN 053
- 18 PLAN VIEW SN 136
- 19 PLAN VIEW SN 170 & SN 172
- 20 SIGN STRUCTURE REPLACEMENT, SIGN PANEL REPORT - SN 002
- 21 SIGN STRUCTURE REPLACEMENT, SIGN PANEL REPORT - SN 053
- 22 SIGN STRUCTURE REPLACEMENT, SIGN PANEL REPORT - SN 136
- 23-24 SIGN STRUCTURE REPLACEMENT, SIGN PANEL REPORT - SN 170
- 25 SIGN STRUCTURE REPLACEMENT, SIGN PANEL REPORT - SN 172
- 26 BORING LOGS - SN 002
- 27 BORING LOGS - SN 053
- 28 BORING LOGS - SN 136
- 29 BORING LOGS - SN 170 & 171
- 30 BORING LOGS - SN 172
- 31-32 GUARDRAIL CALCULATIONS - SN 002
- 33-35 GUARDRAIL CALCULATIONS - SN 053
- 36-38 GUARDRAIL CALCULATIONS - SN 136

PROPOSED HIGHWAY PLANS

VARIOUS ROUTES
SECTION: D-2 OVD SIN STR REPL 18-32
TYPE of IMPROVEMENT: SIGN STRUCTURE
REPLACEMENT
VARIOUS




STATE STANDARDS

- 630001-12 STEEL PLATE BEAM GUARDRAIL
- 630101-10 STRONG POST GUARDRAIL ATTACHED TO CULVERT
- 630301-09 SHOULDER WIDENING FOR TYPE 1 (SPECIAL) GUARDRAIL TERMINALS
- 631011-10 TRAFFIC BARRIER TERMINAL, TYPE 2
- 701006-05 OFF-RD OPERATIONS, 2L, 2W, 15'(4.5m) TO 24'(600mm) FROM PAVEMENT EDGE
- 701101-05 OFF-RD OPERATIONS, MULTILANE, 15'(4.5m) TO 24'(600mm) FROM PAVEMENT EDGE
- 701106-02 OFF-RD OPERATIONS, MULTILANE, MORE THAN 15'(4.5m) AWAY
- 701400-09 APPROACH TO LANE CLOSURE, FREEWAY/EXPRESS
- 701401-12 LANE CLOSURE, FREEWAY/EXPRESSWAY
- 701406-12 LANE CLOSURE, FREEWAY/EXPRESSWAY, DAY OPERATIONS ONLY
- 701411-09 LANE CLOSURE, MULTILANE, AT ENTRANCE OR EXIT RAMP, FOR SPEEDS > 45 MPH
- 701421-08 LANE CLOSURE, MULTILANE, DAY OPERATIONS ONLY, FOR SPEEDS > 45 MPH TO 55 MPH
- 701422-10 LANE CLOSURE, MULTILANE, FOR SPEEDS > 45 MPH TO 55 MPH
- 701901-08 TRAFFIC CONTROL DEVICES
- 701456-05 PARTIAL EXIT RAMP CLOSURE FREEWAY / EXPRESSWAY



FULL SIZE PLANS HAVE BEEN PREPARED USING STANDARD ENGINEERING SCALES. REDUCED SIZED PLANS WILL NOT CONFORM TO STANDARD SCALES. IN MAKING MEASUREMENTS ON REDUCED PLANS, THE ABOVE SCALES MAY BE USED.

J.U.L.I.E.
JOINT UTILITY LOCATION INFORMATION FOR EXCAVATION
1-800-892-0123
OR 811



M-60-005-18

PROJECT ENGINEER: MAHMOUD ETEMADI (815) 284-5393

CONTRACT NO. 46470

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SUBMITTED 9-24-18
R. Mankie
REGIONAL ENGINEER

Dec 7 2018
Dr. E. A. ETC
ENGINEER OF DESIGN AND ENVIRONMENT

Dec 7 2018
Paul P. [Signature]
DIRECTOR OF HIGHWAYS PROJECT IMPLEMENTATION

PRINTED BY THE AUTHORITY
OF THE STATE OF ILLINOIS

SUMMARY OF QUANTITIES

100%
State Funds

CODE NUMBER	ITEM	UNIT	SN 002	SN 053	SN 136	SN 170	SN 172	TOTAL QUANTITY 0021
			2S101U020R009.9	2S081SI088L000.0	2S081SI280L011.3	2S101S251R010.4	2C101S251R010.6	
* 51604000	DRILLED SHAFT IN ROCK	CU YD	2					2
* 63000003	STEEL PLATE BEAM GUARDRAIL, TYPE A, 9 FOOT POSTS	FOOT	468	447	314			1229
* 63100167	TRAFFIC BARRIER TERMINAL, TYPE 1	EACH	2	3	3			8
63200310	GUARDRAIL REMOVAL	FOOT	200		140			340
64300750	IMPACT ATTENUATORS (SEVER USE, NARROW), TEST LEVEL 2	EACH				2		2
67100100	MOBILIZATION	L SUM	0.20	0.20	0.20	0.20	0.20	1
70200100	NIGHTTIME WORK ZONE LIGHTING	L SUM	0.25	0.25	0.25	0.25		1
* 72000300	SIGN PANEL - TYPE 3	SQ FT	331	336	422	304	78	1471
* 72501000	TERMINAL MARKER - DIRECT APPLIED	EACH	3	2	2	2	1	10
73300200	OVERHEAD SIGN STRUCTURE - SPAN, TYPE II-A (4'-6" X 5'-3")	FOOT	117	103.5	114	130		464.5
73302170	OVERHEAD SIGN STRUCTURE - CANTILEVER, TYPE II-C-A (36" X 5'-6")	FOOT					28	28
* 73400200	DRILLED SHAFT CONCRETE FOUNDATIONS	CU YD	33	24.9	29.6	31.2	9	127.7
73600100	REMOVE OVERHEAD SIGN STRUCTURE - SPAN	EACH	1	1	1	1		4
73600200	REMOVE OVERHEAD SIGN STRUCTURE - CANTILEVER	EACH					1	1
73700300	REMOVE CONCRETE FOUNDATION - OVERHEAD	EACH	1	1	1	1	1	5
* 78200005	GUARDRAIL REFLECTOR, TYPE A	EACH	2	2	2	2	1	9
* X0325265	REMOVE ELECTRIC SERVICE	EACH	1	1	1	1	1	5
X7010216	TRAFFIC CONTROL AND PROTECTION (SPECIAL)	L SUM	0.20	0.20	0.20	0.20	0.20	1
X7010410	SPEED DISPLAY TRAILER	CAL MO	1	1	1	1		4
70107025	CHANGEABLE MESSAGE SIGN	CAL DA	7	7	7	7		28
Z0013798	CONSTRUCTION LAYOUT	L SUM	0.20	0.20	0.20	0.20	0.20	1
Z0048665	RAILROAD LIABILITY INSURANCE	L SUM				1		1

FILE NAME =	USER NAME = dssdd	DESIGNED -	REVISED -
pw:\IL084EBID\INTEG.illinois.gov\PMDOT\Documents\DOT Offices\District 2\Projects\Operations\Bridge Section\Winnebago\46470\SLT200117-2\Design Files\46470-sht-cole		CHECKED -	REVISED -
Default	PLOT SCALE = 100.0000' / in.	DATE -	REVISED -
	PLOT DATE = Sep-26-2018 09:39:25 AM		

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**SUMMARY OF
QUANTITIES**

SCALE: _____ SHEET ____ OF ____ SHEETS STA. _____ TO STA. _____

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	D-2 OVD SIN STR REPL 18-32	VARIOUS	40	2
CONTRACT NO. 46470				
ILLINOIS FED. AID PROJECT				

* = SPECIALTY ITEM

GENERAL NOTES

DESIGN: AASHTO Standard Specifications for Structural Supports for Highway Signs, Luminaires and Traffic Signals. ("AASHTO Specifications")

CONSTRUCTION: Current (at time of letting) Illinois Department of Transportation Standard Specifications for Road and Bridge Construction, Supplemental Specifications and Special Provisions. ("Standard Specifications")

LOADING: 90 M.P.H. WIND VELOCITY

WALKWAY LOADING: Dead load plus 500 lbs. concentrated live load.

DESIGN STRESSES:
Field Units
f'c = 3,500 p.s.i.
fy = 60,000 p.s.i. (reinforcement)

WELDING: All welds to be continuous unless otherwise shown. All welding to be done in accordance with current AWS D1.1 and D1.2 Structural Welding Codes (Steel and Aluminum) and the Standard Specifications.

MATERIALS: Aluminum Alloys as shown throughout plans. All Structural Steel Pipe shall be ASTM A53 Grade B or A500 Grade B or C. If A500 pipe is substituted for A53, then the outside diameter shall be as detailed and wall thickness greater than or equal to A53. All Structural Steel Plates and Shapes shall conform to AASHTO M270 Gr. 36, Gr. 50 or Gr. 50W*. Stainless steel for shims, sleeves and handhole covers shall be ASTM A240, Type 302 or 304, or another alloy suitable for exterior exposure and acceptable to the Engineer.

The steel pipe and stiffening ribs at the base plate for the column shall have a minimum longitudinal Charpy V-Notch (CVN) energy of 15 lb.-ft. at 40° F. (Zone 2) before galvanizing.

FASTENERS FOR ALUMINUM TRUSSES: All bolts noted as "high strength" must satisfy the requirements of AASHTO M164 (ASTM A325), or approved alternate, and must have matching lock nuts. Threaded studs for splices (if Members interfere) must satisfy the requirements of ASTM A449, ASTM A193, Grade B7, or approved alternate, and must have matching lock nuts. Bolts and lock nuts not required to be high strength must satisfy the requirements of ASTM A307. All bolts and lock nuts must be hot dip galvanized per AASHTO M232. The lock nuts must have nylon or steel inserts. A stainless steel flat washer conforming to ASTM A240 Type 302 or 304, is required under both head and nut or under both nuts where threaded studs are used. High strength bolt installation shall conform to Article 505.04 (f) (2)d of the IDOT Standard Specifications for Road and Bridge Construction. Rotational capacity ("ROCAP") testing of bolts will not be required.

U-BOLTS AND EYEBOLTS: U-Bolts and Eyebolts must be produced from ASTM A276 Type 304, 304L, 316 or 316L, Condition A, cold finished stainless steel, or an equivalent material acceptable to the Engineer. All nuts for U-Bolts and Eyebolts must be lock nuts equivalent to ASTM A307 with nylon or steel inserts and hot dip galvanized per AASHTO M232. A stainless steel flat washer conforming to ASTM A240, Type 302 or 304, is required under each U-Bolt and Eyebolt lock nut.

GALVANIZING: All Steel Grating, Plates, Shapes and Pipe shall be Hot Dip Galvanized after fabrication in accordance with AASHTO M111. Painting is not permitted.

ANCHOR RODS: Shall conform to ASTM F1554 Gr. 105.



CONCRETE SURFACES: All concrete surfaces above an elevation 6" below the lowest final ground line at each foundation shall be cleaned and coated with Concrete Sealer in accordance with the Standard Specifications.

REINFORCEMENT BARS: Reinforcement Bars designated (E) shall be epoxy coated in accordance with the Standard Specifications.

FOUNDATIONS: The contract unit price for Concrete Foundations and Drilled Shaft Concrete Foundations shall include reinforcement bars complete in place.

TOTAL BILL OF MATERIAL

ITEM	UNIT	TOTAL
OVERHEAD SIGN STRUCTURE SPAN TYPE I-A	Foot	
OVERHEAD SIGN STRUCTURE SPAN TYPE II-A	Foot	464.5
OVERHEAD SIGN STRUCTURE SPAN TYPE III-A	Foot	
OVERHEAD SIGN STRUCTURE WALKWAY TYPE A	Foot	
CONCRETE FOUNDATIONS	Cu. Yds.	
DRILLED SHAFT CONCRETE FOUNDATIONS	Cu. Yds.	118.7
ROCK EXCAVATION	Cu. Yds.	2.0




TYPICAL ELEVATION
(Looking at Face of Signs**)

Elev. A = Elevation at point of minimum clearance to sign, walkway support or truss.

Structure Number	Station	Design Truss Type	c. to c. Supports	Elev. A	Dim. D	Height of Tallest Sign	Total Sign Area
002	87+00	II-A	117	820.47	24	10	331.0
053	98+00	II-A	103.5	579.90	25.4	9	335.5
136	118+50	II-A	114	569.00	32	11.5	422.0
170	87+00	II-A	130	716.54	13	7	303.5

**Looking upstation for structures with signs both sides.

* If M270 Gr. 50W (M222) steel is proposed, chemistry for plate to be used shall first be approved by the Engineer as suitable for galvanizing and welding.



DESIGN WIND LOADING DIAGRAM

Parameters shown are basis for I.D.O.T. Standards and Sign Manual Tables. Installations not within dimensional limits shown require special analysis for all components.

05-A-1 2-17-2017






FILE NAME =	USER NAME = dossed	DESIGNED -	REVISED -
pw:\IL\084EBIDINTEG\illinois.gov\PIDOT\Documents\IDOT Offices\District 2\Projects\Open Bridge Section\Winnebago\Contract\REVISED\2017-2\Design Files\46470-shr\cover.dgn			
PLOT SCALE = 100.0000' / in.	CHECKED -	REVISED -	
PLOT DATE = Nov-27-2018 09:30:04 AM	DATE -	REVISED -	

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**OVERHEAD SIGN STRUCTURES - GENERAL PLAN &
ELEVATION - ALUMINUM TRUSS & STEEL SUPPORTS**

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	D-2 OVD SIN STR REPL 18-32	VARIOUS	40	3
CONTRACT NO.			46470	
ILLINOIS FED. AID PROJECT				

SCALE: _____ SHEET _____ OF _____ SHEETS STA. _____ TO STA. _____



- ① Contractor may alternatively use standard aluminum drive-fit cap to close end. 1/2" Ø drain hole in end plate/drive-fit cap. (Typ. at ends of all chords)
- ② 5 1/2" end dimension may vary by ±1" to provide uniform panel spacing (P).
- ③ Panel spacing (P) shall be uniform for entire truss and between 4'-0" and 5'-0" for Type I-A or 4'-0" and 5'-6" for Types II-A and III-A.
- ④ Vertical Diagonals in front and back face shall alternate.
- ⑤ Hidden lines show wind bracing alternates direction between planes of top and bottom chords.
- ⑥ All diagonals shall be detailed for minimum offset from the panel point based on the following: Offset shall be such as to provide a 3/4" minimum to 1 1/2" maximum clearance between any diagonal and any horizontal or vertical member, and to provide clearance for U-bolt connections of signs or walkway brackets.

0S-A-2 2-17-2017

FILE NAME =	USER NAME = dssdd	DESIGNED -	REVISED -
p:\11\084EBID\INTEG\illinois.gov\PWIDOT\Documents\DOT Offices\District 2\Projects\Open Bridge\ridge-Section\Winnegago\Contract\REVISED\200117-2\Design Files\46470-sheetcover.dgn		DRAWN -	REVISED -
PLOT SCALE = 100.0000' / 1"	CHECKED -	REVISED -	REVISED -
Default	PLOT DATE = Sep-25-2018 08:32:54 AM	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


OVERHEAD SIGN STRUCTURES - ALUMINUM TRUSS
DETAILS FOR TRUSS TYPES I-A, II-A AND III-A

SCALE: _____ SHEET _____ OF _____ SHEETS STA. _____ TO STA. _____


F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
D-2 OVD SIN STR REPL 18-32		VARIOUS	40	4
CONTRACT NO. 46470			ILLINOIS FED. AID PROJECT	

TRUSS UNIT TABLE


Structure Number	Station	Design Truss Type	Exterior Units (2)			Interior Unit				Upper & Lower Chord		Verticals; Horizontals; Vertical, Horizontal, and Interior Diagonals		Camber at Midspan	Splicing Flange					
			No. Panels per Unit	Unit Lgth.(Le)	Panel Lgth.(P)	No. Req'd.	No. Panels per Unit	Unit Lgth.(Li)	Panel Lgth.(P)	O.D.	Wall	O.D.	Wall		Bolts		Weld Sizes		A	B
															No./Splice	Dia.	W	W1		
002	87+00	II-A	8	39'-8 1/2"	4'-8 3/4"	1	8	39'-1"	4'-8 3/4"	7"	5/16"	3"	5/16"	4	6	1"	3/8"	1/4"	11 1/2"	15"
053	98+00	II-A	7	37'-0 1/4"	5'-0 1/4"	1	6	31'-4 1/2"	5'-0 1/4"	6 1/2"	5/16"	3"	5/16"	3.5	6	1"	3/8"	1/4"	11"	14 1/2"
136	118+50	II-A	8	38'-8 1/2"	4'-7 1/4"	1	8	38'-1"	4'-7 1/4"	7"	5/16"	3"	5/16"	3.8	6	1"	3/8"	1/4"	11 1/2"	15"
170	87+00	II-A	6	33'-3"	5'-2 3/4"	2	6	32'-7 1/2"	5'-2 3/4"	7"	3/8"	3"	5/16"	4.75	8	1"	7/16"	5/16"	11 1/2"	15"



① Splicing Flanges shall be attached to each truss unit with the truss shop assembled to camber shown. Truss units shall be in proper alignment and flange surfaces shall be shop bolted into full contact before welding. Sufficient external welds or tacks shall be made to secure flanges until remaining welds are made after disassembly. Adjacent flanges shall be "match marked" to insure proper field assembly.




Note: Units shall be shipped individually with adequate provision to prevent detrimental motion during transport. This may require ropes between horizontals and diagonals or energy dissipating (elastic) ties to the vehicle. The Contractor is responsible for maintaining the configuration and protection of the units.




Camber curve shown is theoretical. Actual camber attained by slope changes at splices between units.


CAMBER ATTAINMENT EXAMPLES:



Camber shown is for fabrication only, measured with truss fully supported. (No-load condition)



TRUSS TYPES I-A, II-A, & III-A



TRUSS TYPES II-A & III-A
SPLICING FLANGES

ASTM B221, Alloy 6061-T6 or ASTM B209, Alloy 6061-T651
*To fit O.D. of Chord with maximum gap of 1/16".

054-A-2

2-17-2017

FILE NAME =	USER NAME = dossed	DESIGNED -	REVISED -
pw:\11\084EBIDINTEG.illinois.gov\PIWIDOT\Documents\DOT Offices\District 2\Projects\Ope	BRWN	BRWN	REVISED 2011-11-2\Design Files\46470-sh
PLOT SCALE = 100.0000' / 1".	CHECKED -	REVIS	REVISED -
PLOT DATE = Nov-27-2018 09:36:20 AM	DATE -	REVIS	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**OVERHEAD SIGN STRUCTURES - ALUMINUM TRUSS DETAILS
FOR TRUSS TYPES I-A, II-A AND III-A**


SCALE: _____ SHEET _____ OF _____ SHEETS STA. _____ TO STA. _____

F.A. RTÉ.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	D-2 OVD SIN STR REPL 18-32	VARIOUS	40	5
			CONTRACT NO.	46470
ILLINOIS FED. AID PROJECT				


5/16" Ø stainless steel
U- bolt with hot dip galvanized
locknuts and stainless steel washers,
typ. 3/8" Ø holes in 2 1/2" Ø tube



PLAN DETAIL "A"
☐ Span between Panel Points



PLAN DETAIL "B"
☐ Span at Panel Point




PLAN DETAIL "C"
☐ Span at ☐ Chord Splice

* Center of horizontal to center of
splice dimension may vary. Verify
before drilling holes in mounting tube.


NOTES

Damper: One damper per truss. (31 lbs. minimum Stockbridge-Type
Aluminum - 29" minimum between ends of weights) Cost
included in Overhead Sign Structure...


Materials: Materials: Aluminum tubes shall be ASTM B221 alloy 6061
temper T6. Cost included in Overhead Sign Structure...



SECTION A-A




SECTION B-B




SECTION C-C


5/16" Ø stainless steel
U- bolt with hot dip galvanized
locknuts and stainless steel washers,
typ. 3/8" Ø holes in mounting tube




**TRUSS DAMPING
DEVICE CONNECTION DETAIL**
(Typical)



**DAMPING DEVICE MOUNTING
TUBE U-BOLT DETAIL**
(Typical)



**TOP CHORD TO CROSS TUBE
U-BOLT DETAIL**
(Typical - Detail "A" and "B")



ELEVATION
Aluminum Overhead
Sign Truss

0S-A-D

2-17-2017

FILE NAME =	USER NAME = dossed	DESIGNED -	REVISED -
pw:\IL\084EBIDINTEG\illinois.gov\PWIDOT\Documents\DOT Offices\District 2\Projects\Open Bridge\Section\Winnabago\Contract\REVISED 2011-7-2\Design Files\46470-sheet cover.dgn			
PLOT SCALE = 100.0000' / in.	CHECKED -	REVISED -	
PLOT DATE = Sep-25-2018 08:33:11 AM	DATE -	REVISED -	


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**OVERHEAD SIGN STRUCTURE
DAMPING DEVICE**


SCALE: _____ SHEET _____ OF _____ SHEETS STA. _____ TO STA. _____

F.A. RTÉ.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	D-2 OVD SIN STR REPL 18-32	VARIOUS	40	6
CONTRACT NO. 46470			ILLINOIS FED. AID PROJECT	

3/4" Ø stainless steel U-bolt.
Provide two washers and two hexagon locknuts. (4)
1 3/16" x 2" slots on 10" Ø pipe.
(4 slots required per pipe)




DETAIL A




SECTION A-A

As an alternate to bolts, may use galvanized drive-fit caps installed after galvanizing frame.



SECTION B-B



For Foundation Details, see base sheet OS-F3 (Spread Footing) or OS4-F3 (Drilled Shaft).

SIDE ELEVATION


Truss Type	Dimensions							
	R	S	T	U	V	W	X	Y
I-A	4'-6"	5'-5 1/2"	4'-0"	5'-6"	6'-4 3/4"	4"	9"	8'-3"
II-A (5)	5'-3"	6'-3 1/4"	4'-6"	6'-1"	6'-11 3/4"	4 3/4"	9 1/2"	8'-3"

10" Ø PIPE TRUSS SUPPORT FRAME

** One butt welded joint is allowed only on one post per support frame. If used, weld procedure must be pre-approved by Engineer and joint shall receive 100% RT or UT (tension criteria) at Contractor's expense.

HANDHOLE COVERS

UPPER LOWER



DETAIL D

Backfill shall be placed prior to erection of support frame

Support Design Loads: See Base Sheet OS-A-1 for design and loading criteria.
Load combinations checked include deadload plus:
a) 100% wind normal to sign, 20% parallel to sign
b) 60% wind normal to sign, 30% parallel to sign

- In lieu of fabricated handhole frame as shown, may cut from 2" plate (rolling direction vertical). All cut faces to be ground to ANSI Roughness of 500µ in or less.
- Galvanizing vent holes of adequate size shall be provided on underside at each end of bracing pipes. Alternately, holes may be provided in wall of pipe column. All vent holes shall be drilled and de-burred, typ.
- Steel pipe, plate, carbon steel handhole covers and rolled sections shall be hot dip galvanized after fabrication. Painting is not permitted. See Base Sheet OS-A-1.
- See General Notes for fasteners.
- Dimensions shown are based on selection criteria in the Sign Structures Manual. Nonstandard applications must have dimensions verified or amended as appropriate.
- "H" based on 15'-0" or actual sign height, whichever is greater.

END ELEVATION

Structure Number	Station	Support		Truss Type	Pipe Wall Thickness	H (6)	A	
		Left	Right					
002	2S101U020R009.9	87+00	X		II-A	.50	32.04	24.65
002	2S101U020R009.9	87+00		X	II-A	.50	32.09	24.70
053	2S081S1088L000.0	98+00	X	X	II-A	.50	29.55	22.21
053	2S081S1088L000.0	98+00	X		II-A	.50	27.81	20.48
136	2S081I280L011.3	118+50		X	II-A	.50	30.19	22.79
136	2S081I280L011.3	118+50	X		II-A	.50	28.68	21.29
170	2S101S251R010.4	87+00	X		II-A	.50	26.37	18.98
170	2S101S251R010.4	87+00		X	II-A	.50	26.37	18.98

OS-A-6 2-17-2017

FILE NAME =	USER NAME = dossdd	DESIGNED -	REVISED -
pw\1\084EBIDINTEG\illinois.gov\PIWIDOT\Documents\DOT Offices\District 2\Projects\Open Bridge-Section\Winnebago\Contract\REVISED\2011\17-2\Design Files\46470-sheet cover.dgn		CHECKED -	REVISED -
PLOT SCALE = 100.0000' / in.		DATE -	REVISED -
Default	PLOT DATE = Nov-27-2018 09:38:29 AM		


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

OVERHEAD SIGN STRUCTURES
SUPPORT FRAME FOR ALUMINUM TRUSS

SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	D-2 OVD SIN STR REPL 18-32	VARIOUS	40	7
CONTRACT NO. 46470			ILLINOIS FED. AID PROJECT	


Hexagon locknut and washer (top), leveling nut and washer (bottom). Galvanize per AASHTO M232. Nuts shall each be tightened against base plate with 200 lb.-ft. minimum torque.




DETAIL B

Ribs shall be cut to fit slope of pipe.

Stainless Steel Standard Grade Wire Cloth, 3" wide, 1/4" maximum opening with a minimum wire diameter of AWG. No. 16 with a minimum 2" lap. Secure to base plate after erection with 3/4" stainless steel banding.




SECTION B-B



SECTION D-D

** Alternate detail if welding col. to base plate first, then snip inside corner of ribs. Terminate weld on rib 1/4" from snip.


No snip req'd. at rib inside corner if placed before col. to base plate welding.**



SADDLE SHIM DETAIL


ASTM B26 Alloy 356-F or ASTM B209 Alloy 6061-T651 (4 required per sign truss)

Truss Chord Nominal Dia.	a
5"	3/4"
5 1/2"	1 3/16"
6"	7/8"
6 1/2"	1 5/16"
7"	1"





SECTION C-C


(Handhole cover not shown)



DETAIL C




ANCHOR ROD DETAIL
Spread Footing Foundation



POSITIONING PLATE(S)

At each location, provide 1/4" thick positioning plate(s) and six (6) additional nuts to be used with leveling nuts to maintain anchor bolts position during concrete placement.



ANCHOR ROD DETAIL
Drilled Shaft Foundation

Anchor rods shall conform to ASTM F1554 Grade 105. Galvanize upper 12" minimum per AASHTO M232. No welding shall be permitted on rods.

10" Ø PIPE SUPPORT FRAME DETAILS

05-A-6A

2-17-2017

FILE NAME =	USER NAME = dossdd	DESIGNED -	REVISED -
pw:\11084EBIDINTEG\illinois.gov\PIWIDOT\Documents\DOT Offices\District 2\Projects\Open Road\Bridges\Section\Winnabago\Contract\REVISED\2017-2\Design Files\46470-shr\cover.dgn			
PLOT SCALE = 100.0000' / in.	CHECKED -	REVISED -	
PLOT DATE = Sep-25-2018 08:33:27 AM	DATE -	REVISED -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

OVERHEAD SIGN STRUCTURES	
SUPPORT FRAME DETAILS - ALUMINUM TRUSS	
SCALE: _____	SHEET _____ OF _____ SHEETS STA. _____ TO STA. _____

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
D-2 OVD SIN STR REPL 18-32		VARIOUS	40	8
CONTRACT NO. 46470			ILLINOIS FED. AID PROJECT	

BAR LIST - EACH FOUNDATION

Bar	Number	Size	Length	Shape
v4(E)	24	#9	F less 5"	—
#4 bar spiral (E) - see Side Elevation				

NOTES:

The foundation dimensions shown are based on the presence of mostly cohesive soils with an average Unconfined Compressive Strength (Qu) of at least 1.25 tsf, which must be determined by previous soil investigations at the jobsite. When other conditions are indicated, the boring data will be included in the plans and the foundation dimensions shown will be the result of site specific designs.


If the conditions encountered are different than those indicated, the Contractor shall notify the Engineer to determine if the foundation dimensions need to be modified. If dimensions "B" or "F" are revised by more than 12" by the Contractor, "as-built" plans shall be prepared and submitted to the District Bureau of Operations for future reference.

No sonotubes or decomposable forms shall be used below the lower conduit entrance. Permanent metal forms or other shielding may not be left in place below that elevation without the Engineer's written permission.

Concrete shall be placed monolithically, without construction joints.

Backfill shall be placed per Article 502 of Standard Specification and prior to erection of support column.

A normal surface finish followed by a Concrete Sealer application will be required on concrete surfaces above the lowest elevation 6" below finished ground line. Cost included in Drilled Shaft Concrete Foundation.




SIDE ELEVATION

END VIEW

3 hoops minimum top and bottom

Approved clamps for grounding*
#6 copper wire or cable
3/4" Ø x 10'-0" copper weld ground rod driven into ground 9'-0". Cost of rod, cable, conduit, caps and clamps shall be included in Drilled Shaft Concrete Foundations.


3" Ø Galvanized Steel Conduit. Thread and cap both ends.



SECTION A-A

For anchor rod size and placement, see Support Frame Detail Sheet.

* Anchor rod shall be ground or filed to bright metal at clamp and cable connection location.



PLAN

**DETAILS FOR 10" Ø SUPPORT FRAME
TYPE I-A or II-A TRUSS**

Structure Number	Station			Left Foundation			Right Foundation			Class DS Concrete (Cu. Yds.)			
		Elevation Top	Elevation Bottom	A	B	F	Elevation Top	Elevation Bottom	A		B	F	
002	2S101U020R009.9	87+00	816.26	784.76	3.5	28.0	31.50	816.21	784.71	3.5	28.0	31.50	*33.0
053	2S081S1088L000.0	98+00	579.92	556.92	2.5	20.5	23.00	578.18	553.68	4.0	20.5	24.50	24.9
136	2S081I280L011.3	118+50	568.15	540.65	2.5	25.0	27.50	566.65	537.65	4.0	25.0	29.00	29.6
170	2S101S251R010.4	87+00	718.00	688.00	3.0	27.0	30.00	718.00	688.50	2.5	27.0	29.50	31.2

* = +2 CU YD OF ROCK EXCAVATION

054-F3


2-17-2017

FILE NAME =	USER NAME = dosddd	DESIGNED -	REVISED -
pw:\11\084EBIDINTEG.illinois.gov\PIDOT\Documents\DOT Offices\District 2\Projects\Ope	DRAWN	BRIDGE-SECTION\Winnebago\Contract	REVISED 2011-7-2\Design Files\46470-sh
PLOT SCALE = 100.0000' / 1"	CHECKED -	REVIS	REVIS
Default	PLOT DATE = Nov-27-2018 09:37:14 AM	DATE -	REVIS


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

OVERHEAD SIGN STRUCTURES	
DRILLED SHAFT DETAILS	
SCALE: _____	SHEET _____ OF _____ SHEETS
STA. _____	TO STA. _____

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	D-2 OVD SIN STR REPL 18-32	VARIOUS	40	9
CONTRACT NO. 46470			ILLINOIS FED. AID PROJECT	



TYPICAL FRONT ELEVATION
 With lights and handrail omitted for clarity.
 For Section B-B, see Base Sheet 05-A-10.



PLAN WALKWAY AND HANDRAIL SKETCH
 (Road plan beneath truss varies)

BRACKET TABLE


WF(A-N)4x1.79 or WF(A-N)4x3.06 ASTM B308, Alloy 6061-T6		
Sign Width		Number Brackets Required
Greater Than	Less Than or Equal To	
	8'-0"	2
8'-0"	14'-0"	3
14'-0"	20'-0"	4
20'-0"	26'-0"	5
26'-0"	32'-0"	6

Notes:
 * Space walkway brackets WF(A-N)4x3.06 and sign brackets WF(A-N)4x1.79 for efficiency and within limits shown:
 $f = 12"$ maximum, 4" minimum (End of sign to ϕ of nearest bracket)
 $g = 12"$ maximum, 4" minimum (End of walkway grating to ϕ of nearest support bracket)
 $h = 6'-0"$ maximum (ϕ to ϕ sign and/or walkway support brackets, WF(A-N)4x1.79 or WF(A-N)4x3.06)
 $k = 2"$ maximum gap between adjacent walkway grating sections and handrail ends

** If walkway bracket at safety chain location is behind sign, add angle to bracket, see Alternate Safety Chain Attachment on Base Sheet 05-A-11.

For Details T and W, Section B-B and Grating Splice Details see Base Sheet 05-A-10.

For Handrail Details see Base Sheet 05-A-11.



SECTION A-A

Handrail and walkway shall span a minimum of three brackets between splices and/or gap joints. Place all sign and walkway brackets as close to panel points as practical. Handrail joints, grating, and light support splices placed as needed.

Structure Number	Station	a	b	c	d	e	Walkway Grating and Handrail Lengths

Truss grating to facilitate inspection shall run full length (center to center of support frames) $\pm 12"$ on overhead trusses. Cost of truss grating is included in "Overhead Sign Structure".

Walkway and Truss Grating width dimensions are nominal and may vary $\pm 1/2"$ based on available standard widths.

FOR ALL STRUCTURES, THE INSIDE WALKWAY SHALL BE INSTALLED, COST IS INCIDENTAL TO OVERHEAD SIGN STRUCTURE - SPAN, TYPE II-A 4'-6" X 5'-3" AND OVERHEAD SIGN STRUCTURE - CANTILEVER, TYPE II-C-A 36"X5'6"

05-A-9

2-17-2017

FILE NAME =	USER NAME = dossed	DESIGNED -	REVISED -
pw:\11\084EBIDINTEG\11\inois.gov\PWIDOT\Documents\DOT Offices\District 2\Projects\Open Bridge-Section\Winnabago\Contract\REVISED\2017-2\Design Files\46470-sheet cover.dgn			
PLOT SCALE = 100.0000' / in.	CHECKED -	REVISED -	
Default	DATE -	REVISED -	
	PLOT DATE = Nov-27-2018 01:13:04 PM		

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

OVERHEAD SIGN STRUCTURES			
ALUMINUM WALKWAY DETAILS			
SCALE: _____	SHEET _____	OF _____ SHEETS	STA. _____ TO STA. _____

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
D-2	OVD SIN STR REPL 18-32	VARIOUS	40	10
CONTRACT NO. 46470			ILLINOIS FED. AID PROJECT	

GENERAL NOTES

DESIGN: AASHTO Standard Specifications for Structural Supports for Highway Signs, Luminaires and Traffic Signals. ("AASHTO Specifications")

CONSTRUCTION: Current (at time of letting) Illinois Department of Transportation Standard Specifications for Road and Bridge Construction, Supplemental Specifications and Special Provisions. ("Standard Specifications")

LOADING: 90 M.P.H. WIND VELOCITY

WALKWAY LOADING: Dead load plus 500 lbs. concentrated live load.

DESIGN STRESSES:

Field Units
 $f' = 3,500$ p.s.i.
 $f_y = 60,000$ p.s.i. (reinforcement)

WELDING: All welds to be continuous unless otherwise shown. All welding to be done in accordance with current AWS D1.1 and D1.2 Structural Welding Codes (Steel and Aluminum) and the Standard Specifications.

MATERIALS: Aluminum Alloys as shown throughout plans. All Structural Steel Pipe shall be ASTM A53 Grade B or A500 Grade B or C. If A500 pipe is substituted for A53, then the outside diameter shall be as detailed and wall thickness greater than or equal to A53.

All Structural Steel Plates and Shapes shall conform to AASHTO M270 Gr. 36, Gr. 50 or Gr. 50W*. Stainless steel for shims, sleeves and handhole covers shall be ASTM A240, Type 302 or 304, or another alloy suitable for exterior exposure and acceptable to the Engineer.

The steel pipe and stiffening ribs at the base plate for the column shall have a minimum longitudinal Charpy V-Notch (CVN) energy of 15 lb.-ft. at 40° F. (Zone 2) before galvanizing.

FASTENERS FOR ALUMINUM TRUSSES: All bolts noted as "high strength" must satisfy the requirements of AASHTO M164 (ASTM A325), or approved alternate, and must have matching lock nuts. Threaded studs for splices (if Members interfere) must satisfy the requirements of ASTM A449, ASTM A193, Grade B7, or approved alternate, and must have matching lock nuts. Bolts and lock nuts not required to be high strength must satisfy the requirements of ASTM A307. All bolts and lock nuts must be hot dip galvanized per AASHTO M232. The lock nuts must have nylon or steel inserts. A stainless steel flat washer conforming to ASTM A240 Type 302 or 304, is required under both head and nut or under both nuts where threaded studs are used. High strength bolt installation shall conform to Article 505.04 (f) (2) of the IDOT Standard Specifications for Road and Bridge Construction. Rotational capacity ("ROCAP") testing of bolts will not be required.

U-BOLTS AND EYEBOLTS: U-Bolts and Eyebolts must be produced from ASTM A276 Type 304, 304L, 316 or 316L, Condition A, cold finished stainless steel, or an equivalent material acceptable to the Engineer. All nuts for U-Bolts and Eyebolts must be lock nuts equivalent to ASTM A307 with nylon or steel inserts and hot dip galvanized per AASHTO M232. A stainless steel flat washer conforming to ASTM A240, Type 302 or 304, is required under each U-Bolt and Eyebolt lock nut.

GALVANIZING: All Steel Grating, Plates, Shapes and Pipe shall be Hot Dip Galvanized after fabrication in accordance with AASHTO M111. Painting is not permitted.

ANCHOR RODS: Shall conform to ASTM F1554 Gr. 105.


CONCRETE SURFACES: All concrete surfaces above an elevation 6" below the lowest final ground line at each foundation shall be cleaned and coated with Concrete Sealer in accordance with the Standard Specifications.

REINFORCEMENT BARS: Reinforcement Bars designated (E) shall be epoxy coated in accordance with the Standard Specifications.


FOUNDATIONS: The contract unit price for Drilled Shaft Concrete Foundations shall include reinforcement bars complete in place.

Structure Number	Station	Design Truss Type	Cantilever Length (L)	Elev. A	Dim. D	Ds	Total Sign Area
2C101S251R010.6	156+50	II-C-A	28'	734'	14'	5'	77.5

Truss Type	Maximum Sign Area	Maximum Length
I-C-A	170 Sq. Ft.	25 Ft.
II-C-A	340 Sq. Ft.	30 Ft.
III-C-A	400 Sq. Ft.	40 Ft.




TYPICAL PLAN
(Walkway not shown)



TYPICAL ELEVATION
Looking in Direction of Traffic

Elev. A = Elevation at point of minimum clearance to sign, walkway support or truss.

Sign support structures may be subject to damaging vibrations and oscillations when sign panels are not in place during erection or maintenance of the structure. To avoid these vibrations and oscillations, consideration should be given to attaching temporary blank sign panels to the structure.



DESIGN WIND LOADING DIAGRAM

Parameters shown are basis for I.D.O.T. Standards. Installations not within dimensional limits shown require special analysis for all components.

Note:

Trusses shall be shipped individually with adequate provision to prevent detrimental motion during transport. This may require ropes between horizontals and diagonals or energy dissipating (elastic) ties to the vehicle. The contractor is responsible for maintaining the configuration and protection of the trusses.

- ① After adjustments to level truss and insure adequate vertical clearance, all top and leveling nuts shall be tightened against the base plate with a minimum torque of 200 lb.-ft. Stainless steel mesh shall then be placed around the perimeter of the base plate. Secure to base plate with stainless steel banding.

* If M270 Gr. 50W (M222) steel is proposed, chemistry for plate to be used shall first be approved by the Engineer as suitable for galvanizing and welding.

TOTAL BILL OF MATERIAL

ITEM	UNIT	TOTAL
OVERHEAD SIGN STRUCTURE CANTILEVER TYPE I-C-A	Foot	28'
OVERHEAD SIGN STRUCTURE CANTILEVER TYPE II-C-A	Foot	
OVERHEAD SIGN STRUCTURE CANTILEVER TYPE III-C-A	Foot	
OVERHEAD SIGN STRUCTURE WALKWAY, TYPE A	Foot	
DRILLED SHAFT CONCRETE FOUNDATIONS	Cu. Yds.	9.0

OSC-A-1

2-17-2017







FILE NAME =	USER NAME = dossed	DESIGNED -	REVISED -
pw:\11084EBIDINTEG.illinois.gov\PWIDOT\Documents\IDOT Offices\District 2\Projects\Open Bridge Section\Winnebago\Contract\REVISED 2011-2\Design Files\46470-sheet cover.dgn			
PLOT SCALE = 100.0000' / 1in.	CHECKED -	REVISOR -	REVISOR -
Default	DATE -	REVISOR -	REVISOR -
PLOT DATE = Nov-27-2018 01:13:27 PM			

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

CANTILEVER SIGN STRUCTURES - GENERAL PLAN & ELEVATION
ALUMINUM TRUSS & STEEL POST

SCALE: _____ SHEET _____ OF _____ SHEETS STA. _____ TO STA. _____

F.A. R.T.E.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	D-2 OVD SIN STR REPL 18-32	VARIOUS	40	11
CONTRACT NO. 46470			ILLINOIS FED. AID PROJECT	



Note:
There are twice as many horizontal diagonals as there are vertical diagonals.

For Section B-B and Section C-C, see Base Sheet OSC-A-3.

TRUSS UNIT TABLE



Truss Type	Dimension "a"	Dimension "b"	Dimension "s"	Limits for Panel Spacing (P)*	Up. & Low. Chord			
					O.D.	Wall	Verticals; Horizontal; Interior Diagonals O.D.	Wall
I-C-A	24"	54"	16"	36" min. to 48" max.	5"	5/16"	2 1/2"	5/16"
II-C-A	36"	66"	21"	42" min. to 54" max.	6 1/2"	5/16"	3 1/4"	5/16"
III-C-A (35' Max.)	36"	84"	21"	48" min. to 66" max.	7"	3/8"	3 1/2"	3/8"
III-C-A (>35' to 40')	36"	84"	21"	48" min. to 66" max.	8"	3/8"	3 1/2"	3/8"

$$*p = \frac{L-s-3"}{\# \text{ Panels}}$$

Structure Number	Station	Truss Type	Design Length (L)	Number of Panels Per Unit	Panel Length (P)*	
172	2C101S251R010.6	156+50	II-C-A	28'	7	3'-8.5"

SHOP CAMBER TABLE

Unit Length (L)	Shop Camber at End
15'	1 1/2"
16'-17'	1 3/4"
18'-20'	2"
21'-22'	2 1/4"
23'-25'	2 1/2"
26'-27'	2 3/4"
28'-30'	3"
31'-32'	3 1/4"
33'-35'	3 1/2"
36'-37'	4"
38'-40'	4 1/2"



OSC-A-2 2-17-2017


FILE NAME =	USER NAME = dossdd	DESIGNED -	REVISED -
pw:\IL\084EBIDINTEG.illinois.gov\PWIDOT\Documents\DOT Offices\District 2\Projects\Open Road\Bridges\Section\Winnabago\Contract\REVISED\2011-7-2\Design_Files\46470-sheetcover.dgn		CHECKED -	REVISED -
Default	PLOT DATE = Nov-27-2018 01:13:46 PM	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


CANTILEVER SIGN STRUCTURES - TRUSS DETAILS
ALUMINUM TRUSS & STEEL POST

F.A. RT.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	D-2 OVD SIN STR REPL 18-32	VARIOUS	40	12
CONTRACT NO. 46470			ILLINOIS FED. AID PROJECT	


SCALE: _____ SHEET _____ OF _____ SHEETS STA. _____ TO STA. _____



PLAN DETAIL




TRUSS DAMPING DEVICE CONNECTION DETAIL




ELEVATION
Aluminum Cantilever Sign Structure

GENERAL NOTES

- Damper: One damper per truss. (31 lbs. Stockbridge-Type Aluminum-29" minimum between ends of weights)
- Materials: Aluminum tubes shall be ASTM B221 alloy 6061 temper T6



SECTION A-A



DAMPING DEVICE MOUNTING TUBE U-BOLT DETAIL
(Typical)

TOP CHORD TO CROSS TUBE U-BOLT DETAIL
(Typical)

OSC-A-D

2-17-2017

FILE NAME =	USER NAME = dossdd	DESIGNED -	REVISED -
pw:\11\084EBIDINTEG.illinois.gov\PI\DOT\Documents\DOT Offices\District 2\Projects\Open Bridge-Section\Winnebago\Contract\REVISED\2017-2\Design Files\46470-sheetcover.dgn			
PLOT SCALE = 100.0000' / 1".	CHECKED -	REVISOR -	REVISOR -
PLOT DATE = Nov-27-2018 01:13:59 PM	DATE -	REVISOR -	REVISOR -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**CANTILEVER SIGN STRUCTURE
DAMPING DEVICE**

SCALE: _____ SHEET _____ OF _____ SHEETS STA. _____ TO STA. _____

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	D-2 OVD SIN STR REPL 18-32	VARIOUS	40	13
CONTRACT NO. 46470			ILLINOIS FED. AID PROJECT	


Holes in galvanized steel post and aluminum collar = bolt $\varnothing + 1/16"$.
Holes in stainless steel sleeve = bolt $\varnothing + 3/16"$.



SECTION B-B


Bolts, washers (including contoured washers), and locknuts shall be stainless steel.

4 Collar I.D. shall be manufactured to correspond to O.D. of actual galvanized post and stainless steel sleeve plus 1/8 inch (± 1/16 inch). Maximum gap between post and collar at any location equals 1/8 inch before tightening bolts.




DETAIL A

(Two locations)




DETAIL B

Two locations (For details not shown, see Detail C)




DETAIL D




PLAN VIEW - TOP OF COLUMN

5 Optional full penetration weld in collar. (Two locations maximum....(180 degrees apart)....X-ray or UT 100%)




SECTION THRU POST ABOVE LOWER CHORDS

Hole in aluminum plate (and 16 ga. stnl. stl. sheet) to be O.D. post + 1/2 inch



DETAIL C



CONTOURED WASHERS

Bolt Size	Contoured Washers	
	Hole Dia.	B
7/8"	1"	2 1/2"
1"	1 1/8"	3"
1 1/4"	1 3/8"	3 1/4"

DETAIL OF STAINLESS STEEL SLEEVE

Weld to post after galvanizing. (Prepare post surface to insure tight, uniform fit and allow welding.) Welds to be 1 1/2 inch long at 6 inch cts. along top edge and at 1/4 inch opening.

Truss Type	Post Size	Upper & Lower Connection Bolt Diameter 3	Lower Juncture Bolt Spacing Dimension "c" 3	Opening in Cap Plate "HH"	Collar Thickness (t)	Side Ribs	
						x	y
I-C-A	16" \varnothing (83#/'')	7/8"	3 1/4"	8"	5/8"	1 3/4"	2 1/4"
II-C-A	24" \varnothing (125#/'')	1"	3 1/2"	12"	7/8"	2"	1 1/4"
III-C-A (35' max.)	24" \varnothing (125#/'')	1 1/4"	3 1/2"	12"	7/8"	2"	1"
III-C-A (>35' to 40')	24" \varnothing (171#/'')	1 1/4"	3 1/2"	12"	7/8"	2"	1"

- 1 Grind top if required to fully seat aluminum plate and stainless steel sheet.
- 2 After tightening lower connection bolts, fill gap with non-hardening, silicone caulk suitable for exterior exposure and acceptable to the Engineer. Cost is included in Overhead Sign Structure Cantilever.
- 3 Upper and lower connection bolts in collar and bolts at lower chord connection shall be high strength with matching locknuts. Connection bolts shall have 2 stainless steel flat washers each.

OSC-A-3

2-17-2017








FILE NAME =	USER NAME = dossdd	DESIGNED -	REVISED -
pw:\11084EBIDINTEG\11nois.gov\PIWIDOT\Documents\DOT Offices\District 2\Projects\Open Bridge-Section\Winnebago\Contract\REVISED\2011-2\Design_Files\46470-sheet-cover.dgn		CHECKED -	REVISED -
PLOT SCALE = 100.0000' / 1"		DATE -	REVISED -
Default	PLOT DATE = Nov-27-2018 01:14:11 PM		

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

CANTILEVER SIGN STRUCTURES - JUNCTURE DETAILS
ALUMINUM TRUSS & STEEL POST

SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
D-2 OVD SIN STR REPL 18-32		VARIOUS	40	14
CONTRACT NO. 46470			ILLINOIS FED. AID PROJECT	



Anchor rods shall conform to ASTM F1554 Grade 105. Galvanize the upper 18" (minimum***) and associated AASHTO M291, Grade A, C or DH heavy hex nuts and hardened washers per AASHTO M232. No welding shall be permitted on rods. Provide a nut at bottom, a hexagon locknut and washer above base plate and a leveling nut and washer below base plate. Nuts shall each be tightened with 200 lb.-ft. minimum torque against base plate. Before or after threading, but before galvanizing, each anchor rod shall be ultrasonically tested (UT) by a Level II or III inspector, qualified in accord with ANSI guidelines, to insure no rejectable flaws exist in the upper 18" (tension criteria). Cost of testing included in Drilled Shaft Concrete Foundations.

Structure Number	Station	H
2C101S251R010.6	156+50	22.02'

Note: "H" based on 15'-0" or actual sign height, whichever is greater.

OSC-A-5 2-17-2017

FILE NAME =	USER NAME = dosddd	DESIGNED -	REVISED -
p:\11\084EBIDINTEG\11\inois.gov\PI\DOT\Documents\DOT Offices\District 2\Projects\Open Road\Bridges\Section\Winnepago\Contract\REVISED\2011\17-2\Design_Files\46470-shield-cover.dgn		CHECKED -	REVISED -
PLOT SCALE = 100.0000' / 1"	DATE =	DATE =	DATE =
Default	PLOT DATE = Nov-27-2018 01:14:23 PM		



**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**CANTILEVER SIGN STRUCTURES - TYPE II-C-A & III-C-A
TRUSS SUPPORT POST - ALUMINUM TRUSS & STEEL POST**

F.A. RTÉ.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
D-2	OVD SIN STR REPL 18-32	VARIOUS	40	15
CONTRACT NO. 46470			ILLINOIS FED. AID PROJECT	

SCALE: SHEET OF SHEETS STA. TO STA.

* Grind anchor rod to bright finish at ground clamp location before installing clamp.




NOTES:
 The foundation dimensions shown in the Foundation Design Table are based on the presence of mostly cohesive soils with an average Unconfined Compressive Strength (Q_u) of at least 1.25 tsf, which must be determined by previous soil investigations at the jobsite. When other conditions are indicated, the boring data will be included in the plans and the foundation dimensions shown in the Foundation Data Table will be the result of site specific designs.
 If the conditions encountered are different than those indicated, the Contractor shall notify the Engineer to determine if the foundation dimensions need to be modified. If dimensions "B" or "F" are revised by more than 12" by the Contractor, "as-built" plans shall be prepared and submitted to the District Bureau of Operations for future reference.
 No sonotubes or decomposable forms shall be used below the lower conduit entrance. Permanent metal forms or other shielding may not be left in place below that elevation without the Engineer's written permission.
 Concrete shall be placed monolithically, without construction joints.
 Backfill shall be placed per Article 502 of Standard Specification and prior to erection of support column.
 A normal surface finish followed by a Concrete Sealer application will be required on concrete surfaces above the lowest elevation 6" below finished ground line. Cost included in "Drilled Shaft Concrete Foundation".


Truss Type	Post Base Sheet	Maximum Cantilever Length (ft)	Maximum Total Sign Area (sq ft)	Shaft Diameter (in)	"B" Depth (ft)	Anchor Rods		Anchor Rod Circle Diameter (in)
						No.	Diameter (in)	
I-C-A	OSC-A-4	25	170	3.0	16.0	8	2	22
II-C-A	OSC-A-5	30	170	3.5	17.0	12	2	30
II-C-A	OSC-A-5	30	340	3.5	21.5	12	2	30
III-C-A	OSC-A-5	35	170	3.5	19.0	12	2	30
III-C-A	OSC-A-5	35	250	3.5	22.5	12	2	30
III-C-A	OSC-A-5	35	400	3.5	26.5	12	2	30
III-C-A	OSC-A-5	40	400	3.5	32.0	12	2	30

Structure Number	Station	Truss Type	Shaft Diameter	Elevation Top	Elevation Bottom	Q_u	A	B	F	Class DS Concrete Cubic Yards
2C101S251R010.6	156+50	II-C-A	3.5	733.75'	708.75		3.5'	21.5'	25'	9.0

OSC-A-9 2-17-2017




TYPICAL FRONT ELEVATION
With lights and handrail omitted for clarity.



PLAN
WALKWAY AND HANDRAIL SKETCH
(Road plan beneath truss varies)

Walkway and truss grating dimensions are nominal and may vary (width $\pm 1/2"$, depth $\pm 1/2"$) based on available standard widths.



SECTION A-A

Truss grating to facilitate inspection shall run full length of cantilevers. Cost of truss grating is included in Overhead Sign Structure Cantilever.

Handrail and walkway grating shall span a minimum of three brackets between splices.
** Use and location of handrail joints or grating splices are optional, based on lengths needed and material availability.

$$TGL = L - \left(\frac{\text{Post O.D.}}{2} + 6" \right)$$

Structure Number	Station	WGL	ED	TGL

Notes:
Space walkway brackets WF(A-N)4x3.06 and sign brackets WF(A-N)4x1.79 for efficiency and within limits shown:

f = 12" maximum, 4" minimum (End of sign to ϕ of nearest bracket)
g = 12" maximum, 4" minimum (End of walkway to ϕ of nearest bracket)
h = 6'-0" maximum (ϕ to ϕ sign and/or walkway support brackets, WF(A-N)4x1.79 or WF(A-N)4x3.06)

*** If walkway bracket at safety chain location is behind sign, add angle to bracket. See alternate safety chain attachment on base sheet OSC-A-8

For details of sign placement, sign/walkway brackets, truss and walkway gratings, grating splices and Section B-B, see Base Sheet OSC-A-7.
For details of handrail, handrail joint, safety chain and Details F and G, see Base Sheet OSC-A-8.

BRACKET TABLE

WF(A-N)4x1.79 or WF(A-N)4x3.06 ASTM B308, Alloy 6061-T6		
Sign Width		Number Brackets Required
Greater Than	Less Than or Equal To	
	8'-0"	2
8'-0"	14'-0"	3
14'-0"	20'-0"	4
20'-0"	26'-0"	5
26'-0"	32'-0"	6

FOR ALL STRUCTURES, THE INSIDE WALKWAY SHALL BE INSTALLED, COST IS INCIDENTAL TO OVERHEAD SIGN STRUCTURE - SPAN, TYPE II-A 4'-6" X 5'-3" AND OVERHEAD SIGN STRUCTURE - CANTILEVER, TYPE II-C-A 36"X5'6"

OSC-A-6 2-17-2017


FILE NAME =	USER NAME = dossed	DESIGNED -	REVISED -
pw:\IL\084EBIDINTEG.illinois.gov\PWIDOT\Documents\DOT Offices\District 2\Projects\Open Bridge-Section\Winnebago\Contract\REVISED 2017-2\Design Files\46470-sheet cover.dgn			
PLOT SCALE = 100.0000' / in.	CHECKED -	REVISOR -	REVISOR -
PLOT DATE = Nov-27-2018 01:14:46 PM	DATE -	REVISOR -	REVISOR -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

CANTILEVER SIGN STRUCTURES - ALUMINUM WALKWAY
DETAILS - ALUMINUM TRUSS & STEEL POST
SCALE: _____ SHEET _____ OF _____ SHEETS STA. _____ TO STA. _____


F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
D-2 OVD SIN STR REPL 18-32		VARIOUS	40	17
CONTRACT NO. 46470			ILLINOIS FED. AID PROJECT	

PLAN VIEW SN 002



FILE NAME =	USER NAME = dssdd	DESIGNED - _____	REVISED - _____	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	PLAN VIEW SN 002		F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
pw:\IL084EB\INTEG\Illinois.gov\PWIDOT\Documents\DOT Offices\District 2\Projects\Operations\Bridges\Section\Winnebago\46470\46470\117-2\Design Files\46470-shl\coe		DRAWN - _____	REVISED - _____		SCALE: _____	SHEET _____	OF _____	SHEETS	STA. _____	TO STA. _____	ILLINOIS	FED. AID PROJECT
Default		PLOT SCALE = 100.0000' / in.	CHECKED - _____		REVISED - _____						VARIOUS	40
		PLOT DATE = Sep-25-2018 08:34:52 AM	DATE - _____		REVISED - _____						CONTRACT NO. 46470	

PLAN VIEW SN 053



FILE NAME =	USER NAME = dssdd	DESIGNED -	REVISED -
pw:\IL04EB\INTEG\Illinois.gov\PW\DOT\Documents\DOT Offices\District 2\Projects\Operations\Bridges\Section\Winnebago\46470\46470-SN053\46470-shi\000000.dwg		DRAWN -	REVISED -
Default	PLOT SCALE = 100,0000' / in.	CHECKED -	REVISED -
	PLOT DATE = Sep-25-2018 08:35:01 AM	DATE -	REVISED -



**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**PLAN VIEW
SN 053**

SCALE: _____ SHEET _____ OF _____ SHEETS STA. _____ TO STA. _____



F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	D-2 OVD SIN STR REPL 18-32	VARIOUS	40	19
CONTRACT NO. 46470				
ILLINOIS FED. AID PROJECT				

PLAN VIEW SN 136



FILE NAME =	USER NAME = dossed	DESIGNED - _____	REVISED - _____	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	PLAN VIEW SN 136		F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.		
pw:\084EB\INTEG\Illinois.gov\PWIDOT\Documents\DOT Offices\District 2\Projects\Operations\Bridges\Section\Winnebago\46470\SLT200117-2\Design Files\46470-sh\code		DRAWN - _____	REVISED - _____		SCALE: _____	SHEET _____	OF _____	SHEETS	STA. _____	TO STA. _____	ILLINOIS	FED. AID PROJECT	
Default		PLOT SCALE = 100.0000' / in.	CHECKED - _____		REVISED - _____						VARIOUS	40	20
		PLOT DATE = Sep-25-2018 08:35:07 AM	DATE - _____		REVISED - _____						CONTRACT NO. 46470		

PLAN VIEW SN 170 & SN 172





FILE NAME =	USER NAME = dssdd	DESIGNED -	REVISED -
pw:\IL04EB\INTEG\Illinois.gov\PWIDOT\Documents\DOT Offices\District 2\Projects\Operations\Bridges\Section\Winnebago\46470\ILT200\117-2\Design Files\46470-sh\co		DRAWN	REVISED
Default	PLOT SCALE = 100,0000' / in.	CHECKED -	REVISED -
	PLOT DATE = Sep-25-2018 08:35:19 AM	DATE -	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**PLAN VIEW
SN 170 & SN 172**


SCALE: _____ SHEET _____ OF _____ SHEETS STA. _____ TO STA. _____

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	D-2 OVD SIN STR REPL 18-32	VARIOUS	40	21
CONTRACT NO. 46470				
ILLINOIS FED. AID PROJECT				



12.0" Radius, 2.0" Border, White on Green;
 [BUSINESS] E Mod 2K; [State St] E Mod 2K; Down Arrow 22.0" 270°;
 Table of letter and object lefts.

B	U	S	I	N	E	S	S	●	
19.6	32.0	44.7	57.4	63.2	76.3	87.3	99.7	124.4	
S	t	a	t	e	S	t			
36.8	53.0	65.0	80.2	92.2	118.7	134.9			
↓									
74.0									



12.0" Radius, 2.0" Border, White on Green;
 [EAST] E 2K; Symbol RA010; [Chicago] E Mod 2K; Down Arrow 22.0" 270°; Down Arrow 22.0" 270°;
 Table of letter and object lefts.

●	E	A	S	T	✈	
27.6	75.6	88.4	101.9	113.0	146.0	
C	h	i	c	a	g	o
49.7	67.2	84.1	92.3	106.4	121.9	137.4
↓	↓					
11.0	155.0					


FILE NAME =	USER NAME = dosddd	DESIGNED -	REVISED -
p:\11\084EBIDINTEG\illinois.gov\PWIDOT\Documents\DOT Offices\District 2\Projects\Ope	BRIDGE-SECTION\Winnebago\Contract	REVISED 2008117-2\Design Files\46470-sheet cover.dgn	
Default	PLOT SCALE = 100.0000' / in.	CHECKED -	REVISED -
	PLOT DATE = Sep-25-2018 08:35:32 AM	DATE -	REVISED -

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

**SIGN STRUCTURE REPLACEMENT
 SIGN PANEL REPORT - SN 002**


SCALE: _____ SHEET ____ OF ____ SHEETS STA. _____ TO STA. _____

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
D-2	OVD SIN STR REPL 18-32	VARIOUS	40	22
CONTRACT NO. 46470			ILLINOIS FED. AID PROJECT	




12.0" Radius, 2.0" Border, White on Green;
 [Quad City] E Mod 2K; [Airport] E Mod 2K; [NEXT RIGHT] E 2K;
 Table of letter and object lefts.

Q	u	a	d	C	i	t	y	
14.8	33.0	48.6	64.1	90.6	108.1	115.9	127.6	
A	i	r	p	o	r	t		
33.1	53.1	62.7	74.6	88.6	104.5	114.6		
N	E	X	T	R	I	G	H	T
24.7	37.6	48.2	60.0	81.0	93.1	98.0	110.5	122.3





12.0" Radius, 2.0" Border, White on Green;
 [EAST] E 2K; [Galesburg] E Mod 2K; [NEXT RIGHT] E 2K;
 Table of letter and object lefts.

INTERSTATE	74	6	E	A	S	T		
12.8	60.8	108.8	121.6	135.1	146.2			
G	a	l	e	s	b	u	r	g
21.9	38.2	55.2	63.4	77.1	92.6	108.2	125.1	135.5
N	E	X	T	R	I	G	H	T
30.7	43.6	54.2	66.0	87.0	99.1	104.0	116.5	128.3





9.0" Radius, 1.5" Border, White on Green;
 [WEST] E 2K; [Davenport] E Mod 2K; Arrow 160 - 35.0" 45°;
 Table of letter and object lefts.

INTERSTATE	74	6	W	E	S	T	↗	
10.8	58.8	106.8	125.0	135.7	146.7	155.7		
D	a	v	e	n	p	o	r	t
19.3	35.6	50.8	66.4	81.9	98.8	112.9	128.8	138.8




12.0" Radius, 2.0" Border, White on Green;
 [EXIT] E Mod 2K 120% spacing; [11 A] E Mod 2K;
 12.0" Radius, 2.0" Border, White on Green;
 [WEST] E 2K; [Andalusia] E Mod 2K; [NEXT RIGHT] E 2K;
 Table of letter and object lefts.

E	X	I	T	I	I	A		
58.6	67.7	78.9	83.1	105.5	113.9	125.8		
■	W	E	S	T				
28.0	79.0	97.2	107.9	119.0				
A	n	d	a	l	u	s	i	a
14.5	34.5	50.0	65.5	82.5	92.1	107.3	122.8	131.0
N	E	X	T	R	I	G	H	T
24.7	37.6	48.2	60.0	81.0	93.1	98.0	110.5	122.3




12.0" Radius, 2.0" Border, White on Green;
 [EXIT] E Mod 2K 120% spacing; [11 B] E Mod 2K;
 12.0" Radius, 2.0" Border, White on Green;
 [EAST] E 2K; [Rock Island] E Mod 2K; Arrow 160 - 35.0" 45°;
 Table of letter and object lefts.

E	X	I	T	I	I	B			
115.6	124.7	135.9	140.0	162.4	170.8	182.9			
■	E	A	S	T	↗				
38.6	89.6	102.3	115.9	126.9	172.2				
R	o	c	k	I	s	I	a	n	d
14.3	30.1	44.5	60.0	86.6	93.5	109.0	117.2	134.1	149.6




9.0" Radius, 1.5" Border, White on Green;
 [WEST] E 2K; [Des Moines] E Mod 2K;
 Table of letter and object lefts.

W	E	S	T					
31.0	88.0	106.2	116.9					
D	e	s	M	o	i	n	e	s
13.6	29.9	43.7	70.2	89.1	105.0	114.6	130.1	143.8




6.0" Radius, 1.3" Border, White on Green;
 [Whitman Street] E Mod 2K; [1 MILE] E Mod 2K;
 Table of letter and object lefts.

W	h	i	t	m	a	n	S	t	r	e	e	t
12.1	29.5	43.6	50.1	61.3	80.1	94.3	116.4	129.9	141.1	149.7	161.5	172.9
1	M	I	L	E								
69.6	89.1	101.2	106.0	115.0								




9.0" Radius, 1.5" Border, White on Green;
 [Forest Hills] E Mod 2K; [Road] E Mod 2K; [1/2 MILE] E Mod 2K;
 Table of letter and object lefts.

F	o	r	e	s	t	H	i	l	l	s
16.0	28.3	41.5	50.1	61.6	73.1	93.3	108.7	116.7	124.7	131.2
R	o	a	d							
54.5	67.7	79.7	92.7							
1/2	M	I	L	E						
43.4	79.3	91.4	96.2	105.2						




6.0" Radius, 1.3" Border, White on Green;
 [Auburn St] E Mod 2K; [NEXT RIGHT] E Mod 2K;
 Table of letter and object lefts.

A	u	b	u	r	n	S	t	
10.9	27.5	41.7	54.6	68.7	78.6	100.7	114.2	
N	E	X	T	R	I	G	H	T
21.4	32.3	41.1	50.9	68.3	78.4	82.9	93.4	103.3



6.0" Radius, 1.3" Border, White on Green;
 [Spring Creek] E Mod 2K; [Road] E Mod 2K; Arrow 133 - 30.0° 45°;
 Table of letter and object lefts.


S	p	r	i	n	g	C	r	e	e	k	↗
6.5	21.4	34.4	44.2	52.2	65.2	87.3	101.8	110.5	122.2	135.2	152.0
R	o	a	d								
51.8	65.0	77.0	89.9								



6.0" Radius, 1.3" Border, White on Green;
 [Spring Creek] E Mod 2K; [Road] E Mod 2K; Arrow 133 - 30.0" 45°;
 Table of letter and object lefts.

S	p	r	i	n	g	C	r	e	e	k	↗
6.5	21.4	34.4	44.2	52.2	65.2	87.3	101.8	110.5	122.2	135.2	152.0
R	o	a	d								
51.8	65.0	77.0	89.9								

BORING LOGS



Illinois Department of Transportation
Division of Highways
IDOT

SOIL BORING LOG

Page 1 of 1
Date 3/16/15

ROUTE US 20 Bypass DESCRIPTION P92-US20BYP-15 Sign Truss, US 20 EB @ Ramp to US Business 20 EB LOGGED BY W. Garza

SECTION _____ LOCATION Winnebago Twp. - 3SE, SEC. , TWP. 26N, RNG. 1E

COUNTY Winnebago DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45 Automatic


STRUCT. NO. _____ Latitude _____ Northing _____
Station _____ Longitude _____ Easting _____

BORING NO. B-1b
Station 14' E
Offset 79.00ft N CL EB
Ground Surface Elev. 92.80 ft

ELEVATION (ft)	DEPTH (ft)	BULGE (in)	SHEAR (tsf)	PENETROMETER (%)	DESCRIPTION	ELEVATION (ft)	DEPTH (ft)	BULGE (in)	SHEAR (tsf)	PENETROMETER (%)
-89.204888					MEDIUM tan clean medium coarse SAND		6			
42.280717			0.5	25.0	Hard wash prohibited sampling. Augered 5' through hard, rock-like resistance to end of boring (continued)		21			
90.80		1								
89.30		2	1.0	30.0						
		4	B							
68.30					End of Boring					
		1								
		1	0.3	32.0						
		3	B							
86.30										
		1								
		2								
83.80		2								
		3								
		2	0.5	12.0						
		3	P							
81.80										
		1								
		3	1.1	12.0						
		5	P							
79.30										
		2								
		3								
		9		12.0						
76.30										
		40								
		24								
		27								
74.30										
		15								
-20										

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)



Illinois Department of Transportation
Division of Highways
IDOT

SOIL BORING LOG

Page 1 of 1
Date 3/17/15

ROUTE US 20 Bypass DESCRIPTION P92-US20BYP-15 Sign Truss, US 20 EB @ Ramp to US Business 20 EB LOGGED BY W. Garza

SECTION _____ LOCATION Winnebago Twp. - 3SE, SEC. , TWP. 26N, RNG. 1E

COUNTY Winnebago DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45 Automatic

STRUCT. NO. _____ Latitude _____ Northing _____
Station _____ Longitude _____ Easting _____

BORING NO. B-2b
Station 1' W
Offset 61.00ft S CL
Ground Surface Elev. 91.80 ft

ELEVATION (ft)	DEPTH (ft)	BULGE (in)	SHEAR (tsf)	PENETROMETER (%)	DESCRIPTION	ELEVATION (ft)	DEPTH (ft)	BULGE (in)	SHEAR (tsf)	PENETROMETER (%)
-89.204959					Wash		40			
42.280409			0.5	23.0	VERY DENSE tan weathered LIMESTONE with GRAVEL (continued)		31			
89.80		3								
		3	0.8	28.0	Wash		29			
		4	B		VERY DENSE tan weathered LIMESTONE		100/9"			
88.30										
		2								
		3	1.4	24.0	VERY DENSE tan weathered LIMESTONE		100/2"			
		5	B							
85.80					End of Boring					
		2								
		3	0.8	24.0						
		3	P							
83.30										
		2								
		3	0.1	12.0						
		2	P							
80.80										
		2								
		3	0.3	11.0						
		5	P							
77.80										
		3								
		10								
		17								
75.80										
		13								
		18								
		25								
73.30										
		18								
-20										

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)

BORING LOGS



Illinois Department of Transportation
Division of Highways
IDOT

SOIL BORING LOG

Page 1 of 1

Date 3/18/15

ROUTE John Deere Road DESCRIPTION P92-I74 Sign Truss-15 Sign Truss, John Deere Road at Ramp to I-74 WB, 1/4 m. E. of I-74 LOGGED BY W. Garza

SECTION LOCATION S. Moline Twp. - 16NE, SEC. , TWP. 17N, RNG. 1W

COUNTY Rock Island DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45 Automatic

STRUCT. NO. 053 Latitude Longitude Northing Easting

BORING NO. B-1	Station 10' W	Offset 50.00ft N CL	Ground Surface Elev. 99.00 ft	D P T H (ft)	B O W S (/6")	U C S Qu (tsf)	M O S T (%)	Surface Water Elev. _____ ft				Stream Bed Elev. _____ ft				Groundwater Elev.: First Encounter 77.0 ft ▼ Upon Completion 75.5 ft ▾ After _____ Hrs. _____ ft			
								D P T H (ft)	B O W S (/6")	U C S Qu (tsf)	M O S T (%)	D P T H (ft)	B O W S (/6")	U C S Qu (tsf)	M O S T (%)	D P T H (ft)	B O W S (/6")	U C S Qu (tsf)	M O S T (%)

Depth (ft)	Soil Description	D (ft)	B (/6")	U (tsf)	M (%)	Surface Water Elev. (ft)	Stream Bed Elev. (ft)	Groundwater Elev. (ft)	Soil Description	D (ft)	B (/6")	U (tsf)	M (%)
-90.490364	41.472059								STIFF olive-green SILTY CLAY with 23RGANICS (continued)				
	Dirty shoulder rock												
97.00						77.50							
	VERY STIFF gray SILTY CLAY LOAM		5		16.0				VERY DENSE light gray weathered SHALE				
95.50			9	3.6									
	VERY STIFF gray SILTY CLAY		4	2.8	17.0				VERY DENSE gray SHALE				
92.50			8						End of Boring				
	STIFF gray SILTY CLAY TILL		2		17.0								
90.50			8	1.7									
	STIFF gray SILTY CLAY		3	1.5	21.0								
88.00			6										
	MEDIUM dark gray SILTY CLAY TILL		2	0.9	19.0								
85.00			6										
	SOFT dark gray LOAM		2	0.4	26.0								
83.00			3										
	SOFT gray CLAY LOAM with 8% ORGANICS		0	0.3	53.0								
80.50			3										
			0										
-20			0										

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrator)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)



Illinois Department of Transportation
Division of Highways
IDOT

SOIL BORING LOG

Page 1 of 1

Date 3/26/15

ROUTE John Deere Road DESCRIPTION P92-I74 Sign Truss-15 Sign Truss, John Deere Road at Ramp to I-74 WB, 1/4 m. E. of I-74 LOGGED BY W. Garza

SECTION LOCATION S. Moline Twp. - 16NE, SEC. , TWP. 17N, RNG. 1W

COUNTY Rock Island DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45 Automatic

STRUCT. NO. 053 Latitude Longitude Northing Easting


BORING NO. B-2	Station 12' W	Offset 17.00ft S CL	Ground Surface Elev. 100.10 ft	D P T H (ft)	B O W S (/6")	U C S Qu (tsf)	M O S T (%)	Surface Water Elev. _____ ft				Stream Bed Elev. _____ ft				Groundwater Elev.: First Encounter 78.1 ft ▼ Upon Completion 80.1 ft ▾ After _____ Hrs. _____ ft			
								D P T H (ft)	B O W S (/6")	U C S Qu (tsf)	M O S T (%)	D P T H (ft)	B O W S (/6")	U C S Qu (tsf)	M O S T (%)	D P T H (ft)	B O W S (/6")	U C S Qu (tsf)	M O S T (%)

Depth (ft)	Soil Description	D (ft)	B (/6")	U (tsf)	M (%)	Surface Water Elev. (ft)	Stream Bed Elev. (ft)	Groundwater Elev. (ft)	Soil Description	D (ft)	B (/6")	U (tsf)	M (%)
-90.490336	41.471869								MEDIUM gray SILTY CLAY with 12RGANICS (continued)				
	MEDIUM brown LOAM		0.5	13.0									
98.10						78.60							
	STIFF light gray SILTY LOAM		5		21.0				LOOSE light gray clean medium coarse SAND				
96.60			7	1.8									
	MEDIUM light gray/tan SILTY CLAY		3	0.9	21.0				VERY DENSE light gray weathered SHALE				
94.10			6						End of Boring				
	STIFF gray SILTY CLAY		5		19.0								
91.60			8	1.8									
	VERY STIFF gray SILTY CLAY		1	2.1	19.0								
89.10			6										
	STIFF dark gray SILTY CLAY LOAM with 11RGANICS		3	1.2	40.0								
86.60			4										
	STIFF gray SILTY CLAY		2	1.2	27.0								
84.10			2										
	MEDIUM gray SILTY CLAY		0	0.7	34.0								
81.60			3										
			0										
-20			0										

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrator)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)

BORING LOGS



Illinois Department of Transportation
Division of Highways
IDOT

SOIL BORING LOG

Page 1 of 1
Date 3/3/17

ROUTE FAI 280 DESCRIPTION C60-013-18 Sign Truss on I-280 WB at Ramp to IL 92 EB LOGGED BY Wally Garza

SECTION 81-1-1 LOCATION Blackhawk (West Part) - SE 16, SEC. , TWP. 17N, RNG. 2W

COUNTY Winnebago DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45


STRUCT. NO. 081-0136 Latitude 41° 27' 39.48" Northing 1,746,426.8176
Station 118+50 Longitude -90° 36' 39.57" Easting 2,174,800.6148

BORING NO. B-1c
Station 117+95
Offset 69.00ft RI WB CL
Ground Surface Elev. 93.60 ft

DEPTH (ft)	B (%)	U (tsf)	M (%)	Soil Description								
				Surface Water Elev. (ft)	Stream Bed Elev. (ft)	Groundwater Elev. (ft)	First Encounter Upon Completion (ft)					
91.60	0.6	18.0		MEDIUM brown SANDY LOAM				MEDIUM tan medium SAND (continued)	72.60	6		
90.10	3	0.8	30.0					MEDIUM dark brown SILTY CLAY LOAM	70.10			
87.10	1	0.4	21.0					SOFT brown SANDY LOAM	67.60	2		
85.10	4							MEDIUM tan moist medium SAND				
82.60	1							MEDIUM brown dirty SAND	64.10			
80.10	7							MEDIUM brown medium SAND				
77.60	1							VERY LOOSE brown medium SAND				
75.10	2							LOOSE tan fine SAND				
72.60	1							MEDIUM tan medium SAND				

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrator)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)



Illinois Department of Transportation
Division of Highways
IDOT

SOIL BORING LOG

Page 1 of 1
Date 3/8/17

ROUTE FAI 280 DESCRIPTION C60-013-18 Sign Truss on I-280 WB at Ramp to IL 92 EB LOGGED BY Wally Garza

SECTION 81-1-1 LOCATION Blackhawk (West Part) - SE 16, SEC. , TWP. 17N, RNG. 2W

COUNTY Winnebago DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45

STRUCT. NO. 081-0136 Latitude 41° 27' 39.24" Northing 1,746,403.4947
Station 118+50 Longitude -90° 36' 43.29" Easting 2,174,517.9040


BORING NO. B-2c
Station 118+68
Offset 32.00ft LI WB CL
Ground Surface Elev. 98.80 ft

DEPTH (ft)	B (%)	U (tsf)	M (%)	Soil Description								
				Surface Water Elev. (ft)	Stream Bed Elev. (ft)	Groundwater Elev. (ft)	First Encounter Upon Completion (ft)					
96.80	0.5	15.0		MEDIUM brown SILTY CLAY LOAM				MEDIUM tan fine SAND (continued)	77.80	4		
94.80	6							MEDIUM tan dry fine SAND				
92.80	4	0.2	11.0					VERY STIFF brown SANDY LOAM with SAND lens	72.80	7		
90.30	3	0.8	21.0					MEDIUM black SANDY LOAM				
87.30	0		15.0					LOOSE tan/brown dirty moist SAND	67.80	3		
85.30	3							MEDIUM tan SAND with medium GRAVEL				
82.80	7							MEDIUM brown medium SAND				
80.30	6							MEDIUM brown medium SAND				
77.80	3							MEDIUM tan fine SAND				

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrator)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)

BORING LOGS



Illinois Department of Transportation
Division of Highways
IDOT

SOIL BORING LOG

Page 1 of 1
Date 2/17/16

ROUTE FA 509 DESCRIPTION C60-013-18 Sign Truss, .1 m. N. of Whitman Road LOGGED BY Wally Garza

SECTION 1-HBY LOCATION Rockford Twp. - SE 13, SEC. , TWP. 44N, RNG. 1E

COUNTY Winnebago DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45

STRUCT. NO. 101-0170 Latitude 42° 17' 11.23" Northing 2,048,838.6120
Station 147+50 West Side Longitude -89° 03' 51.96" Easting 2,594,829.2224


BORING NO. B-2a
Station 11' South
Offset 62.00ft W CL
Ground Surface Elev. 99.00 ft

DEPTH (ft)	BULGE (in)	SHEAR (tsf)	PENETRATION (%)	SOIL DESCRIPTION				DEPTH (ft)	BULGE (in)	SHEAR (tsf)	PENETRATION (%)										
				D	B	U	M					D	B	U	M						
97.00				MEDIUM brown LOAM		0.5	27.0					78.00									
95.50	2	0.8	11.0	MEDIUM brown SANDY LOAM								75.50	10								
93.00	5	1.1	11.0	STIFF tan SANDY LOAM								73.00	12								
90.00	2	1.0	24.0	MEDIUM/STIFF tan SANDY CLAY LOAM								70.50	30								
88.00	6			MEDIUM tan SANDY GRAVEL								68.00	24								
85.50	4			MEDIUM tan moist SANDY GRAVEL																	
83.00	6			DENSE tan medium SANDY GRAVEL																	
80.50	9			MEDIUM tan SANDY GRAVEL																	
	7			MEDIUM tan SANDY GRAVEL																	

Surface Water Elev. _____ ft
Stream Bed Elev. _____ ft
Groundwater Elev.: _____ ft
First Encounter _____ ft
Upon Completion _____ ft
After _____ Hrs. _____ ft

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)



Illinois Department of Transportation
Division of Highways
IDOT

SOIL BORING LOG

Page 1 of 1
Date 2/16/17

ROUTE FA 509 DESCRIPTION C60-013-18 Sign Truss, .1 m. N. of Whitman Road LOGGED BY Wally Garza

SECTION 1-HBY LOCATION Rockford Twp. - SE 13, SEC. , TWP. 44N, RNG. 1E

COUNTY Winnebago DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45

STRUCT. NO. 101-0171 Latitude 42° 17' 10.80" Northing 2,048,796.8651
Station 147+50 East Side Longitude -89° 03' 50.29" Easting 2,594,954.7949

BORING NO. B-1a
Station 17.5' N
Offset 68.00ft E CL
Ground Surface Elev. 100.70 ft

DEPTH (ft)	BULGE (in)	SHEAR (tsf)	PENETRATION (%)	SOIL DESCRIPTION				DEPTH (ft)	BULGE (in)	SHEAR (tsf)	PENETRATION (%)										
				D	B	U	M					D	B	U	M						
98.70				LOOSE light brown dirty fine SAND			8.0					79.70	11								
97.20	2			LOOSE tan fine SAND								77.20									
94.70	6			MEDIUM tan fine SAND								74.70	11								
92.20	4			MEDIUM tan fine SAND								72.20	11								
89.70	6			DENSE tan dry SANDY GRAVEL								69.70	4								
87.20	14			VERY DENSE tan moist SANDY GRAVEL																	
84.70	16			DENSE tan SANDY GRAVEL																	
82.20	16			DENSE tan SANDY GRAVEL																	
	10			MEDIUM tan SANDY GRAVEL																	

Surface Water Elev. _____ ft
Stream Bed Elev. _____ ft
Groundwater Elev.: _____ ft
First Encounter _____ ft
Upon Completion _____ ft
After _____ Hrs. _____ ft

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)

BORING LOGS



Illinois Department of Transportation
Division of Highways
IDOT

SOIL BORING LOG

Page 1 of 1

Date 2/21/17

ROUTE FA 509 DESCRIPTION C60-013-18 Cantilever Sign Truss, IL 251 SB at ramp to Spring Creek Road EB LOGGED BY Wally Garza

SECTION 1-HBY LOCATION Rockford Twp. - NE 13, SEC. , TWP. 44N, RNG. 1E

COUNTY Winnebago DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME-45

STRUCT. NO. 101-0172 Latitude 42° 17' 17.97" Northing 2,049,529.4038
Station 156+50 Longitude -89° 03' 43.50" Easting 2,595,455.9734

BORING NO. B-1b
Station 15' N
Offset 66.50ft W CL
Ground Surface Elev. 98.50 ft

D E L T H (ft)	B L C O S T (/6")	U C S Qu (tsf)	M O S T (%)	Soil Description								
				Surface Water Elev. _____ ft	Stream Bed Elev. _____ ft	Groundwater Elev.: First Encounter _____ None ft Upon Completion _____ Dry ft After _____ Hrs. _____ ft	D E L T H (ft)	B L C O S T (/6")	U C S Qu (tsf)	M O S T (%)		
		0.6 P	23.0	MEDIUM brown SILTY CLAY LOAM				DENSE tan SANDY GRAVEL (continued)	22 25			
96.50	2			SOFT tan SANDY LOAM				DENSE tan dry fine SAND	9 13 18			
95.00	1 2	0.4 P	15.0									
				MEDIUM gray SANDY LOAM				VERY DENSE tan dry SANDY GRAVEL	13 25 32			
-5	1 1 5	0.5 P	13.0									
92.50				MEDIUM/STIFF light gray SANDY LOAM				VERY DENSE tan SANDY GRAVEL	16 26 28			
	4 4 6	1.0 B	10.0									
90.00				MEDIUM dark brown SANDY LOAM				VERY DENSE tan moist SANDY GRAVEL	28 27 32			
-10	4 8 62	0.8 B	12.0									
87.00				MEDIUM tan medium SAND & GRAVEL				End of Boring				
	3 5 13											
85.00				DENSE tan dry SANDY GRAVEL								
	7 17 28											
-15				DENSE tan dry SANDY GRAVEL								
82.50												
	14 24 24			DENSE tan dry SANDY GRAVEL								
80.00												
	8			DENSE tan SANDY GRAVEL								
-20												

Northing and Easting were calculated using the ILLP-WF coordinate system

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)

FILE NAME =	USER NAME = dssdd	DESIGNED -	REVISED -
pw:\IL04EB\INTEG\Illinois.gov\PWIDOT\Documents\IDOT Offices\District 2\Projects\Operations\Bridges\Section\Winnebago\46470\46470-117-2\Design Files\46470-sh\c		DRAWN -	REVISED -
Default	PLOT SCALE = 100,0000' / in.	CHECKED -	REVISED -
	PLOT DATE = Sep-25-2018 08:36:52 AM	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


BORING LOGS
SN 172

SCALE: _____ SHEET _____ OF _____ SHEETS STA. _____ TO STA. _____

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	D-2 OVD SIN STR REPL 18-32	VARIOUS	40	32
CONTRACT NO. 46470				
ILLINOIS FED. AID PROJECT				

SN 002 NORTH FOUNDATION GUARDRAIL CALCULATIONS

ONE-WAY ROADWAYS ON TANGENT



- L_B =Distance to barrier
- L_C =Clear zone
- L_H =Distance to back of hazard
- L_F =Distance to front of hazard
- L_R =Runout length
- L_1 =Length needed for approach end
- L_2 =Length of hazard
- L_3 =Length to be omitted from length of need

Design Speed (mph) =	65
Traffic Volume (ADT) =	13000
Lane Width (ft) =	12

L_B (ft) =	5
L_C (ft) =	34
L_H (ft) =	36
L_F (ft) =	31
L_R (ft) =	300
L_2 (ft) =	8.25
L_1 (ft) =	255.9
L_3 (ft) =	61.5


See BDE Figure 38-3A, See BDE Figure 38-3D for CZ Curve Adjustment
 Must Insert Number, If Infinity, Insert Number > 30
 See BDE Figure 38-6C

NOTE: This tool was created to be an aide, please insure that you have reviewed Chapter 38 (Roadside Safety) of the BDE Manual, Applicable Standards, and other IDOT Documents relating to Roadside Safety Design

See Chapter 49 for 3R values for Clear Zones

SN 002 SOUTH FOUNDATION GUARDRAIL CALCULATIONS

ONE-WAY ROADWAYS ON TANGENT



- L_B =Distance to barrier
- L_C =Clear zone
- L_H =Distance to back of hazard
- L_F =Distance to front of hazard
- L_R =Runout length
- L_1 =Length needed for approach end
- L_2 =Length of hazard
- L_3 =Length to be omitted from length of need

Design Speed (mph) =	65
Traffic Volume (ADT) =	13000
Lane Width (ft) =	12

L_B (ft) =	10
L_C (ft) =	34
L_H (ft) =	36
L_F (ft) =	33
L_R (ft) =	300
L_2 (ft) =	8.25
L_1 (ft) =	211.8
L_3 (ft) =	54.4

See BDE Figure 38-3A, See BDE Figure 38-3D for CZ Curve Adjustment

Must Insert Number, If Infinity, Insert Number > 30


See BDE Figure 38-6C

NOTE: This tool was created to be an aide, please insure that you have reviewed Chapter 38 (Roadside Safety) of the BDE Manual, Applicable Standards, and other IDOT Documents relating to Roadside Safety Design

See Chapter 49 for 3R values for Clear Zones

SN 053 NORTH FOUNDATION GUARDRAIL CALCULATIONS

ONE-WAY ROADWAYS ON TANGENT



- L_B =Distance to barrier
- L_C =Clear zone
- L_H =Distance to back of hazard
- L_F =Distance to front of hazard
- L_R =Runout length
- L_1 =Length needed for approach end
- L_2 =Length of hazard
- L_3 =Length to be omitted from length of need

Design Speed (mph) =	65
Traffic Volume (ADT) =	40600
Lane Width (ft) =	12

L_B (ft) =	10
L_C (ft) =	34
L_H (ft) =	32
L_F (ft) =	29
L_R (ft) =	300
L_2 (ft) =	8.25
L_1 (ft) =	206.3
L_3 (ft) =	45.0


See BDE Figure 38-3A, See BDE Figure 38-3D for CZ Curve Adjustment
 Must Insert Number, If Infinity, Insert Number > 30
 See BDE Figure 38-6C

NOTE: This tool was created to be an aide, please insure that you have reviewed Chapter 38 (Roadside Safety) of the BDE Manual, Applicable Standards, and other IDOT Documents relating to Roadside Safety Design

See Chapter 49 for 3R values for Clear Zones

SN 053 SOUTH FOUNDATION GUARDRAIL CALCULATIONS

ONE-WAY ROADWAYS ON TANGENT



- L_B =Distance to barrier
- L_C =Clear zone
- L_H =Distance to back of hazard
- L_F =Distance to front of hazard
- L_R =Runout length
- L_1 =Length needed for approach end
- L_2 =Length of hazard
- L_3 =Length to be omitted from length of need

Design Speed (mph) =	65
Traffic Volume (ADT) =	40600
Lane Width (ft) =	12

L_B (ft) =	8
L_C (ft) =	34
L_H (ft) =	16
L_F (ft) =	13
L_R (ft) =	300
L_2 (ft) =	8.25
L_1 (ft) =	150.0
L_3 (ft) =	11.8

See BDE Figure 38-3A, See BDE Figure 38-3D for CZ Curve Adjustment

Must Insert Number, If Infinity, Insert Number > 30

See BDE Figure 38-6C

NOTE: This tool was created to be an aide, please insure that you have reviewed Chapter 38 (Roadside Safety) of the BDE Manual, Applicable Standards, and other IDOT Documents relating to Roadside Safety Design

See Chapter 49 for 3R values for Clear Zones

FILE NAME =	USER NAME = dssdd	DESIGNED - _____	REVISED - _____
pw:\IL04EB\INTEG\Illinois.gov\PWIDOT\Documents\IDOT Offices\District 2\Projects\Operations\Bridges\Section\Winnebago\46470\SLT200117-2\Design Files\46470-shl\c		DRAWN - _____	REVISED - _____
Default	PLOT SCALE = 100,0000' / in.	CHECKED - _____	REVISED - _____
	PLOT DATE = Sep-25-2018 08:39:04 AM	DATE - _____	REVISED - _____

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


SN 053 SOUTH FOUNDATION
GUARDRAIL CALCULATIONS

SCALE: _____ SHEET _____ OF _____ SHEETS STA. _____ TO STA. _____

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
—	D-2 OVD SIN STR REPL 18-32	VARIOUS	40	36
CONTRACT NO. 46470				
ILLINOIS FED. AID PROJECT				

SN 053 SOUTH FOUNDATION (JOHN DEERE RD EB) GUARDRAIL CALCULATIONS

ONE-WAY ROADWAYS ON TANGENT



- L_B =Distance to barrier
- L_C =Clear zone
- L_H =Distance to back of hazard
- L_F =Distance to front of hazard
- L_R =Runout length
- L_1 =Length needed for approach end
- L_2 =Length of hazard
- L_3 =Length to be omitted from length of need

Design Speed (mph) =	65
Traffic Volume (ADT) =	40600
Lane Width (ft) =	12

L_B (ft) =	16
L_C (ft) =	34
L_H (ft) =	23
L_F (ft) =	21
L_R (ft) =	300
L_2 (ft) =	8.25
L_1 (ft) =	91.3
L_3 (ft) =	11.8


See BDE Figure 38-3A, See BDE Figure 38-3D for CZ Curve Adjustment
 Must Insert Number, If Infinity, Insert Number > 30
 See BDE Figure 38-6C

NOTE: This tool was created to be an aide, please insure that you have reviewed Chapter 38 (Roadside Safety) of the BDE Manual, Applicable Standards, and other IDOT Documents relating to Roadside Safety Design

See Chapter 49 for 3R values for Clear Zones

SN 136 NORTH FOUNDATION GUARDRAIL CALCULATIONS

ONE-WAY ROADWAYS ON TANGENT



- L_B =Distance to barrier
- L_C =Clear zone
- L_H =Distance to back of hazard
- L_F =Distance to front of hazard
- L_R =Runout length
- L_1 =Length needed for approach end
- L_2 =Length of hazard
- L_3 =Length to be omitted from length of need

Design Speed (mph) =	65
Traffic Volume (ADT) =	24500
Lane Width (ft) =	15

L_B (ft) =	8
L_C (ft) =	34
L_H (ft) =	41
L_F (ft) =	38
L_R (ft) =	300
L_2 (ft) =	8.25
L_1 (ft) =	229.4
L_3 (ft) =	71.0


See BDE Figure 38-3A, See BDE Figure 38-3D for CZ Curve Adjustment
 Must Insert Number, If Infinity, Insert Number > 30
 See BDE Figure 38-6C

NOTE: This tool was created to be an aide, please insure that you have reviewed Chapter 38 (Roadside Safety) of the BDE Manual, Applicable Standards, and other IDOT Documents relating to Roadside Safety Design

See Chapter 49 for 3R values for Clear Zones

SN 136 SOUTH FOUNDATION (I-280 EB) GUARDRAIL CALCULATIONS

ONE-WAY ROADWAYS ON TANGENT



- L_B =Distance to barrier
- L_C =Clear zone
- L_H =Distance to back of hazard
- L_F =Distance to front of hazard
- L_R =Runout length
- L_1 =Length needed for approach end
- L_2 =Length of hazard
- L_3 =Length to be omitted from length of need

Design Speed (mph) =	65
Traffic Volume (ADT) =	24500
Lane Width (ft) =	12

L_B (ft) =	27
L_C (ft) =	34
L_H (ft) =	32
L_F (ft) =	29
L_R (ft) =	300
L_2 (ft) =	8.25
L_1 (ft) =	46.9
L_3 (ft) =	4.7

See BDE Figure 38-3A, See BDE Figure 38-3D for CZ Curve Adjustment

Must Insert Number, If Infinity, Insert Number > 30

See BDE Figure 38-6C

NOTE: This tool was created to be an aide, please insure that you have reviewed Chapter 38 (Roadside Safety) of the BDE Manual, Applicable Standards, and other IDOT Documents relating to Roadside Safety Design

See Chapter 49 for 3R values for Clear Zones

FILE NAME =	USER NAME = dssdd	DESIGNED -	REVISED -
pw:\IL084EB\INTEG\Illinois.gov\PWIDOT\Documents\IDOT Offices\District 2\Projects\Operations\Bridges\Section\Winnebago\46470\SLT200\117-2\Design Files\46470-shield\REVISED -			
Default	PLOT SCALE = 100,0000' / in.	CHECKED -	REVISED -
	PLOT DATE = Sep-25-2018 08:40:38 AM	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


SN 136 SOUTH FOUNDATION (I-280 EB)
GUARDRAIL CALCULATIONS

SCALE: _____ SHEET _ OF _ SHEETS STA. _____ TO STA. _____

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	D-2 OVD SIN STR REPL 18-32	VARIOUS	40	39
CONTRACT NO. 46470				
ILLINOIS FED. AID PROJECT				

SN 136 SOUTH FOUNDATION (I-280 WB) GUARDRAIL CALCULATIONS

ONE-WAY ROADWAYS ON TANGENT



- L_B =Distance to barrier
- L_C =Clear zone
- L_H =Distance to back of hazard
- L_F =Distance to front of hazard
- L_R =Runout length
- L_1 =Length needed for approach end
- L_2 =Length of hazard
- L_3 =Length to be omitted from length of need

Design Speed (mph) =	65
Traffic Volume (ADT) =	24500
Lane Width (ft) =	15

L_B (ft) =	28
L_C (ft) =	34
L_H (ft) =	32
L_F (ft) =	29
L_R (ft) =	300
L_2 (ft) =	8.25
L_1 (ft) =	37.5
L_3 (ft) =	2.4

See BDE Figure 38-3A, See BDE Figure 38-3D for CZ Curve Adjustment
Must Insert Number, If Infinity, Insert Number > 30
See BDE Figure 38-6C

NOTE: This tool was created to be an aide, please insure that you have reviewed Chapter 38 (Roadside Safety) of the BDE Manual, Applicable Standards, and other IDOT Documents relating to Roadside Safety Design

See Chapter 49 for 3R values for Clear Zones