NOTES:

THICKNESS AND MATERIALS

- 1. THE WIDTH OF THE FULL DEPTH PATCH OVER A TRENCH SHALL BE 12 (300) WIDER ON EACH SIDE OF THE TRENCH.
- 2. FOR METHOD OF MEASUREMENT AND BASIS OF PAYMENT, SEE RECURRING SPECIAL PROVISION "PATCHING WITH HOT-MIX ASPHALT OVERLAY REMOVAL".

SEQUENCE OF CONSTRUCTION (PATCHING FIRST)

- 1. REMOVE THE EXISTING HMA MATERIAL OVER THE AREA TO BE PATCHED.
- 2. REMOVE AND REPLACE WITH CLASS C OR D PATCH.
- 3. REPLACE HMA MATERIAL OVER THE AREA TO BE PATCHED.

SEQUENCE OF CONSTRUCTION (MILLING FIRST)

- 1. MILL HMA FIRST IF THERE IS AT LEAST 41/2 INCHES OR MORE OF HMA MATERIAL ON TOP OF THE EXISTING PAVEMENT OR IF THE PAVEMENT IS FULL DEPTH HMA. A MINIMUM OF 2 INCHES OF HMA MATERIAL SHALL BE IN PLACE AFTER MILLING.
- 2. REMOVE AND REPLACE WITH FULL DEPTH CLASS D PATCHES TO TOP OF MILLED SURFACE.

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.

FILE NAME = USER NAME = beverel DESIGNED - R. SHAH REVISED - A. ABBAS 04-27-98 PAVEMENT PATCHING FOR DRAWN STATE OF ILLINOIS REVISED - R. BORD D1-01-07 1376 10-00095-00-SW HMA SURFACED PAVEMENT PLOT SCALE = 58.000 '/ IN. CHECKED REVISED - R. BORO 09-04-07 **DEPARTMENT OF TRANSPORTATION** BD400-04 (BD-22) CONTRACT NO. 63511 PLOT DATE = 18/27/2008 DATE - 10-25-94 REVISED - K. ENG 10-27-08 SCALE: NONE SHEET NO. 1 OF 1 SHEETS STA.

ing file: W:\Projects\75019007 - Grand Ave Streetscape State I\93_IDOT_MARKINGS.dwg Aug 17