

SCHEDULE OF QUANTITIES

SHEET 13 OF 14

RAISED REFLECTIVE PAVEMENT MARKER

LOCATION	STATION	TO	STATION	LENGTH (FT)	78100100	78100100	78100100	78300200
					TWO-WAY AMBER QUANTITY (EACH)	ONE-WAY AMBER QUANTITY (EACH)	ONE-WAY CRYSTAL QUANTITY (EACH)	RRPM REMOVAL (EACH)
S.B. C.L.	135+00.00		156+52.00	2152.00			28.0	28.0
S.B. TWLTL	135+00.00		156+52.00	2152.00	55.0			55.0
S.B. TWLTL	157+76.00		159+76.00	200.00	12.0			12.0
S.B. TWLTL	159+76.00		167+78.00	802.00	22.0			22.0
S.B. C.L.	157+76.00		167+78.00	1002.00			14.0	14.0
S.B. TWLTL	168+96.00		170+96.00	200.00	12.0			12.0
S.B. TWLTL	170+96.00		176+20.00	524.00	15.0			15.0
S.B. C.L.	168+96.00		176+20.00	724.00			11.0	11.0
S.B. TWLTL	177+48.00		179+48.00	200.00	12.0			12.0
S.B. TWLTL	179+48.00		182+42.00	294.00	9.0			9.0
S.B. C.L.	177+48.00		182+42.00	494.00			8.0	8.0
S.B. TWLTL	183+22.00		184+06.00	84.00	4.0			4.0
S.B. LT TURN	185+06.00		186+06.00	100.00			4.0	4.0
S.B. C.L.	183+22.00		186+06.00	284.00			5.0	5.0
S.B. TWLTL	187+15.00		189+15.00	200.00	12.0			12.0
S.B. TWLTL	189+15.00		200+40.00	1125.00	30.0			30.0
S.B. C.L.	187+15.00		200+40.00	1325.00			18.0	18.0
S.B. TWLTL	201+20.00		203+20.00	200.00	12.0			12.0
S.B. MEDIAN	203+20.00		206+50.00	330.00	18.0			18.0
S.B. C.L.	201+20.00		211+70.00	1050.00			15.0	15.0
S.B. RT TURN	203+69.00		207+39.00	370.00			11.0	11.0
S.B. RT TURN	208+96.00		211+70.00	274.00			8.0	8.0
S.B. MEDIAN	213+30.00		217+00.00	370.00	20.0			20.0
S.B. C.L.	213+30.00		241+40.00	2810.00			37.0	37.0
S.B. LT TURN	224+17.00		226+55.00	238.00			7.0	7.0
S.B. LT TURN	224+17.00		226+55.00	238.00		7.0		7.0
S.B. LT TURN	238+78.00		241+40.00	262.00		8.0		8.0
S.B. LT TURN	238+78.00		241+40.00	262.00			8.0	8.0
S.B. RT TURN	238+78.00		241+40.00	262.00			8.0	8.0
S.B. RT TURN	238+78.00		241+40.00	262.00			8.0	8.0
S.B. C.L.	242+45.00		295+07.00	5262.00			67.0	67.0
S.B. LT TURN	252+83.00		255+28.00	245.00		8.0		8.0
S.B. LT TURN	252+83.00		255+28.00	245.00			8.0	8.0
S.B. LT TURN	274+74.00		277+12.00	238.00		7.0		7.0
S.B. LT TURN	274+74.00		277+12.00	238.00			7.0	7.0
S.B. LT TURN	292+26.00		295+07.00	281.00		9.0		9.0
S.B. LT TURN	292+26.00		295+07.00	281.00			9.0	9.0
S.B. RT TURN	292+26.00		295+07.00	281.00			9.0	9.0
S.B. RT TURN	292+26.00		294+86.00	260.00			8.0	8.0
S.B. C.L.	296+29.00		348+37.00	5208.00			67.0	67.0
S.B. LT TURN	319+52.00		321+90.00	238.00		7.0		7.0
S.B. LT TURN	319+52.00		321+90.00	238.00			7.0	7.0

RAISED REFLECTIVE PAVEMENT MARKER (CONT.)

LOCATION	STATION	TO	STATION	LENGTH (FT)	78100100	78100100	78100100	78300200
					TWO-WAY AMBER QUANTITY (EACH)	ONE-WAY AMBER QUANTITY (EACH)	ONE-WAY CRYSTAL QUANTITY (EACH)	RRPM REMOVAL (EACH)
S.B. LT TURN	345+77.00		348+60.00	283.00		9.0		9.0
S.B. LT TURN	345+77.00		348+60.00	283.00			9.0	9.0
S.B. RT TURN	345+77.00		348+37.00	260.00			8.0	8.0
S.B. RT TURN	345+77.00		348+37.00	260.00			8.0	8.0
S.B. C.L.	349+40.00		401+62.00	5222.00			67.0	67.0
S.B. LT TURN	356+18.00		358+56.00	238.00		7.0		7.0
S.B. LT TURN	356+18.00		358+56.00	238.00			7.0	7.0
S.B. LT TURN	389+22.00		391+60.00	238.00		7.0		7.0
S.B. LT TURN	389+22.00		391+60.00	238.00			7.0	7.0
S.B. LT TURN	399+23.00		401+62.00	239.00		7.0		7.0
S.B. LT TURN	399+23.00		401+62.00	239.00			7.0	7.0
S.B. C.L.	402+60.00		408+00.00	540.00			8.0	8.0
S.B. MEDIAN	408+00.00		415+00.00	700.00	36.0			36.0
N.B. C.L.	135+00.00		156+52.00	2152.00			28.0	28.0
N.B. TWLTL	135+00.00		136+73.00	173.00	10.0			10.0
N.B. TWLTL	136+73.00		156+52.00	1979.00	51.0			51.0
N.B. C.L.	157+76.00		167+78.00	1002.00			14.0	14.0
N.B. LT TURN	157+76.00		158+76.00	100.00			4.0	4.0
N.B. TWLTL	159+76.00		167+78.00	802.00	22.0			22.0
N.B. C.L.	168+96.00		176+20.00	724.00			11.0	11.0
N.B. LT TURN	168+96.00		169+96.00	100.00			4.0	4.0
N.B. TWLTL	170+96.00		176+20.00	524.00	15.0			15.0
N.B. C.L.	177+48.00		182+42.00	494.00			8.0	8.0
N.B. LT TURN	177+48.00		178+48.00	100.00			4.0	4.0
N.B. TWLTL	179+48.00		182+42.00	294.00	9.0			9.0
N.B. C.L.	183+22.00		186+08.00	286.00			5.0	5.0
N.B. TWLTL	183+22.00		184+06.00	84.00	4.0			4.0
S.B. TWLTL	184+06.00		186+08.00	202.00	14.0			14.0
N.B. RT TURN	187+15.00		188+70.00	155.00			5.0	5.0
N.B. RT TURN	187+15.00		188+70.00	155.00			5.0	5.0
N.B. C.L.	187+15.00		200+40.00	1325.00			18.0	18.0
N.B. LT TURN	187+15.00		188+15.00	100.00			4.0	4.0
N.B. TWLTL	189+15.00		200+40.00	1125.00	30.0			30.0
N.B. C.L.	201+20.00		211+70.00	1050.00			15.0	15.0
N.B. LT TURN	201+20.00		202+20.00	100.00			4.0	4.0
N.B. MEDIAN	203+20.00		206+50.00	330.00	18.0			18.0
N.B. C.L.	213+32.00		241+40.00	2808.00			37.0	37.0
N.B. LT TURN	213+32.00		216+10.00	278.00			8.0	8.0
N.B. LT TURN	213+32.00		216+10.00	278.00			8.0	8.0
N.B. MEDIAN	213+32.00		217+00.00	368.00	20.0			20.0
N.B. LT TURN	227+39.00		229+77.00	238.00			7.0	7.0
N.B. LT TURN	227+39.00		229+77.00	238.00		7.0		7.0