

MAINLINE SCHEDULE

LOCATION IL 53	LENGTH	WIDTH	WIDTH AVG	SHLDR WIDTH BY SIDE	SHLDR WIDTH	AREA PVMT	AREA SHLDR	BITUMINOUS CONC. SURF COURSE SUPERPAVE 1 1/2"	BIT. CONC. LEV. BIND. COURSE SUPERPAVE 3/4"	BIT. PRIME COAT	LEVEL BINDER HAND METHOD	AGG PRIME COAT	BIT SURF REMOVAL 1 1/2"	BIT SURF REMOVAL 2 1/4"	BIT. SURF REM. BUTT JT.	TEMP RAMP	AGG SHLDRS TY B
	FT	FT	FT	FT	FT	SO YD	SO YD	TONS	TONS	GALLONS	TONS	TONS	SO YD	SO YD	SO YD	SO YD	TONS
GRUNDY COUNTY																	
MEDIAN AREA AT I-55 OVERHEAD																	
LOG MI. 0.031 TO 0.056	132.0	40.0	40.0	6' RT, 8' LT	14.0	586.7	205.3	66.5	33.3	63.4	0.4	1.6		792.0		30.0	15.0
LOG MI. 0.056 TO 0.066	52.8	40-42	41	6' RT, 8' LT	14	240.5	82.1	27.1	13.6	25.8	0.2	0.7		322.7			6.0
LOG MI. 0.066 TO 0.078	63.4	46	46	6' RT, 8' LT	14	324.0	98.6	35.5	17.8	33.8	0.2	0.9		422.7			7.2
LOG MI. 0.078 TO 0.082	21.1	46	46	0	0	107.8	0.0	9.1	4.5	8.6	0.1	0.2		107.8			2.4
LOG MI. 0.082 TO 0.092	52.8	28-40	34	0	0	199.5	0.0	16.8	8.4	16.0	0.1	0.4		199.5		181.1	6.0
LOG MI. 0.092 TO 0.108	84.5	28	28	0	0	262.9	0.0	22.1	11.0	21.0	0.1	0.5		262.9			9.6
LOG MI. 0.108 TO 0.177	364.5	28	28	6' RT, 8' LT	14	1134.0	567.0	142.9	71.4	136.1	0.9	3.4		1701.0			41.5
LOG MI. 0.177 TO 0.190	68.6	26-28	27	6' RT, 8' LT	14	205.8	106.7	26.3	13.1	25.0	0.2	0.6		312.5			7.8
IL 53 & IL 129 INTERSECTION	SEE PLAN SHEET	FOR LIMITS															
LOG MI. 0.190 TO 0.260	369.6	VAR	VAR	VAR	VAR	607.3	3617.1	354.8	177.4	338.0	2.1	8.5		4224.4		26.7	
LOG MI. 0.260 TO 0.351	480.5	22	22	5' RT, 5' LT	10	1174.6	533.9	143.5	71.8	222.1	0.9	3.4		1708.4			54.7
LOG MI. 0.351 TO 0.408	300.96	33	33	5' RT, 5' LT	10	1103.5	334.4	120.8	60.4	186.9	0.7	2.9		1437.9			34.3
LOG MI. 0.434 at OLD RT 66 TO 600' S. ON RT. 66	600	22	22	5' RT, 5' LT	10	1466.7	666.7	179.2	89.6	277.3	1.1	4.3		2133.3	142.2	26.7	68.3
LOG MI. 0.408 TO 0.566	834.2	33	33	8' RT, 8' LT	16	3058.7	1483.0	381.5	190.8	590.4	2.3	9.1		4541.8	217.8	26.7	95.0
LOG MI. 0.566 TO 0.622	295.7	RAILROAD BRIDGE OMISSION															
LOG MI. 0.622 TO 0.736	601.9	22	22	8' RT, 8' LT	16	1471.3	1070.0	213.5	106.7	330.4	1.3	5.1		2541.4	168.9	21.1	68.5
LOG MI. 0.736 TO 0.831	501.6	22	22	5' RT, 5' LT	10	1226.1	557.3	149.8	74.9	231.9	0.9	3.6		1783.5			57.1
LOG MI. 0.831 TO 1.982	6077.3	24	24	0	0	16206.1	0.0	1361.3	680.7	2106.8	8.1	32.4	16206.1				692.1
LOG MI. 1.982 TO 2.148	876.5	26	26	3' RT, 3' LT	6	2532.1	584.3	261.8	130.9	405.1	1.6	6.2		3116.4			99.8
LOG MI. 2.148 TO 3.187	5485.9	24	24	0	0	14629.1	0.0	1228.8	614.4	1901.8	7.3	29.3	14629.1				624.8
LOG MI. 3.187 TO 3.389	1066.5	24	24	3' RT, 3' LT	6	2844.0	711.0	298.6	149.3	462.2	1.8	7.1	3555.0		133.3	16.7	121.5
LOG MI. 3.389 TO 3.430	216.5	SN 032-0023 OVER MAZON RIVER BRIDGE OMISSION															
LOG MI. 3.430 TO 3.781	1853.3	24	24	3' RT, 3' LT	6	4942.1	1235.5	518.9	259.5	803.1	3.1	12.4	6177.7		133.3	16.7	211.1
LOG MI. 3.781 TO 4.840	5591.52	24	24	0	0	14910.7	0.0	1252.5	626.3	1938.4	7.5	29.8	14910.7				636.8
BRACEVILLE RD. INTERSECTION	SEE PLAN SHEET	FOR LIMITS															
LOG MI. 4.840 TO 4.896	295.7	27-35.5	31.25	4' RT, 4' LT	8	1026.7	262.8	108.3	54.2	167.6	0.6	2.6		1289.6			33.7
LOG MI. 4.896 TO 4.935	205.9	35.5	35.5	4' RT, 4' LT	8	812.2	183.0	83.6	41.8	129.4	0.5	2.0		995.2			23.4
LOG MI. 4.935 TO 4.983	253.4	VAR.	VAR.	VAR.	VAR.	333.7	1948.8	191.7	95.9	182.6	1.1	4.6		2282.5			
LOG MI. 4.983 TO 5.013	158.4	35.5	35.5	4' RT, 8' LT	12	624.8	211.2	70.2	35.1	66.9	0.4	1.7		836.0		26.7	18.0
LOG MI. 5.013 TO 5.028	79.2	35-31	33	4' RT, 8' LT	12	290.4	105.6	33.3	16.6	31.7	0.2	0.8		396.0		16.7	9.0
LOG MI. 5.028 TO 5.076	253.4	31-27	29	4' RT, 4' LT	8	816.5	225.2	87.5	43.8	83.3	0.5	2.1		1041.8			28.9
LOG MI. 5.076 TO 6.440	7201.9	24	24	0	0	19205.1	0.0	1613.2	806.6	2496.7	9.6	38.4	19205.1		80.0	13.3	820.2
TOTAL	34439.6					92343.0	14789.8	9000	4500	13283	53.8	215	74684	32450	875	403	3793