

PERIMETER EROSION BARRIER

LOCATION	QUANTITY
STATION	OFFSET (FOOT)
81+97.90 TO 82+36.50	LT 51.3
81+97.90 TO 83+70.20	RT 241.6
82+61.50 TO 85+53.80	LT 282.6
84+28.80 TO 86+20.50	RT 233.0
85+66.70 TO 87+46.00	LT 187.3
86+14.80 TO 86+79.30	RT 51.9
TOTAL	1047.6

TEMPORARY SEDIMENT TRAP

LOCATION	QUANTITY
STA.	OFFSET (EACH)
87+00.00	32.7' RT 1
87+50.00	20.0' RT 1
TOTAL	2

PROTECTIVE COAT

LOCATION	QUANTITY	
STATION	(SQ FT)	(SQ YD)
SIDEWALK		
82+62.80 TO 85+58.90	LT 1844.0	204.9
84+23.80 TO 85+88.60	RT 1385.2	153.9
85+81.90 TO 91+31.90	LT 3309.2	367.7
86+11.70 TO 91+40.00	RT 2880.0	320.0
CURB & GUTTER TYB-6.12		
82+59.93 TO 82+98.48	LT 104.5	11.6
83+21.74 TO 83+71.75	RT 201.4	22.4
84+22.24 TO 85+00.00	RT 284.8	31.6
90+81.62 TO 91+41.62	RT 189.3	21.0
90+94.06 TO 91+34.06	LT 158.8	17.6
CURB & GUTTER TYB-6.24		
82+98.48 TO 90+94.06	LT 2394.5	266.1
85+00.00 TO 90+81.62	RT 1707.0	189.7
	SUBTOTAL	1606.5
		X 2 COATS
	TOTAL	3213.0

PIPE CULVERT REMOVAL

LOCATION	QUANTITY
STATION	OFFSET (FOOT)
82+06.60 TO 82+92.80	LT 87
TOTAL	87

INLET AND PIPE PROTECTION

LOCATION	QUANTITY
STA.	OFFSET (EACH)
82+00.00	34.8' LT 1
83+54.00	22.5' LT 1
83+62.93	50.5' RT 1
84+00.00	36.2' LT 1
84+32.84	51.5' RT 1
87+50.00	22.6' LT 1
87+50.00	35.5' LT 1
89+25.00	22.6' LT 1
89+25.00	20.0' RT 1
90+83.70	18.7' RT 1
90+95.00	21.3' LT 1
TOTAL	11

COMBINATION CURB AND GUTTER REMOVAL

LOCATION	QUANTITY
STATION	OFFSET (FOOT)
82+21.16 TO 82+38.22	LT 25.6
82+60.61 TO 82+82.74	LT 32.4
83+20.03 TO 83+71.75	RT 98.0
84+22.24 TO 86+69.15	RT 292.1
86+19.91 TO 91+33.17	LT 508.8
91+35.00 TO 91+41.62	RT 36.1
TOTAL	993.0

GUTTER OUTLET REMOVAL

LOCATION	QUANTITY
STATION	OFFSET (FOOT)
86+70.15 TO 87+00.26	LT 29.8
88+72.59 TO 89+02.10	LT 29.8
TOTAL	59.6

PIPE CULVERTS, CLASS A, TYPE 2, 18"

LOCATION	QUANTITY
STATION	OFFSET (FOOT)
82+00.00 TO 83+00.00	LT 100.7
84+00.00 TO 84+40.00	LT 40.3
TOTAL	141.0

BITUMINOUS MATERIAL (PRIME COAT)

LOCATION	QUANTITY	
STATION	(SQ YD)	(TON)
HMA SURFACE COURSE	6366.6	2.4
HMA BINDER COURSE	5481.3	2.1
TOTAL		4.5

AGGREGATE (PRIME COAT)

LOCATION	QUANTITY
STATION TO STATION	(TON)
81+97.89 TO 91+55.94	16.2
TOTAL	16.2

PORTLAND CEMENT CONCRETE SIDEWALK, 5 INCH

LOCATION	QUANTITY
STATION	OFFSET (SQ FT)
82+62.80 TO 85+58.90	LT 1844.0
84+23.80 TO 85+88.60	RT 1385.5
85+81.90 TO 91+31.90	LT 3309.5
86+11.70 TO 91+40.00	RT 2880.0
TOTAL	9419.0

SIDEWALK REMOVAL

LOCATION	QUANTITY
STATION	OFFSET (SQ FT)
84+23.90 TO 84+78.50	RT 469.9
91+18.90 TO 91+32.20	LT 139.9
91+33.30 TO 91+39.90	RT 163.2
TOTAL	773.0

PRECAST REINFORCED CONCRETE FLARED END SECTIONS, 12"

LOCATION	QUANTITY
STATION	OFFSET (EACH)
83+54.00	32.5' LT 1
86+35.00	59.5' RT 1
TOTAL	2

CONSTRUCTING TEST STRIP

LOCATION	QUANTITY
JOBSITE	(EACH)
	4
TOTAL	4

INCIDENTAL HOT-MIX ASPHALT SURFACING

LOCATION	QUANTITY
*JOBSITE	(TON)
	30
TOTAL	30

DETECTABLE WARNINGS

LOCATION	QUANTITY
STATION	(SQ FT)
82+64.20 TO 82+66.20	LT 10.0
91+28.00 TO 91+30.00	LT 26.0
TOTAL	36.3

BITUMINOUS CONCRETE SHOULDER REMOVAL

LOCATION	QUANTITY
STATION	OFFSET (SQ YD)
81+97.89 TO 82+22.00	LT 18.5
81+97.89 TO 83+19.80	RT 49.8
82+81.80 TO 84+67.20	RT 74.6
86+69.20 TO 90+87.60	RT 289.1
TOTAL	432.0

STRIP REFLECTIVE CRACK CONTROL TREATMENT

LOCATION	QUANTITY
STATION	(FOOT)
81+97.89 TO 92+72.60	2152
TOTAL	2152

PRECAST REINFORCED CONCRETE FLARED END SECTIONS, 15"

LOCATION	QUANTITY
STATION	OFFSET (EACH)
87+00.00	32.7' RT 1
TOTAL	1

PAVEMENT REMOVAL

LOCATION	QUANTITY
STATION	(SQ YD)
OAK PARK AVE.	
81+97.89 TO 85+50.94	1710.8
86+21.02 TO 91+55.94	2221.7
COMMERCIAL ENTRANCE	
81+97.89 TO 82+92.99 (LT)	137.9
WEST POINT DR.	125.9
83+19.79 TO 85+00.00 (RT)	549.5
SOUTH POINT DR.	
90+97.23 TO 91+55.94 (LT)	172.0
90+87.64 TO 91+55.94 (RT)	173.0
TOTAL	5090.8

HOT-MIX ASPHALT SHOULDERS, 8"

LOCATION	QUANTITY
STATION TO STATION	(SQ YD)
81+97.89 TO 82+38.20	LT 24.3
81+97.89 TO 82+98.80	RT 46.7
TOTAL	71.0

PRECAST REINFORCED CONCRETE FLARED END SECTIONS, 18"

LOCATION	QUANTITY
STATION	OFFSET (EACH)
82+00.00	34.8' LT 1
83+00.00	33.8' LT 1
84+00.00	36.2' LT 1
84+40.00	40.9' LT 1
TOTAL	4

*ESTIMATED QUANTITY