

F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
2516	08-00037-00-RS	KENDALL	20	02
CONTRACT NO. 87377				

GENERAL NOTES AND CONSTRUCTION SPECIFICATIONS

- The "Standard Specifications for Road and Bridge Construction" adopted Jan. 1, 2007, Supplemental Specifications and Recurring Specifications and Provisions adopted Jan. 1, 2009, National Electric Code, 2008 edition, the "Standard Specifications for Water and Sewer Main Construction in Illinois", fifth edition, dated May, 1996, and revisions thereto, these improvement plans and details, special provisions and codes and ordinances of the United City of Yorkville, Illinois shall govern applicable portions of this project.
- The Contractor shall obtain, erect, maintain and remove all signs, barricades, flaggers and other traffic control devices as may be necessary for the purpose of regulating, warning or guiding traffic. Placement and maintenance of all traffic control devices shall be in accordance with the applicable parts of Article 107.14 of the Standard specifications and the Illinois Manual on Uniform Traffic Control Devices for Streets and Highways.
- Location of utilities shown on plans are approximate only, and are not necessarily complete. Contractor shall make his own investigations as to location of all existing underground structures, cables and pipe lines.
- All elevations are based on U.S.G.S. Datum.
- All road signs, street signs and traffic signs which need to be relocated or moved due to construction shall be taken down and stored by the Contractor except those that are necessary for proper traffic control which shall be temporarily reset until completion of construction operations. After completion of the work, the Contractor shall reset all said signs. The work shall be included in the traffic control pay items, and shall not be paid for separately.
- Special attention is drawn to the fact that Article 105.06 of the standard specifications requires the Contractor to have a competent superintendent on the project site at all times, irrespective of the amount of work sublet. The superintendent shall be capable of reading and understanding the plans and specifications, shall have full authority to execute orders to expedite the project, shall be responsible for scheduling and have control of all work as the agent of the Contractor. Failure to comply with this provision will result in a suspension of work as provided in Article 108.08.
- Any reference to standards throughout the plans or special provisions shall be interpreted as the latest standard of the department as shown on the plans.
- The Contractor shall protect and carefully preserve all section or subsection monuments or property or reference markers until the owner, his agent or an authorized surveyor has witnessed or otherwise referenced their locations.
- The unit price for all removal pay items shall include all required saw cuts.
- All work performed relative to this improvement shall comply with all applicable rules and regulations of O.S.H.A.
- Contractor shall provide and install two weighted sand bags on each Type I or Type II Barricade used. (One weighted sand bag across each bottom rail.) This work will not be paid for separately. But the cost shall be considered as included in the contract unit price for the construction items involved and no additional compensation will be allowed.
- Before starting any excavation, the Contractor shall call "JULIE" at 800-892-0123 for field locations of buried electric, telephone and gas facilities. (48 hour notification is required)
- 10 feet transitions shall be used to match proposed curb & gutter and median items of work to existing curbs & gutters and medians in the field, unless otherwise shown. The transitions shall be paid for at the contract unit price for the proposed items of work specified.
- The Contractor shall coordinate construction activities with utility companies and the United City of Yorkville.
- When milled pavement is open to traffic the maximum grade differential between passes of the milling machine shall not exceed 1/8 inches (40 mm) where the speed limit is 45 mph (80 km/h) or less and 1 inch (25 mm) where the speed limit is greater than 45 mph (80 km/h). With written approval from the Engineer, a maximum grade differential of 3 inches (75 mm) may be allowed if the edge of the milling is sloped a minimum 1:3 (V:H).
- Butt joints will be installed at the ends of all resurfacing (where the resurfacing meets existing pavement) in accordance with the "HMA Detail at Butt Joints" sheet included in the plans, unless otherwise specified.

- Whenever, during construction operations any loose material is deposited in the flow line of drainage structures such that the natural flow of water is obstructed, it shall be removed at the close of each working day. At the conclusion of construction operations, all drainage structures shall be free from dirt and debris. The work specified above will not be paid for separately, but shall be considered as included in the contract pay items.
- Existing public and private utilities are shown on the plans according to information obtained from utility companies, municipalities, and surveys. The Contractor shall familiarize himself with the location of all utilities and structures that may be found in the vicinity of the construction. He will also assume responsibility for all utilities whether shown or not, and must realize that the actual locations and/or elevations of the utilities may be different that indicated.

Should any damages occur due to the Contractor's negligence, the Contractor, at his own expense, shall make repairs in a manner acceptable to the Engineer. The Contractor shall notify all utility companies of his construction schedule and coordinate construction operations with the utility companies so that relocation of utility lines and structures may proceed in an orderly manner.
- During Construction, if the Contractor encounters or otherwise becomes aware of any sewer, underdrains or field drains within the right-of-way other than those shown on the plans, he shall so inform the Engineer who shall direct the work necessary to maintain or to replace the facilities in service and to protect them from damage during construction if to be maintained. Existing facilities to be maintained that are damaged because of non-compliance with this provision shall be replaced at the Contractor's own expense.
- All mailbox turnouts and driveway turnouts for aggregate driveways shall be installed according to state standard 406201-01.

INDEX OF SHEETS

SHEET NO.	SHEET DESCRIPTION
1.	COVER SHEET AND LOCATION MAP
2.	GENERAL NOTES, STATE STANDARDS, AND INDEX OF SHEETS
3.	SUMMARY OF QUANTITIES
4.	TYPICAL EXISTING AND PROPOSED CROSS SECTIONS
5.	PLAN & PROFILE - FOX ROAD - STA 10+00 TO STA 15+50
6.	PLAN & PROFILE - FOX ROAD - STA 15+50 TO STA 21+00
7.	PLAN & PROFILE - FOX ROAD - STA 21+00 TO STA 26+50
8.	PLAN & PROFILE - FOX ROAD - STA 26+50 TO STA 32+00
9.	PLAN & PROFILE - FOX ROAD - STA 32+00 TO STA 37+50
10.	PLAN & PROFILE - FOX ROAD - STA 37+50 TO STA 43+00
11.	PLAN & PROFILE - FOX ROAD - STA 43+00 TO STA 48+50
12.	PLAN & PROFILE - FOX ROAD - STA 48+50 TO STA 54+00
13.	PLAN & PROFILE - FOX ROAD - STA 54+00 TO STA 59+50
14.	PLAN & PROFILE - FOX ROAD - STA 59+50 TO STA 65+00
15.	PLAN & PROFILE - FOX ROAD - STA 65+00 TO STA 68+25
16.	INTERSECTION IMPROVEMENT PLAN - FOX ROAD & MAIN STREET
17.	DETAILS DISTRICT THREE CADD DETAILS
18.	406-1 RURAL MAILBOX TURNOUT DETAILS
19.	406-8 HMA DETAIL AT BUTT JOINTS
20.	780-3 TYPICAL SPACING DETAIL FOR CROSSWALKS AND STOPBARS

LEGEND

EXISTING	DESCRIPTION	PROPOSED
	SANITARY SEWER	
	STORM SEWER	
	END SECTION	
	WATER MAIN & SIZE	
	WATER SERVICE & BOX	
	CONTOUR	
	GAS MAIN	
	TELEPHONE CABLE	
	MANHOLE	
	CATCH BASIN	
	INLET	
	HYDRANT	
	VALVE VAULT	
	TREE	
	ELEVATION	
	STREET LIGHT	
	SIGNS	
	FOUND IRON PIPE	
	GUY WIRE	
	FLAG POLE	
	UTILITY POLE	
	UTILITY PEDESTAL	
	HANDHOLE	

STATE STANDARDS

STD. NO.	DESCRIPTION
000001-05	STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS
406201-01	MAILBOX TURNOUT
424001-05	CURB RAMPS FOR SIDEWALKS
442201-03	CLASS C AND D PATCHES
542301-02	PRECAST REINFORCED CONCRETE FLARED END SECTION
604001-03	FRAME AND LIDS - TYPE 1
606001-04	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
701201-03	LANE CLOSURE 2L 2W - DAY ONLY
701306-02	LANE CLOSURE 2L, 2W SLOW MOVING OPERATIONS- DAY ONLY, FOR SPEEDS >45 MPH
701501-05	URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED
701801-04	LANE CLOSURE MULTI LANE, 1W 2W - CROSSWALK OR SW CLOSURE
701901-01	TRAFFIC CONTROL DEVICES
780001-02	TYPICAL PAVEMENT MARKINGS
781001-03	TYPICAL APPLICATION RAISED REFLECTIVE MARKERS

Plotted: Jan 28, 2009 @ 11:26am - Plotted By: kpaung - Tab: 02 - SPECNS (22x34)

COPYRIGHT © 2009 ENGINEERING ENTERPRISES, INC.

Engineering Enterprises, Inc.
 Consulting Engineers
 52 Wheeler Road
 Sugar Grove, Illinois 60554 630/466-9350

UNITED CITY OF YORKVILLE
 800 GAME FARM ROAD
 YORKVILLE, ILLINOIS 60560

NO.	DATE	REVISIONS
1	01/28/09	PER IDOT REVIEW

FOX ROAD LAPP IMPROVEMENTS

GENERAL NOTES, STATE STANDARDS, AND INDEX OF SHEETS

DATE: SEPT, 2008
 PROJECT NO: Y00815
 FILE NO: Y00815-CVR
 SHEET **2** OF **20**

PATH = H:\Users\erj\Y00815\eng\Y00815-Cvr.dwg