



Illinois Department
of Transportation

Division of Highways
SCI Engineering, Inc.

FAP 665 (IL 116) & FAP

SOIL BORING LOG

Page 1 of 1

Date 1/6/09

ROUTE 534 (IL 94) DESCRIPTION Culvert Boring LOGGED BY SCI
(136, 137)W&RS-3; 136R;
SECTION 109BR-2 LOCATION Media Township; NE 1/4, SEC. 17, TWP. 9N, RNG. 4W,
COUNTY Henderson DRILLING METHOD Hand Auger HAMMER TYPE N/A

STRUCT. NO. _____
Station _____
BORING NO. 29
Station 97+35
Offset 80.00ft Lt
Ground Surface Elev. 645.0 ft
Surface Water Elev. _____ ft
Stream Bed Elev. _____ ft
Groundwater Elev.:
First Encounter 644.0ft
Upon Completion 643.5 ft
After - Hrs. Backfilled ft

DEPTH (ft)	DIAMETER (ft)	UNIFORMITY COEFFICIENT (tsf)	PERCENT PASSING NO. 20 (SPT)	DESCRIPTION
0				SILTY CLAY LOAM: Grayish brown (A-7)
0.5		0.5	44	Concrete and asphalt rubble in area of culvert to approximately 40 feet north of culvert end.
1.0		1.0	21	CLAY LOAM: Brown and gray (A-7)
2.8		2.8	19	Qu (tsf) results were performed on auger cuttings. Grades to trace fine gravel at 4 feet. Becomes harder to hand auger at 4 feet.
2.5		2.5	18	SANDY LOAM: Brown (A-4)
2.5		2.5	18	CLAY LOAM: Grayish brown (A-7)
8.0				End of Boring at 8.0 ft.

The Unconfined Compressive Strength (UCS) Failure Mode is Indicated by (B-Bulge, S-Shear, P-Penetrator)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)
AASHTO Classifications are based on visual classifications unless otherwise noted. BBS, form 137 (Rev. 8-99)



Illinois Department
of Transportation

Division of Highways
SCI Engineering, Inc.

FAP 665 (IL 116) & FAP

SOIL BORING LOG

Page 1 of 1

Date 12/10/08

ROUTE 534 (IL 94) DESCRIPTION Culvert Boring LOGGED BY SCI
(136, 137)W&RS-3; 136R;
SECTION 109BR-2 LOCATION Media Township; NE 1/4, SEC. 17, TWP. 9N, RNG. 4W,
COUNTY Henderson DRILLING METHOD CME 45 w/HSA HAMMER TYPE Automatic

STRUCT. NO. _____
Station _____
BORING NO. 30
Station 97+63
Offset 16 ft Lt
Ground Surface Elev. 662.9 ft
Surface Water Elev. _____ ft
Stream Bed Elev. _____ ft
Groundwater Elev.:
First Encounter 643.9 ft
Upon Completion 641.9 ft
After - Hrs. Backfilled ft

DEPTH (ft)	DIAMETER (ft)	UNIFORMITY COEFFICIENT (tsf)	PERCENT PASSING NO. 20 (SPT)	DESCRIPTION
0				FILL: Dark brown and brown silty clay (A-6)
2				CLAY LOAM: Gray and brown, trace fine gravel (A-7) (continued)
3		3.5	24	
3		P		
2				Becomes brown
2		1.3	26	
3		P		
637.9				End of Boring at 25.0 ft.
2				
2		1.0	30	
3		P		
654.9				CLAY: Brown and gray (A-7)
2				
3		1.8	25	
3		B		
2				Becomes grayish brown
2		0.6	30	
2		B		
1				Becomes gray
2		0.8	32	
2		B		
646.4				SILTY CLAY: Gray (A-7)
1				
1		0.6	30	
2		B		
643.7				
1				
1		<0.25	45	
2		P		

The Unconfined Compressive Strength (UCS) Failure Mode is Indicated by (B-Bulge, S-Shear, P-Penetrator)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)
AASHTO Classifications are based on visual classifications unless otherwise noted. BBS, form 137 (Rev. 8-99)