



Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

April 14, 2015

SUBJECT: FAu Route 1300 (Central Road)
Section 08-00201-00-BT (Des Plaines)
Cook County
Contract No. 63210
Item 043
April 24, 2015 Letting
Addendum A

NOTICE TO PROSPECTIVE BIDDERS:

Due to clarify information necessary to revise the following:

- 1. Deleted the Special Provision HMA-Quantity Correction (BMPR) from page 29**

Prime contractors must utilize the enclosed material when preparing their bid and must include any Schedule of Prices changes in their bidding proposal.

Bidders using computer-generated bids are cautioned to reflect any and all Schedule of Prices changes, if involved, into their computer programs.

Very truly yours,

John Baranzelli, P.E.
Acting Engineer of Design and Environment

A handwritten signature in cursive script, reading "Ted B. Walschleger P.E.", with a small "P.E." to the right.

By: Ted B. Walschleger, P.E.
Engineer of Project Management

INDEX OF SPECIAL PROVISIONS

LOCATION OF PROJECT.....	1
DESCRIPTION OF PROJECT.....	1
STATUS OF UTILITIES TO BE ADJUSTED	2
MAINTENANCE OF ROADWAYS.....	4
TRAFFIC CONTROL PLAN.....	5
TRAFFIC CONTROL AND PROTECTION (ARTERIALS).....	6
PUBLIC CONVENIENCE AND SAFETY (DIST 1).....	7
TEMPORARY INFORMATION SIGNING.....	8
HMA MIXTURE DESIGN REQUIREMENTS (D-1).....	10
AGGREGATE SUBGRADE IMPROVEMENT (D-1)	25
SLIPFORM PAVING (D-1).....	28
HOT MIX ASPHALT - QUANTITY CORRECTION	29
SOLAR-POWERED FLASHING BEACON ASSEMBLY (COMPLETE).....	30
TRAFFIC SIGNAL SPECIFICATIONS FOR DETECTOR REPLACEMENT AND/OR INSTALLATION ON ROADWAY GRINDING, RESURFACING, & PATCHING OPERATIONS (D-1).....	33
STEEL PLATE BEAM GUARDRAIL, TYPE A (SPECIAL).....	37
REMOVAL AND DISPOSAL OF REGULATED SUBSTANCES.....	38
REBUILD EXISTING HANDHOLE.....	45
ADJUSTMENTS AND RECONSTRUCTIONS.....	46
DRAINAGE AND UTILITY STRUCTURES TO BE ADJUSTED	47
CONSTRUCTION LAYOUT STAKES.....	48
TRAFFIC SIGNAL SPECIFICATIONS.....	51
GROUND TIRE RUBBER (GTR) MODIFIED ASPHALT BINDER (D-1).....	109
RECLAIMED ASPHALT PAVEMENT AND RECLAIMED ASPHALT SHINGLES (D-1).....	111
COARSE AGGREGATE FOR BACKFILL, TRENCH BACKFILL AND BEDDING (D-1)	122
DRAINAGE AND INLET PROTECTION UNDER TRAFFIC (DISTRICT 1)	123
IDOT TRAINING PROGRAM GRADUATE ON-THE-JOB TRAINING SPECIAL PROVISION	125
REQUIREMENTS REGARDING FLAGGING AND CABLE LOCATION FOR CONSTRUCTION ON CN	127
REQUEST FOR FLAGGING SERVICES AND CABLE LOCATION	128
RIGHT OF ENTRY (ROE) LICENSE AGREEMENT INFORMATION	129
STORM WATER POLLUTION PREVENTION PLAN	134

revised 4-14-15

~~HOT MIX ASPHALT - QUANTITY CORRECTION (BMIPR)~~

~~Effective: October 1, 2014
Revised: October 2, 2014~~

Revise the fifth paragraph of Article 406.13(b) of the Standard Specifications to read as follows:

"HMA and Stone Matrix Asphalt (SMA) mixture in excess of 103 percent of the quantity shown on the plans or the plan quantity as specified by the Engineer will not be measured for payment. The "adjusted quantity to be placed" and the "adjusted pay quantity" for HMA and SMA mixtures will be calculated as follows.

Adjusted Quantity To Be Placed = C x quantity shown on the plans or the plan quantity as specified by the Engineer

where: C = English: $C = \frac{G_{mb} \times 46.8}{U}$ Metric: $C = \frac{G_{mb} \times 24.99}{U}$

and where: G_{mb} = average bulk specific gravity from approved mix design
U = unit weight of HMA shown on the plans in lb/sq yd/in.
(Kg/sq m/25 mm), used to estimate plan quantity
46.8 = English constant
24.99 = metric constant

Adjusted Pay Quantity (not to exceed 103 percent of the quantity shown on the plans or the plan quantity as specified by the Engineer) = B x HMA tons actually placed

where: $B = \frac{1}{C}$

If project circumstances warrant a new mix design, the above equations shall be used to calculate the adjusted plan quantity and adjusted pay quantity for each mix design using its respective average bulk specific gravity."