



Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

April 14, 2015

SUBJECT: Station Boulevard
Project CMM-4003(287)
Section 13-00300-00-PK (Aurora)
DuPage County
Contract No. 61B33
Item 174
April 24, 2015 Letting
Addendum (A)

NOTICE TO PROSPECTIVE BIDDERS:

Due to clarify information necessary to revise the following:

- 1. Deleted Hot Mix Asphalt – Quantity Correction (BMPR) from the Table of Contents for the Special Provisions.**
- 2. Deleted Hot Mix Asphalt – Quantity Correction (BMPR) from Pages 27 and 28 of the Special Provisions.**

Prime contractors must utilize the enclosed material when preparing their bid and must include any Schedule of Prices changes in their bidding proposal.

Bidders using computer-generated bids are cautioned to reflect any and all Schedule of Prices changes, if involved, into their computer programs.

Very truly yours,

John Baranzelli, P.E.
Acting Engineer of Design and Environment

A handwritten signature in black ink, appearing to read 'Ted B. Walschleger P.E.' with a stylized flourish at the end.

By: Ted B. Walschleger, P.E.
Engineer of Project Management

TABLE OF CONTENTS

LOCATION OF PROJECT.....	1
DESCRIPTION OF PROJECT.....	1
SOILS INFORMATION.....	1
PROGRESS SCHEDULE.....	1
RESTRICTION ON CLOSURE OF COMMUTER PARKING SPACES.....	2
COMPLETION DATE PLUS WORKING DAYS.....	2
SUBMITTALS.....	2
MAINTENANCE OF ROADWAYS.....	2
TRAFFIC CONTROL PLAN.....	3
TEMPORARY INFORMATION SIGNING.....	4
STATUS OF UTILITIES TO BE ADJUSTED.....	5
TEMPORARY PAVEMENT.....	6
ADJUSTMENTS AND RECONSTRUCTIONS.....	7
AGGREGATE SUBGRADE IMPROVEMENT (D-1).....	8
COARSE AGGREGATE FOR BACKFILL, TRENCH BACKFILL AND BEDDING (D-1).....	10
DRAINAGE AND INLET PROTECTION UNDER TRAFFIC (D-1).....	10
GROUND TIRE RUBBER (GTR) MODIFIED ASPHALT BINDER (D-1).....	12
HMA MIXTURE DESIGN REQUIREMENTS (D-1).....	13
HOT MIX ASPHALT - QUANTITY CORRECTION (BMPP).....	27
RECLAIMED ASPHALT PAVEMENT AND RECLAIMED ASPHALT SHINGLES (D-1).....	28
HEAT OF HYDRATION CONTROL FOR CONCRETE STRUCTURES (D-1).....	38
DRILLED SOLDIER PILE RETAINING WALL.....	38
IDOT DISTRICT 1 TRAFFIC SIGNAL SPECIFICATIONS.....	44
MAST ARM SIGN PANELS.....	44
SUBMITTALS.....	44
INSPECTION OF ELECTRICAL SYSTEMS.....	46
MAINTENANCE AND RESPONSIBILITY.....	46
DAMAGE TO TRAFFIC SIGNAL SYSTEM.....	48
TRAFFIC SIGNAL INSPECTION (TURN-ON).....	48
LOCATING UNDERGROUND FACILITIES.....	52
RESTORATION OF WORK AREA.....	52
ELECTRIC SERVICE INSTALLATION.....	52
GROUNDING OF TRAFFIC SIGNAL SYSTEMS.....	55

Revised 4/14/15

the Department. The mix sample shall be tested according to the Illinois Modified AASHTO T 324 and shall meet the requirements specified herein. Mix production shall not exceed 1500 tons (1350 metric tons) or one day's production, whichever comes first, until the testing is completed and the mixture is found to be in conformance. The requirement to cease mix production may be waived if the plant produced mixture demonstrates conformance prior to start of mix production for a contract.

The Department may conduct additional Hamburg Wheel Tests on production material as determined by the Engineer. If the mixture fails to meet the Hamburg Wheel criteria, no further mixture will be accepted until the Contractor takes such action as is necessary to furnish a mixture meeting the criteria"

The Contractor shall immediately cease production upon notification by the Engineer of failing Hamburg Wheel test. All prior produced material may be paved out provided all other mixture criteria are being met. No additional mixture shall be produced until the Engineer receives passing Hamburg Wheel tests.

Method of Measurement:

Add the following after the fourth paragraph of Article 406.13 (b):

"The plan quantities of SMA mixtures shall be adjusted using the actual approved binder and surface Mix Design's G_{mb} ."

Basis of Payment:

Replace the seventh paragraph of Article 406.14 of the Standard Specifications with the following:

"For all mixes designed and verified under the Hamburg Wheel criteria, the cost of furnishing and introducing anti-stripping additives in the HMA will not be paid for separately, but shall be considered as included in the contract unit price of the HMA item involved.

No additional compensation will be awarded to the Contractor because of reduced production rates associated with the addition of the anti-stripping additive."

~~HOT MIX ASPHALT - QUANTITY CORRECTION (BMPP)~~

~~Effective: October 1, 2014~~

~~Revised: October 2, 2014~~

~~Revise the fifth paragraph of Article 406.13(b) of the Standard Specifications to read as follows:~~

~~"HMA and Stone Matrix Asphalt (SMA) mixture in excess of 103 percent of the quantity shown on the plans or the plan quantity as specified by the Engineer will not be measured for payment. The "adjusted quantity to be placed" and the "adjusted pay quantity" for HMA and SMA mixtures will be calculated as follows.~~

~~Adjusted Quantity To Be Placed = C x quantity shown on the plans or the plan quantity as specified by the Engineer~~

~~where: C = English: $C = \frac{G_{mb} \times 46.8}{U}$ Metric: $C = \frac{G_{mb} \times 24.99}{U}$~~

~~and where: G_{mb} = average bulk specific gravity from approved mix design
 U = unit weight of HMA shown on the plans in lb/sq yd/in.
 (kg/sq m/25 mm), used to estimate plan quantity
 46.8 = English constant
 24.99 = metric constant~~

~~Adjusted Pay Quantity (not to exceed 103 percent of the quantity shown on the plans or the plan quantity as specified by the Engineer) = B x HMA tons actually placed~~

~~where: $B = \frac{1}{C}$~~

~~If project circumstances warrant a new mix design, the above equations shall be used to calculate the adjusted plan quantity and adjusted pay quantity for each mix design using its respective average bulk specific gravity."~~

RECLAIMED ASPHALT PAVEMENT AND RECLAIMED ASPHALT SHINGLES (D-1)

Effective: November 1, 2012

Revise: January 2, 2015

Revise Section 1031 of the Standard Specifications to read:

"SECTION 1031. RECLAIMED ASPHALT PAVEMENT AND RECLAIMED ASPHALT SHINGLES

1031.01 Description. Reclaimed asphalt pavement and reclaimed asphalt shingles shall be according to the following.

- (a) Reclaimed Asphalt Pavement (RAP). RAP is the material resulting from cold milling or crushing an existing hot-mix asphalt (HMA) pavement. RAP will be considered processed FRAP after completion of both crushing and screening to size. The Contractor shall supply written documentation that the RAP originated from routes or airfields under federal, state, or local agency jurisdiction.
- (b) Reclaimed Asphalt Shingles (RAS). Reclaimed asphalt shingles (RAS). RAS is from the processing and grinding of pre-consumer or post-consumer shingles. RAS shall be a clean and uniform material with a maximum of 0.5 percent unacceptable material, as defined in Bureau of Materials and Physical Research Policy Memorandum "Reclaimed Asphalt Shingle (RAS) Sources", by weight of RAS. All RAS used shall come from a Bureau of Materials and Physical Research approved processing facility where it shall be ground and processed to 100 percent passing the 3/8 in. (9.5 mm) sieve and

Revised 4/14/15