

TRAFFIC CONTROL DETOUR GENERAL NOTES

- CLOSURE OF 175TH STREET WILL NOT BE PERMITTED UNTIL 171ST STREET IS REOPENED TO TRAFFIC AND VICE VERSA.
- ALL SIGNING SHALL BE IN ACCORDANCE WITH APPLICABLE PROVISIONS OF THE STATE OF ILLINOIS "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION" ADOPTED JANUARY 1, 2007, THE DETAILS IN THESE PLANS, AND THE LATEST EDITION OF THE STATE OF ILLINOIS "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES".
- THE CONTRACTOR SHALL PROCEED WITH THE WORK IN AN EXPEDIENT MANNER TO REDUCE THE LENGTH OF DURATION OF THE 175TH STREET DETOUR; THE DETOUR SHALL NOT EXCEED 21 CALENDAR DAYS.
- THE ENGINEER SHALL BE NOTIFIED IN WRITING AT LEAST THREE WEEKS PRIOR TO THE DAY THE DETOUR IS TO BE IN EFFECT. THE ENGINEER WILL CONTACT THE APPROPRIATE LOCAL OFFICIALS AND INTERESTED PARTIES.
- THE ROAD SHALL NOT BE CLOSED UNTIL ALL SIGNING IS ERECTED IN ACCORDANCE WITH THE DETOUR PLAN AND APPROVED BY THE ENGINEER.
- THE CONTRACTOR SHALL MAKE ALL CHANGES IN THE SIGNING THAT ARE DEEMED NECESSARY BY THE ENGINEER.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTENANCE OF ALL BARRICADES, SIGNS, LIGHTS, AND OTHER TRAFFIC CONTROL DEVICES, INSTALLED BY HIM, THAT ARE IN PLACE AND OPERATING 24 HOURS A DAY, 7 DAYS A WEEK, FOR THE DURATION OF THIS DETOUR.
- ALL EXISTING SIGNING THAT DOES NOT APPLY AND/OR CONFLICTS WITH THE DETOUR ROUTE WHILE THE DETOUR IS IN EFFECT SHALL BE COMPLETELY COVERED BY THE CONTRACTOR.
- ALL DETOUR SIGNING SHALL BE POST MOUNTED PER ARTICLE 701.14 AND STANDARDS 701901.
- ALL DETOUR SIGNING DESIGNATED WITH "(O)" IN THE SIGN CODE SHALL HAVE BLACK LEGENDS ON ORANGE HIGH INTENSITY BACKGROUNDS AND STANDARD BLACK BORDERS. ALL DETOUR SIGNING SHALL BE NEW OR LIKE NEW CONDITION.
- THE SIZES OF ALL SIGNS NOT SPECIFIED IN THESE PLANS SHALL BE IN ACCORDANCE WITH THE ILLINOIS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.
- TYPE III BARRICADES, AND THEIR APPLICATION, SHALL CONFORM TO HIGHWAY STANDARD 701901.
- THE "ROAD CLOSED" SIGN ON A TYPE III BARRICADE SHALL BE MOUNTED ABOVE THE TOP OF THE BARRICADE AS SHOWN IN THE SIGN LEGEND. ALL TYPE III BARRICADES SHALL HAVE TWO AMBER TYPE 'A' LOW INTENSITY FLASHING LIGHTS SPACED NEAR THE CENTERLINE OF THE SUPPORTS.
- CONSTRUCTION EQUIPMENT SHALL NOT BE PARKED IMMEDIATELY BEHIND THE TYPE III BARRICADES AT ANY TIME. ARTICLE 701.11 OF THE STANDARD SPECIFICATIONS SHALL APPLY.
- THE ENGINEER SHALL BE NOTIFIED AT LEAST THREE (3) DAYS PRIOR TO THE REMOVAL OF THE DETOUR. THE ENGINEER WILL CONTACT THE APPROPRIATE LOCAL OFFICIALS AND INTERESTED PARTIES.
- PORTABLE CHANGEABLE MESSAGE SIGNS SHALL FLASH THE MESSAGE SHOWN IN THE SIGN LEGEND. TWO PHASES SHALL BE USED. EACH PHASE SHALL BE DISPLAYED FOR 3 SECONDS WITH A MAXIMUM CYCLE OF 6 SECONDS. LETTERS SHALL BE 18 INCHES HIGH AND ALL UPPER-CASE. CHANGEABLE MESSAGE SIGNS SHALL COMPLY WITH THE REQUIREMENTS IN SECTION 6F.60 OF THE 2009 MUTCD.

SIGN LEGEND

1A		W20-3(0)-48	5		M4-8A(0)-2412	11		M3-2-2412	15		M3-4-2412
1		W20-3(0)-48	6		R3-1-36	12		SPECIAL(O)-171st St 24"x18" (6" SERIES B) BLACK ON ORANGE	16		SPECIAL(O)-171st St 24"x18" (6" SERIES B) BLACK ON ORANGE
2		W20-2(0)-48	7		R3-2-36	13		M4-8(0)-2412	17		SPECIAL(O)-171st St 24"x18" (6" SERIES B) BLACK ON ORANGE
3		R11-2-4830 ON TYPE III BARRICADE	8		M3-2-2412	14		M4-8(0)-2412	18		M3-4-2412
4		R11-4-6030 & M4-10L(0)-4818 ON TYPE III BARRICADE	9		SPECIAL(O)-171st St 24"x18" (6" SERIES B) BLACK ON ORANGE			M4-8(0)-2412			SPECIAL(O)-171st St 24"x18" (6" SERIES B) BLACK ON ORANGE
			10		M4-9R(0)-3024			M5-1R(0)-2115			M4-9R(0)-3024
					M3-2-2412			M5-1L(0)-2115			
					SPECIAL(O)-171st St 24"x18" (6" SERIES B) BLACK ON ORANGE			M4-8(0)-2412			
					M4-9R(0)-3024			M5-1L(0)-2115			
					M3-2-2412			M4-8(0)-2412			
					SPECIAL(O)-171st St 24"x18" (6" SERIES B) BLACK ON ORANGE			M4-8(0)-2412			
					M4-9L(0)-3024			M5-1L(0)-2115			

