## INDEX OF SHEETS

## LIST OF STATE STANDARDS

SHEET	NO.	DESCRIPTION	STANDARD NO.	DESCRIPTION
	1	COVER SHEET	000001-06	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
	2	INDEX OF SHEETS, STANDARDS, AND GENERAL NOTES	442201-03	CLASS C AND D PATCHES
·	3-3A	SUMMARY OF QUANTITIES	604001-03	FRAME AND LIDS. TYPE 1
	4	EXISTING & PROPOSED TYPICAL SECTIONS	606001 <i>-04</i>	COMBINATION CONCRETE CURB AND GUTTER
	,5-10 11-21	ROADWAY & PAVEMENT MARKINGS PLANS	701427-01	LANE CLOSURE, MULTILANE, INTERMITTENT OR MOVING OPERATIONS, FOR SPEEDS <= 40 MPH
	22	DETECTOR LOOP REPLACEMENT PLANS  DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING (BD-8)	701601- <i>08</i>	URBAN LANE CLOSURE, MULTILANE, IW OR 2W WITH NONTRAVERSABLE MEDIAN
	23	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT (BD-22)	701602 <b>-06</b>	URBAN LANE CLOSURE, MULTILANE, 2W WITH BIDIRECTIONAL LEFT TURN LANE
	24	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT (BD-24)	701606- <i>08</i>	LANE CLOSURE, MULTILANE, 2-W, WITH MOUNTABLE MEDIAN
	25	BUTT JOINT AND HMA TAPER DETAILS (BD-32)	701701- <i>08</i>	URBAN LANE CLOSURE, MULTILANE INTERSECTION
·	26	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS (TC-1)	701901- <i>02</i>	TRAFFIC CONTROL DEVICES
٠.	27	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT) (TO	886001-04	DETECTOR LOOP INSTALLATION
	28	DISTRICT ONE TYPICAL PAVEMENT MARKINGS (TC-13)	886006-0/	TYPICAL LAYOUT FOR DETECTOR LOOPS
	29	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC) (TC-14)		
	30	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING (TC-16)		
	31	ARTERIAL ROAD INFORMATION SIGN (TC-22)		
	32	DISTRICT ONE DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFACING (TS-07)	-	

## GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES.

(48 HOUR NOTIFICATION IS REQUIRED).

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE CITY OF CALUMET AND THE VILLAGE OF LANSING.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2 INCHES (40 MM) WHERE THE SPEED LIMIT IS 45 MPH (45 KM/H) OR LESS AND 1 INCH WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (45 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HOT-MIX ASPHALT TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MS. PATRICE HARRIS AREA TRAFFIC FIELD ENGINEER AT (708) 597-9800 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKING.

THE RESIDENT ENGINEER SHALL VERIFY ALL EXISTING PAVEMENT MARKINGS BEFORE MILLING.

DO NOT SCALE PLANS FOR CONSTRUCTION DIMENSIONS

DOUBLE LANE MARKERS ARE TO BE USED AS SHOWN ON THE DISTRICT ONE DETAIL "TYPICAL APPLICATIONS - RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)" SHOWN IN THE PLANS.

ALL PAVEMENT PATCHING LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS.

THE CONTRACTOR SHALL CONTACT THE DISTRICT ONE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS IN ADVANCE OF BEGINNING WORK.

THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE ACCESS TO ABUTTING PROPERTY AT ALL TIMES DURING THE CONSTRUCTION OF THIS PROJECT.

BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES (AND RAISED REFLECTIVE MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING, EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

	FILE HAVE 1	USER HAME + our ashiya	DESIGNED	-	REVISED	~	T			
- 1	ci/p=,=ork/p=idot/qure=hige/d0246279/BII	1311-sht-plandgn	DRAWN	*	REVISEO	-	1			
		PLOT SCALE + 160,6000 1/ in.	CHECKED	*	REVISED	*	1			
1		PLOT DATE + 12/28/2012	DATE	-	REVISEO	-	1			

STATE OF ILLINOIS					
DEPARTMENT OF	TRANSPORTATION	L			

IDEX	OF	SHEETS,	LIS	r of	STATE	STAN	VDARDS	&	GENER	AL	NOTES	ľ
			ILI	. 83	(TORRE	NCE /	AVENUE)					ŀ
. 1":5/	3/	CHEEL	NO.	20	1 CUCE	75	CTI		70		**************	ţ.