INDEX OF SHEETS

<u>S</u>	HEET NO.	DESCRIPTION
	ł	COVER SHEET
	2	INDEX OF SHEETS, STATE STANDARDS, AND GENERAL NOTES
	3~4	SUMMARY OF QUANTITIES
	5-6	EXISTING AND PROPOSED TYPICAL SECTIONS
	7-12	ROADWAY AND PAVEMENT MARKING PLANS
	13	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING
	14	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT
	15	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT
	16	BUTT JOINT AND HMA TAPER DETAILS
	17	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS
	18	TYPICAL APPLICATIONS FOR RAISED REFLECTIVE PAVEMENT MARKERS (SNOW PLOW RESISTANT)
	19	DISTRICT ONE TYPICAL PAVEMENT MARKINGS
	20	ARTERIAL ROAD INFORMATION SIGNING

STATE STANDARDS

000001-06STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
442201-03CLASS C AND D PATCHES
482011-03HMA SHOULDER STRIPS/ SHOULDERS WITH RESURFACING OR
WIDENING AND RESURFACING PROJECTS
604011-04FRAME AND LIDS, TYPE 1
606001-04 CONCRETE CURB AND COMBINATION CONCRETE CURB AND GUTTER
701011-03OFF-RD MOVING OPERATIONS, 2L. 2W. DAY ONLY
701301-04LANE CLOSURE, 2L. 2W. SHORT TERM OPERATIONS
701311-03LANE CLOSURE, 2L. 2W. MOVING OPERATIONS-DAY ONLY
701336-06LANE CLOSURE, 2L. 2W. WORK AREAS IN SERIES FOR SPEEDS > 45 MPH
701901-02TRAFFIC CONTROL DEVICES
780001-03TYPICAL APPLICATION RAISED REFLECTIVE PAVEMENT MARKERS

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 OR "CUAN" (CHICAGO UTILITY ALERT NETWORK) AT 312-744-7000 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES, (48 HOURS NOTIFICATION IS REQUIRED).

IO FEET (3 METERS) TRANSITIONS SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER AND MEDIAN ITEMS OF WORK TO EXISTING CURBS AND GUTTERS AND MEDIANS IN THE FIELD, UNLESS OTHERWISE SHOWN, THE TRANSITION SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH THE UTILITY COMPANIES AND THE VILLAGE OF FRANKFORT.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

THE CONTRACTOR SHALL CONTRACT THE DISTRICT ONE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO START OF WORK.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED I 1/2 INCHES (40MM) WHERE THE SPEED LIMIT IS 45 MPH (80 KM/H). WITH WRITEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES (75MM) MAY BE ALLOWED IFTHE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V;H) BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

PERMANENT PAVEMENT MARKINGS SHALL BE THERMOPLASTIC (OF THE EXTRUDED TYPE) AND SHOULD BE PLACED IN ACCORDANCE WITH THE "DISTRICT ONE TYPICAL PAVEMENT MARKINGS" DETAIL. (TC-13)

RAISED REFLECTIVE PAVEMENT MARKERS SHALL BE IN ACCORDANCE WITH THE DISTRICT ONE "TYPICAL APPLICATION RAISED REFLECTIVE PAVEMENT MARKERS" DETAIL.

THE RESIDENT ENGINEER SHALL CONTACT MR. LAWRENCE HILL, AREA TRAFFIC ENGINEER, AT (815) 485-6475 PRIOR TO PLACING ANY PAVEMENT MARKINGS.

1								
		USER HAME I stordpo	DESIGNED -	REVISEO -				
	QI\GHUHYK\phidkit\stadpa\dRZ49543\QI3Q	ll-sht-plar.dgn	DRAWN -	REVISED .				
-		PLOT SCALE - 168,0200 1/ in.	CHECKED -	REVISEO .				
		PEOT DATE > 1/28/2813	DATE .	REVISEO				

STATE	0F	ILLINOIS
DEPARTMENT ()F 1	TRANSPORTATION

SCALE

 					
INDEX OF	SHEETS, 5	TATE STANDARDS.	AND GENERAL NOTES		F.A.P RTE.
F.A.P. 330/ U	S 45 (LA (GRANGE RD.)SAGE	ER RO. TO STUENKAL	RO.	330
C. Cu	FET NA	05 6			L