



LEGEND

- WORK AREA
- TYPE II BARRICADES OR DRUMS WITH STEADY BURN MONODIRECTIONAL LIGHT (AT SPECIFIED SPACING)
- DIRECTION OF TRAFFIC FLOW
- SIGN
- ARROW BOARD
- TYPE III BARRICADE

NOTES:

1. SIGN PLACEMENT AND SPACING SHALL BE IN ACCORDANCE WITH STD. 701400 AND STD. 701401/701446 FOR LANE CLOSURES.
2. DIRECTIONAL INDICATOR BARRICADES AT 50' C-C SPACING SHALL BE USED IN LANE CLOSURE TAPERS. TYPE II BARRICADES AT 100' SPACING SHALL BE USED ELSEWHERE, UNLESS OTHERWISE INDICATED.
3. SIGN PLACEMENT AND SPACING SHALL BE IN ACCORDANCE WITH STD. 701411 AT AFFECTED ENTRANCE/EXIT RAMP.

COLLINS ENGINEERS
 123 N. Rock Dr.
 Suite 900
 Chicago, IL 60606
 Tel: (312) 704-9300
 Fax: (312) 704-9300
 www.collinseng.com
 ILLINOIS PROFESSIONAL DESIGN FIRM LICENSE NO. 104-080993

USER NAME =	DESIGNED - RG	REVISED -
	DRAWN - RG	REVISED -
PLOT SCALE =	CHECKED - MR	REVISED -
PLOT DATE =	DATE - DECEMBER 2012	REVISED -

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

**STAGING AND TRAFFIC CONTROL
 SB EDENS /KENNEDY JUNCTION
 STAGE V**

SCALE: SHEET OF SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94	2012-055BR	COOK	107	10C
ILLINOIS FED. AID PROJECT			CONTRACT NO. 60V58	