



(STA. EQN. #1)
 STA. 298+01.63 (BK) =
 STA. 298+20.65 (AH)

LEGEND	
① EXIST. 4" SUB-BASE GRANULAR MATERIAL	⑮ PROP. STRIP REFLECTIVE CRACK CONTROL TREATMENT
② EXIST. 8" P.C.C. PAVEMENT	⑯ PROP. HOT-MIX ASPHALT SHOULDERS 6 1/2"
③ EXIST. 8" H.M.A. SHOULDER	⑰ PROP. LEVELING BINDER (MACHINE METHOD), N70 1"
④ EXIST. 4" OVERLAY	⑱ PROP. HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70 1 1/2"
⑤ EXIST. COMBINATION CURB AND GUTTER, TYPE B-6.06	⑳ PROP. COMBINATION CONCRETE CURB AND GUTTER, TYPE M-4.24
⑥ PROP. PAVEMENT REMOVAL	㉑ PROP. CONCRETE MEDIAN SURFACE, 4"
⑦ PROP. PAVED SHOULDER REMOVAL	㉒ PROP. CONCRETE MEDIAN, TYPE SM-4.24
⑧ PROP. HOT-MIX ASPHALT SURFACE REMOVAL (VARIABLE DEPTH) *	㉓ PROP. AGGREGATE WEDGE SHOULDER, TYPE B
⑨ PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"	㉔ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 5"
⑩ PROP. COMBINATION CURB AND GUTTER REMOVAL	㉕ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 8"
⑪ PROP. CONCRETE MEDIAN SURFACE REMOVAL	㉖ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B TYPE B - LINE 5"
⑫ PROP. SUBBASE GRANULAR MATERIAL, TYPE B 4"	㉗ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B TYPE B - LINE 6"
⑬ PROP. SUBBASE GRANULAR MATERIAL, TYPE A 8"	
⑭ PROP. HMA BASE COURSE 11" ***	
⑮ PROP. PCC BASE COURSE WIDENING 9"	

- *** NOTES:
- (A) LT TURN LANE TAPER VAR. FR. 4'-7" TO 13'-0" FR. STA. 297+11.63 TO 298+68.46 RT AND IS 13'-0" TO 5'-0" FR. STA. 300+14.88 TO 301+65.14 RT (EB PAVT).
 - (B) LT TURN LANE WIDTH VAR. FR. 0' TO 8'-0" FR. STA. 300+14.88 TO 301+65.14 LT (EB PAVT).
 - (C) PAINTED MEDIAN WIDTH VAR. FR. 0' TO 16'-0" FR. STA. 298+68.46 TO 301+65.14 RT (EB PAVT).
 - (D) PAVEMENT STRIPING 6" WHITE (2'DASH/6'SKIP) FR. STA 296+23.02 TO 298+68.46 RT AND MODIFIED URETHANE PAVEMENT MARKING, TYPE B - LINE 8" FR. STA. 298+68.46 TO 301+65.14 RT (EB PAVT).

* NOMINAL MILLING DEPTH 1/2" @ Q OR pgl
 *** WHERE WIDENING IS GREATER THAN 6' OR UNDER NEW TURN LANE