F. A. U. RTE.	SECTION	COUNTY	SHEETS	SHEET
100	104 RS-8	MCHENR	Y 22	2.
STA.		TO STA.		A

## INDEX OF SHEET

SHEET NO.	
2	INDEX OF SHEETS, STATE STANDARDS AND GENERAL NOTES
3	SUMMARY OF QUANTITIES
4-8	TYPICAL SECTIONS AND MIXTURE REQUIREMENT TABLE
9-12	ROADWAY AND PAVEMENT MARKING PLANS
13	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING
14	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT
15	CURB OR CURB AND GUTTER REMOVAL AND REPLACMENT
16	BUTT JOINT AND HMA TAPER DETAILS
17	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS
18	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)
19	DISTRICT ONE TYPICAL PAVEMENT MARKINGS
20	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC)
21	PAVEMENT MARKINGS LETTERS AND SYMBOLS FOR TRAFFIC STAGING
22	TEMPORARY INFORMATION SIGNING

## LIST OF STANDARDS

000001-04 STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS

442201-02 CLASS C AND D PATCHES

482011-02 BIT. SHOULDER STRIPS/ SHLDS. WITH RESURFACING OR WIDENING AND RESURFACING PROJECTS

701201-02 LANE CLOSURE, 2-L,2-W, DAY ONLY FOR SPEEDS > 45MPH

701301-02 LANE CLOSURE, 2-L,2-W, SHORT TIME OPERATIONS

701306-01 LANE CLOSURE, 2-L,2-W SLOW MOVING OPERATIONS-DAY ONLY FOR SPEEDS > 45

701311-02 LANE CLOSURE, 2-L,2W MOVING OPERATIONS-DAY ONLY

.701421-01 LANE CLOSURE, MULTILANE, DAY OPERATIONS ONLY, FOR SPEEDS 2 45 MPH TO 55 MPH

## GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED)

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES IN THE VILLAGE OF HEBRON.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 40 MM (11/2 INCHES) WHERE THE SPEED LIMIT IS 80 KM/H (45 MPH) OR LESS AND 25 MM (1 INCH) WHERE THE SPEED LIMIT IS GREATER THAN 80 KM/H (45 MPH). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 75 MM (3 INCHES) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HOT-MIX ASPHALT TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MS. DEBBIE HANLON AREA TRAFFIC FIELD TECHNICIAN AT (847) 438-2300 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKIMG.

ILLINOIS DEPARTMENT OF TRANSPORTATION

IL 47

INDEX OF SHEEETS, STATE STANDARDS & GENERAL NOTES

SCALE: VERT. 1"=50" DATE 2/6/2007

DRAWN BY CHECKED BY