GENERAL NOTES

- 1. ANY REFERENCE TO A STANDARD IN THESE PLANS SHALL BE INTERPRETED TO MEAN THE EDITION AS INDICATED BY THE SUB NUMBER LISTED IN THE INDEX OF SHEETS OR THE COPY OF THE STANDARD INCLUDED IN THESE PLANS.
- 2. IN ADDITION TO FIELD SURVEYS, PLAN DIMENSIONS AND DETAILS RELATIVE TO THE EXISTING FACILITIES HAVE BEEN TAKEN FROM EXISTING PLANS AND ARE SUBJECT TO CONSTRUCTION VARIATIONS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY SUCH DIMENSIONS AND DETAILS IN THE FIELD. SUCH VARIATIONS SHALL NOT BE A CAUSE FOR ADDITIONAL COMPENSATION DUE TO A CHANGE IN THE SCOPE OF WORK; HOWEVER, THE CONTRACTOR WILL BE PAID FOR THE QUANTITY ACTUALLY FURNISHED AT THE UNIT PRICE BID FOR THE WORK.
- 3. ACCESS TO ALL ENTRANCES AND SIDE ROADS SHALL BE MAINTAINED AT ALL TIMES.
- 4. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING UTILITY PROPERTY FROM CONSTRUCTION OPERATIONS, AS OUTLINED IN ARTICLE 107.31 OF THE STANDARD SPECIFICATIONS. THE J.U.L.I.E. NUMBER IS 1-800-892-0123. A MINIMUM OF 48 HOURS ADVANCE NOTICE IS REQUIRED.
- 5. THE THICKNESS OF BITUMINOUS MIXTURES SHOWN ON THE PLANS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE BITUMINOUS MIXTURE IS PLACED.
- 6. UNLESS DIRECTED BY THE ENGINEER, PAVEMENT MARKING LINES SHALL NOT BE LAID DIRECTLY OVER A LONGITUDINAL CRACK OR JOINT NOR OVER A TAR OR ASPHALT PAINTED LINE. THE EDGE OF A CENTERLINE OR LANE LINE SHALL BE OFFSET A MINIMUM DISTANCE OF 2" FROM A LONGITUDINAL CRACK OR JOINT. EDGE LINES SHALL BE APPROXIMATELY 2" FROM THE EDGE LINE OF PAVEMENT. SEE SECTION 780 OF THE STANDARD SPECIFICATIONS FOR TRAFFIC CONTROL ITEMS.
- 7. THE FOLLOWING RATES OF APPLICATION HAVE BEEN USED TO CALCULATE THE PLAN QUANTITIES:
 BITUMINOUS MATERIALS (PRIME COAT)
 BITUMINOUS MATERIALS (PRIME COAT)
 AGGREGATE PRIME COAT
 BITUMINOUS CONCRETE SURFACE / BINDER
 AGGREGATE MATERIAL
 O.00038 TON/SQ. YD. (ON AGG.)
 O.001425 TON/SQ. YD. (ON AGG.)
 O.002 TON/SQ. YD. PER 1"
 2.05 TON/CU. YD.
- 8. THE EXISTING ROAD SIGNS THAT INTERFERE WITH CONSTRUCTION WILL BE REMOVED OR RELOCATED AS DIRECTED BY THE ENGINEER. AFTER THE CONSTRUCTION IS COMPLETED, THE CONTRACTOR WILL REPLACE THE SIGNS AS DIRECTED BY THE ENGINEER. THIS WORK WILL NOT BE PAID SEPARATELY BUT SHALL BE CONSIDERED INCLUDED IN THE CONTRACT, AND NO COMPENSATION WILL BE ALLOWED.
- 9. NO COMMITMENTS MADE.

COMMITMENTS

THE FIELD/RESIDENT ENGINEER SHALL CONTACT STUDIES & PLANS CONCERNING ANY MAJOR PLAN CHANGES TO MAKE SURE NO PREVIOUS COMMITMENTS (NOT LISTED) WERE MADE AFFECTING THE DESIGN AND ALLOW AN IMPROVED DESIGN FOR FUTURE PROJECTS.

STANDARDS

601001-04 701201-04 701306-03 701901-02

THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT:

THE TOLLOWING WITHOUT	REGULACIONENTS ARE ALTEROR	L TON THIS INCOLOR	
MIXTURE USE(S):	LEVEL BINDER (MACH METHOD)	HMA SURFACE COURSE	
PG:	PG 64-22	PG 64-22	
DESIGN AIR VOIDS:	4.0% @ N 50	4.0% @ N 50	
MIXTURE COMPOSITION: (GRADATION MIXTURE)	IL 9.5	IL 9.5 OR IL 12.5	
FRICTION AGGREGATE:	N/A	MIX "C"	
20 YEAR ESAL	N/A	N/A	

DISTRICT SIX	
EXAMINED 1/23	20 /2
OPERATIONS ENGINEER	

EXAMINED JAN 19	20	12_
PROJECT IMPLEMENTATION ENGINE	ER	
EXAMINED ANNY 17	_ 20	12
PROGRAM DEVELOPMENT ENGINEE	R	

ILE NAME = DESIGNED REVISED TOTAL SHEE' SHEETS NO. USER NAME = pererava SECTION COUNTY **GENERAL NOTES** STATE OF ILLINOIS DRAWN REVISED rava\d0290642\D672F20-sht-gennote.don SCOTT 9 2 566 (1-NRHM)I PLOT SCALE = 100.0000 '/ in. CHECKED -REVISED -**DEPARTMENT OF TRANSPORTATION** CONTRACT NO. 72F20 PLOT DATE = Jan-31-2012 10:44:24AM DATE REVISED -SCALE: SHEET OF SHEETS STA. TO STA.