



TABLE

D	T	D _o (min.)	t	Reinforcement "As" W.W.F. each direction	OR Bar size	No. 15 (No. 4) Bar C Length	Radius
900 (36)	See applicable Standards	D + 2T	150 (6)	425 mm ² /m (.20 sq. inch/ft.)	No. 15 (No. 4)	1.2 m (4'-0")	480 (19)
1.2 m (4'-0")			150 (6)	740 mm ² /m (.35 sq. inch/ft.)	No. 15 (No. 5)	1.35 m (4'-6")	660 (26)
1.5 m (5'-0")			200 (8)	740 mm ² /m (.35 sq. inch/ft.)	No. 15 (No. 5)	1.5 m (5'-0")	810 (32)

GENERAL NOTES

The flat slab top may be used in lieu of the tapered tops shown on Standards 602001, 602011, 602306, 602401, or 602501 at the option of the Contractor or when field conditions prohibit the use of tapered tops.

All dimensions are in millimeters (inches) unless otherwise shown.

DATE	DESCRIPTION OF THE REVISIONS	BY

**PRECAST REINFORCED CONCRETE
FLAT SLAB TOP**

STANDARD 602601

IL PROJ. NO.	GRE-3215
A.I.P. PROJ. NO.	3-17-0049-B4
FILE NAME	IDOT-602601
DATE	03-24-2006