
STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

Various Routes OVD SIN STR REP & REPL 2005-12 Various Counties Sheet 47 of 82 Contract Number 44872

* Anchor rod shall be ground or filed to bright metal at clamp and cable connection location.



Bar Number Size Length Shape #9 F less 5" 16 #4 bar spiral (E) - see Side Elevation

BAR LIST - EACH FOUNDATION

The foundation dimensions shown are based on the presence of mostly cohesive soils with an average Unconfined Compressive Strength (Qu) of at least 1.25 tsf, which must be determined by previous soil investigations at the jobsite. When other conditions are indicated. the boring data will be included in the plans and the foundation dimensions shown will be the result of site specific designs.


If the conditions encountered are different than those indicated, the Contractor shall notify the Engineer to determine if the foundation dimensions need to be modified. If dimensions "B" or "F" are revised by more than 12" by the Contractor, "as-built" plans shall be prepared and submitted to the District Bureau of Operations for future reference.

No sonotubes or decomposable forms shall be used below the lower conduit entrance. Permanent metal forms or other shielding may not be left in place below that elevation without the Engineer's written permission.

Concrete shall be placed monolithically, without construction joints.

Backfill shall be placed per Article 502 of Standard Specification and prior to erection of support column. A normal surface finish followed by a Bridge Seat Sealer application will be required

on concrete surfaces above the lowest elevation 6" below finished ground line. Cost included in Drilled Shaft Concrete Foundation.



SIDE ELEVATION

7'-6" & to &

Structure Number	Station	Elevation Top	Left Foundation				Right Foundation					Class SI
			Elevation Bottom	А	В	F	Elevation Top	Elevation Bottom	А	В	_ Co	Concrete (Cu. Yds.)
3S057I074L134.8	683 + 00 WB	N/A		3' - 0"	13' - 6"	16' - 6"	N/A		3' - 0"	13' - 6"	16' - 6"	12.00
					ļ							

***************************************		***************************************	1					 	 			

SECTION A-A

PLAN

OVERHEAD SIGN STRUCTURES DRILLED SHAFT DETAILS

DESIGNED -EXAMINED CHECKED -ENGINEER OF BRIDGE DESIGN PASSED DRAWN MINERS OF REIDGES AND STREETINES CHECKED -0S4-F2 1-7-05

NUMBER	REVISION	DATE

2'-6" ø

DETAILS FOR 8" \$ SUPPORT FRAME TYPE I-A TRUSS

END VIEW

District 3 Truss Repair & Replacement