



THERMOPLASTIC PAVEMENT MARKING LEGEND

- (A) 4" DOUBLE SOLID YELLOW, CENTERLINE (TYPICAL)
- (B) 4" WHITE SKIP-DASH, LANELINE (10' DASH, 30' SKIP) (TYPICAL)
- (C) 4" SOLID WHITE, EDGE LINES (TYPICAL)
- (D) 6" SOLID/DOTTED WHITE, TURN LANE LINE (TYPICAL)
- (E) 8" SOLID WHITE, ISLAND OUTLINE (TYPICAL)
- (F) 12" SOLID YELLOW DIAGONAL @ 45° (20-75' C-C MINIMUM OF 5) (TYPICAL)
- (G) 12" SOLID WHITE DIAGONAL @ 45° (75' SPACING) (TYPICAL)
- (H) 24" SOLID WHITE, STOP BAR (TYPICAL)
- (I) LETTERS & SYMBOLS, WHITE (TYPICAL)

FILE NAME =	USER NAME = mcsse	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	SCALE:	SHEET NO. OF SHEETS STA. TO STA.	F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
c:\pwork\pwidot\mcsse\d0177698\01316	@-sht-plan.dgn	DRAWN -	REVISED -				866	3 RS-3	LAKE	35	11
	PLOT SCALE = 50.0000' / IN.	CHECKED -	REVISED -				CONTRACT NO. 60J94				
	PLOT DATE = 2/3/2010	DATE -	REVISED -				ILLINOIS FED. AID PROJECT				