


PAVEMENT MARKIN LEGEND

- ① PR PREFORMED PLASTIC PAVEMENT MARKING, TYPE B (INLAID), LINE 5" (30' SKIP, 10' DASH WHITE)
- ② PR URETHANE PAVEMENT MARKING, LINE 5" (SOLID YELLOW)
- ③ PR URETHANE PAVEMENT MARKING, LINE 5" (SOLID WHITE)
- ④ PR URETHANE PAVEMENT MARKING, LINE 6" (SOLID WHITE)
- ⑤ PR PREFORMED PLASTIC PAVEMENT MARKING, TYPE B (INLAID), LINE 6" (6' SKIP, 2' DASH WHITE)
- ⑥ PR PREFORMED PLASTIC PAVEMENT MARKING, TYPE B (INLAID), LINE 8" (SOLID WHITE)
- ⑦ PR PREFORMED PLASTIC PAVEMENT MARKING, TYPE B (INLAID), LINE 12" (SOLID WHITE)
- ⑧ PR PREFORMED PLASTIC PAVEMENT MARKING, TYPE B (INLAID), LINE 12" (SOLID YELLOW)
- ⑨ PR PREFORMED PLASTIC PAVEMENT MARKING, TYPE B (INLAID), LINE 24" (SOLID WHITE)
- ⑩ PR PREFORMED PLASTIC PAVEMENT MARKING, TYPE B (INLAID), LETTERS AND SYMBOLS (SOLID WHITE)
- ▷ PR RAISED REFLECTIVE PAVEMENT MARKERS, ONE-WAY CRYSTAL
- ▶ PR RAISED REFLECTIVE PAVEMENT MARKERS, ONE-WAY AMBER
- ◆ PR RAISED REFLECTIVE PAVEMENT MARKERS, TWO-WAY AMBER

EXIST. CURVE IL961
 PI STA. = 37+73.16
 Δ = 19° 57' 30" (LT)
 D = 2° 59' 04"
 R = 1,919.81'
 T = 337.79'
 L = 668.74'
 E = 29.49'
 EX & PR S.E. = 5.3% (55 MPH DESIGN)
 T.R. = 44.73' (HIGH SIDE ONLY)
 S.E. RUN = 158.05' (HIGH SIDE ONLY)
 P.C. STA. = 34+35.37
 P.T. STA. = 41+04.11
 S.E. ATTAINED (MATCH EXIST - LOW SIDE ONLY):
 STA 33+35.36 TO STA 34+85.36
 STA 40+54.11 TO STA 42+04.11
 S.E. ATTAINED (HIGH SIDE ONLY):
 STA 32+82.58 TO STA 34+85.36
 STA 40+54.11 TO STA 42+56.89



FILE NAME =	USER NAME = laughlinr1	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	IL RTE 96 PLAN			F.A.I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
es:\pwork\PWIDOT\LAUGHLINRL\0182983\086_Plan_IL 96.dgn		DRAWN -	REVISED -		SCALE: 1"=20'	SHEET NO. 48 OF 52 SHEETS	STA. 30+00	TO STA. 36+00	172	1-(1,2,3,4,5)RS	ADAMS	165	86
		CHECKED -	REVISED -		CONTRACT NO. 72A09								
		DATE -	REVISED -		FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT								