## INDEX OF SHEETS

## STATE STANDARDS

SHEET NO.	DESCRIPTION	STANDARD NO.	DESCRIPTION	
1	TITLE SHEET	442201 <b>-03</b>	CLASS C AND D PATCHES	
2	INDEX OF SHEETS, STATE STANDARDS & GENERAL NOTES.	701301- <i>0</i> 3	LANE CLOSURE, 2L, 2W, SHORT TIM	E OPERATIONS
3	SUMMARY OF QUANTITIES	701606 <b>-06</b>	URBAN LANE CLOSURE, MULTILANE,	2W WITH MOUNTABLE MEDIAN
4-5	EXISTING AND PROPOSED TYPICAL SECTIONS	701701-06	URBAN LANE CLOSURE, MULTILANE 1	NTERSECTION
6-7	ROADWAY AND PAVEMENT MARKING PLANS	701901-01	TRAFFIC CONTROL DEVICES	
8	DETECTOR LOOP REPLACEMENT			
9	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING (BD-9)			
10	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT (BD-22)			
11	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT (BD-24)			
12	BUTT JOINT AND HMA TAPER DETAILS (BD-32)			
13	HMA TAPER AT EDGE OF PCC PAVEMENT (BD-33)			
14	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, (TC-10) INTERSECTIONS AND DRIVEWAYS			
15	TYPICAL APPLICATIONS: RAISED REFLECTIVE PAVEMENT (TC-11) MARKERS (SNOW-PLOW RESISTANT)			
16	DISTRICT ONE TYPICAL PAVEMENT MARKINGS (TC-13)			
17	TRAFFIC CONTROL AND PROTECTION OF TURN BAYS (TC-14) (TO REMAIN OPEN TO TRAFFIC)			
18	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING (TC-16)			
19	ARTERIAL ROAD INFORMATION SIGN (TC-22)			
19A	TYPICAL SUPPLEMENTAL SIGNING AND PAVEMENT MARKING TREATMENT FOR	RAILROAD CROSSINGS	(TC-23)	All the second s
20	DISTRICT 1 DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFA	CING (TS-07)		

## GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT (800) 892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE, AND GAS FACILITIES, (48 HOUR NOTIFICATION REQUIRED)

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGE OF BLUE ISLAND.

THE CONTRACTOR WILL NOT BE ABLE TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT THE WRITTEN PERMISSION OF THE DEPARTMENT.

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT) IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MS. PATRICE HARRIS. AREA TRAFFIC FIELD ENGINEER, AT (708) 597-9800 A MINIMUM OF TWO WEEKS PRIOR TO PLACEMENT OF FINAL PAVEMENT MARKINGS.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC. THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2 INCHES WHERE THE SPEED LIMIT IS 45 MPH OR LESS, AND 1 INCH WHERE THE SPEED LIMIT IS 45 MPH. WITH WRITTEN APPROVAL FROM THE RESIDENT ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM OF 1:3 (V:H)

THE CONTRACTOR SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS IN ADVANCE OF BEGINNING WORK.

ANY PAVEMENT MARKINGS AND RAISED REFLECTIVE PAVEMENT MARKERS OBLITERATED BY MILLING AND RESURFACING OPERATIONS ON SIDE STREETS AND ENTRANCES SHALL BE REPLACED AND PAID FOR IN KIND

ALL DAMAGE TO EXISTING PAVEMENT MARKINGS OR RAISED REFLECTIVE PAVEMENT MARKERS OUTSIDE THE REMOVAL LINE SHOWN ON THE PLANS SHALL BE REPLACED AT NO ADDITIONAL COST TO THE DEPARTMENT.

BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES (AND RAISED REFLECTIVE PAVEMENT MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING. EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

ALL PAVEMENT PATCHING LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

DRAINAGE ADJUSTMENT OR RECONSTRUCTION LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRÍOR TO CONSTRUCTION AND ORDERING OF MATERIALS.

THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE ACCESS TO ABUTTING PROPERTY AT ALL TIMES DURING THE CONSTRUCTION OF THIS PROJECT.

DOUBLE LANE MARKER'S ARE TO BE USED AS SHOWN ON THE DISTRICT ONE DETAIL "TYPICAL APPLICATIONS - RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)" SHOWN IN THE PLANS.

FILE NAME =	USER NAME = abebawa	DESIGNED -	REVISED -	_
c:\pw_work\pwidot\abebawa\d0128251\D102°	09-sht-planidgn	DRAWN -	REVISED -	
	PLOT SCALE = 50.0000 '/ IN.	CHECKED -	REVISED -	
	PLOT DATE = 3/20/2009	DATE -	REVISED - 1	

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 

					1 To	APLE AVENUE) GENERAL NOTES	;
SCALE	:	SHEET NO.	OF '	SHEETS	STA.	TO STA.	

 F.A.P RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
344	3034-1A-RS	COOK	20	2
		CONTRACT	NO. 6	OF08
FED. F	OAD DIST. NO. 1   ILLINOIS FED. AI	PROJECT		