

RAISED REFLECTIVE PAVEMENT MARKING					
STA.	TO	STA.	LENGTH	RAISED REF PAVEMENT MARKERS	RAISED REF PVT MRKRS REMOVAL
			(FT)	(EACH)	(EACH)
459+87	TO	493+87	3,400	43	43
BRIDGE OMISSION (493+87 TO 497+97)					
497+97	TO	653+86	15,589	195	195
RECONSTRUCTION LIMITS (653+86 TO 664+00)					
664+00	TO	716+90	5,290	66	66
TOTALS				303	303

HOT-MIX ASPHALT SHOULDERS						
STA.	TO	STA.	LENGTH	EXC & GR EX SHLD	HMA SHLD, 8"	SHLD RUMBLE STRIP
			(FT)	(UNIT)	(SQ YD)	(FT)
459+87	TO	493+87	3,400	68	3022	6800
BRIDGE OMISSION (493+87 TO 497+97)						
497+97	TO	508+95	1,098			2196
508+48	TO	653+86	14,538	291	12923	29076
RECONSTRUCTION LIMITS (653+86 TO 664+00)						
664+00	TO	716+90	5,290	106	4702	10580
TOTALS				465	20,648	48,652

MOWING				
STA.	TO	STA.	LENGTH	
			(FT)	(UNIT)
459+87	TO	493+87	3,400	34
BRIDGE OMISSION (493+87 TO 497+97)				
497+97	TO	653+86	15,589	156
RECONSTRUCTION LIMITS (653+86 TO 664+00)				
664+00	TO	716+90	5,290	53
TOTALS				243

CONSTRUCTING TEST STRIP	EACH
TOTAL	1

ENGINEERING FIELD OFFICE TYPE A	CAL MO
TOTAL	6

MOBILIZATION	L SUM
TOTAL	1

TRAF CONT & PROT STD 701306	L SUM
TOTAL	1

TRAF CONT & PROT STD 701326	L SUM
TOTAL	1

TRAF CONT & PROT STD 701336	L SUM
TOTAL	1

SHOULDER RUMBLE STRIP	FT
TOTAL	1

RATES:

FOR ALL HOT MIXES: 112 LBS/SQ.YD.IN.
 FOR AGGREGATE SHOULDERS TYPE B: 2.05 TON/CUYD
 OR 114 LBS/SQ.YD.IN

FOR BIT MATLS (PRIME COAT): 0.004 ton/gal
 -ON GRANULAR BASE: 0.5 GAL/SQ. YD.
 -ON EXIST. PVT.: 0.05 GAL/SQ.YD.
 -ON COLD MILLED AREA: 0.1 GAL/SQ.YD.
 -ON NEW PAV'T: 0.03 GAL/SQ.YD.

FOR AGG (PRIME COAT):
 -ON EXIST PVT: 4 LBS/SQ. YD.
 -ON COLD MILLED SURF: 4 LBS/SQ.YD.
 -ON NEW PVT: 2 LBS/SQ.YD.

* (108x,130,102)RS-3; 129RS-4, 101RS-2