

ROUTE		SECTION	COUNTY	SHEET	
F.A.P.	VAR.	*	PEORIA	TOTAL	NO.
MKD.	IL 90			100	78

* (108X, 130, 102)RS-3; 129RS-4, 101RS-2

STA		STA	LENGTH FT	WIDTH FT	AREA SQ YD	HMA SURFACE REMOVAL BUTT JOINT SQ YD	HMA SURFACE REMOVAL 3/4" SQ YD	HMA SURFACE REMOVAL 1 1/4" SQ YD	HMA SURFACE REMOVAL 1 1/2" SQ YD	HMA SURFACE REMOVAL 2" SQ YD	POLYMERIZED BITUMINOUS MATERIALS (PRIME COAT) TON	AGGREGATE (PRIME COAT) TON	POLYMERIZED LEVELING BINDER, 3/4" TON	HMA SURFACE COURSE, 1 1/2" TON	HMA SHOULDERS 1 1/2" TON	MATERIAL TRANSFER DEVICE TON	TEMPORARY RAMP SQ YD	AGGREGATE SHOULDERS, TYPE B TON
0 + 12	TO	0 + 42	30	VAR.	614.6	817.5					0.340	1.6		68.7		68.7	55.6	12.0
0 + 42	TO	1 + 59.62	117.62	VAR.	627.9				627.9		0.340	1.9	26.4	52.7		52.7		12.0
1 + 59.62	TO	47 + 29	4669.4	26	13489.3				13489.3		7.302	40.5	566.6	1133.1		1133.1		265.9
47 + 29	TO	52 + 53	524	26	1513.8				1513.8		0.819	4.5	63.6	127.2		127.2		29.8
52 + 53	TO	92 + 47	3994	26	11538.2				11538.2		6.246	34.6	484.6	969.2		969.2		227.4
92 + 47	TO	103 + 00	1053	26	3042.0				3042.0		1.647	9.1	127.8	255.5		255.5		60.0
103 + 00	TO	106 + 70	370	26	1068.9				1068.9		0.579	3.2	44.9	89.8		89.8		21.1
106 + 70	TO	108 + 00	130	26	375.6				375.6		0.203	1.1	15.8	31.5		31.5		7.4
108 + 00	TO	109 + 00	100	26	288.9				288.9		0.156	0.9	12.1	24.3		24.3		5.7
109 + 00	TO	109 + 50	50	26	144.4				144.4		0.078	0.4	6.1	12.1		12.1		2.8
109 + 50	TO	113 + 70.60 (BK)	420.6	26	1215.1		233.7		1215.1		0.784	4.3	51.0	102.1	19.6	121.7		
113 + 69.59 (AH)	TO	116 + 50	280.41	26	810.1		155.8		810.1		0.523	2.9	34.0	68.0	13.1	81.1		
116 + 50	TO	117 + 36	86	26	248.4				248.4		0.134	0.7	10.4	20.9		20.9		4.9
116 + 50	TO	120 + 87	351	26	1014.0				1014.0		0.549	3.0	42.6	85.2		85.2		20.0
120 + 87	TO	122 + 50	163	26	470.9				470.9		0.255	1.4	19.8	39.6		39.6		9.3
122 + 50	TO	127 + 50	500	26	1444.4		277.8		1444.4		0.932	5.2	60.7	121.3	23.3	144.7		
127 + 50	TO	139 + 98	1248	26	3605.3				3605.3		1.952	10.8	151.4	302.8		302.8		71.1
139 + 98	TO	182 + 88	4290	26	12393.3				12393.3		6.709	37.2	520.5	1041.0		1041.0		244.3
182 + 88	TO	187 + 87	499	26	1441.6				1441.6		0.780	4.3	60.5	121.1		121.1		28.4
187 + 87	TO	214 + 00	2613	26	7548.7				7548.7		4.086	22.6	317.0	634.1		634.1		148.8
214 + 00	TO	215 + 00	100	26	288.9				288.9		0.156	0.9	12.1	24.3		24.3		5.7
215 + 00	TO	216 + 20	120	26	346.7				346.7		0.188	1.0	14.6	29.1		29.1		6.8
216 + 20	TO	216 + 60	40	27	120.0		22.2		120.0		0.077	0.4	5.0	10.1	1.9	11.9		2.3
216 + 60	TO	228 + 00	1140	28	3546.7				3546.7		1.920	10.6	149.0	297.9		297.9		64.9
228 + 00	TO	252 + 36	2436	26	7037.3				7037.3		3.809	21.1	295.6	591.1		591.1		138.7
SUB-TOTALS						818	689	0	73620	0	40.6	225	3092	6253	58	6311	56	1389

APPLICATION RATE (POLY PRIME)
 0.1 Gal./Sq. Yd. on Cold Milled Surface
 .05 Gal./Sq. Yd. on Shoulder Overlay
 .03 Gal./Sq. Yd. Fog Coat on New Binder

APPLICATION RATE (AGG PRIME)
 4 Lb/Sq. Yd. on Cold Milled Surface
 2 Lb/Sq. Yd. on Binder

**TABULATION OF
 RESURFACING
 QUANTITIES
 (SHEET 1 OF 6)**