

ROUTE		SECTION	COUNTY	SHEET	
F.A.P.	VAR.	*	PEORIA	TOTAL	NO.
MKD.	IL 90			100	81

\* (108X, 130, 102)RS-3; 129RS-4, 101RS-2

			INCIDENTAL HMA SURFACE COURSE, 1 1/2"				HMA SURFACE REMOVAL BUTT JOINT		POLYMERIZED BITUMINOUS MATERIALS (PRIME COAT)	AGGREGATE SURFACE COURSE, 1 1/2"			
	STATION	TYPE OF ENTRANCE	WIDTH (FT)	LENGTH (FT)	AREA (SQ. YD)	TONS	AREA	(SQ. YD)	TONS	WIDTH (FT)	LENGTH (FT)	AREA (SQ. YD)	TONS
RT	13 + 49	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
LT	20 + 13	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	29 + 67	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
LT	36 + 95	PE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
LT	38 + 95	PE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	39 + 81	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
LT	40 + 25	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	44 + 15	PE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
LT	60 + 58	PE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	62 + 28	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	62 + 32	PE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
LT	63 + 50	PE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	67 + 10	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	80 + 16	PE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
LT	80 + 44	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	91 + 00	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
LT	94 + 16	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	94 + 87	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	115 + 66	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	128 + 21	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
LT	131 + 84	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	137 + 52	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
LT	137 + 73	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	140 + 00	PE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
LT	171 + 91	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	171 + 91	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
LT	178 + 14	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	181 + 17	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
LT	192 + 62	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
RT	194 + 50	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
LT	199 + 23	PE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
LT	202 + 72	FE	20	5	11.1	0.9	11.1		0.005	14	5	7.8	0.7
<b>SUB-TOTALS</b>					<b>356</b>	<b>30</b>	<b>356</b>		<b>0.1</b>				<b>21</b>

**APPLICATION RATE (POLY PRIME)**  
 0.1 Gal./Sq. Yd. on Cold Milled Surface  
 .05 Gal./Sq. Yd. on Shoulder Overlay  
 .03 Gal./Sq. Yd. Fog Coat on New Binder

**TABULATION OF  
 RESURFACING  
 QUANTITIES  
 (SHEET 4 OF 6)**