



Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

May 27, 2016

SUBJECT: FAS 357 (CH 1)
Section 86-00075-06-PV
Woodford County
Contract No. 89685
Item 158
June 10, 2016 Letting
Addendum (A)

NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

1. Revised page 7 of the Special Provisions.

Prime contractors must utilize the enclosed material when preparing their bid and must include any Schedule of Prices changes in their bidding proposal.

Bidders using computer-generated bids are cautioned to reflect any and all Schedule of Prices changes, if involved, into their computer programs.

Very truly yours,

Maureen M. Addis, P.E.
Acting Bureau Chief of Design and Environment

A handwritten signature in black ink, reading "Ted B. Walschleger P.E." with a stylized flourish at the end.

By: Ted B. Walschleger, P.E.
Engineer of Project Management

ADDENDUM #1

The Contractor may, at his/her option, add a drying agent to lower the moisture content as specified. The drying agent must be approved by the Engineer prior to use. Additional compensation will not be allowed for the use of a drying agent, but will be considered as included in the cost of the various earthwork items."

In the first sentence of the third paragraph delete "above steps have" and replace with "work has."

AGGREGATE BASE COURSE, TYPE B 6" AND 12"

Effective: November 5, 2004

Revised: November 18, 2015

This work shall be in accordance with Section 351 of the Standard Specifications and as specified herein.

All Aggregate Base Course material shall be CRUSHED STONE or **CRUSHED GRAVEL** and have a minimum IBR of ~~80~~ **44**. ***IBR tests shall be performed within 12 months of the bid opening and the results submitted to the Engineer for approval prior to material being delivered to the project. (ADDENDUM #1 IN BOLD)***

AGGREGATE SURFACE COURSE, TYPE B

This work shall be in accordance with Section 351 of the Standard Specifications and as specified herein.

All Aggregate Surface Course material shall be CRUSHED STONE or **CRUSHED GRAVEL** and have a minimum IBR of ~~80~~ **44**. ***IBR tests shall be performed within 12 months of the bid opening and the results submitted to the Engineer for approval prior to material being delivered to the project. (ADDENDUM #1 IN BOLD)***

ANTI-STRIP ADDITIVE FOR HOT-MIX ASPHALT

Effective July 30, 2010

If an anti-stripping additive is required for any hot-mix asphalt in accordance with Article 1030.04(c), the cost of the additive will not be paid for separately, but shall be considered as included in the contract unit price bid for the hot-mix asphalt item(s) involved.

HOT-MIX ASPHALT SURFACE COURSE SURFACE TESTS

Effective: November 1, 2003 Revised January 1, 2007

The Contractor shall provide a person to operate the straight edge in accordance with Article 406.11 of the Standard Specifications and communicate with County Personnel to minimize the surface course bumps. If surface course bumps cannot be removed at this time, County personnel will record the locations and provide deductions as stated in Article 406.11.