

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
-	-	KANE	545	289
FED. ROAD DIST. NO. 7		ILLINOIS	FED. AID PROJECT-	

SHEET SA- 2  
OF 14 SHEETS

Contract #63074

INDEX OF DRAWINGS

SA - 1 of 14	General Plan and Elevation
SA - 2 of 14	General Notes, Index of Sheets and Total Bill of Material
SA - 3 of 14	Foundation Plan and Reinforcement
SA - 4 of 14	Top Slab Reinforcement
SA - 5 of 14	Plan and Elevation West Wall
SA - 6 of 14	Plan and Elevation East Wall
SA - 7 of 14	Wall Reinforcement
SA - 8 of 14	Wingwall Details Stage 1
SA - 9 of 14	Wingwall Details Stage 2
SA - 10 of 14	Drainage Details
SA - 11 of 14	Bar Splicer Details
SA - 12 of 14	Rail Details
SA - 13 of 14	Architectural Treatment
SA - 14 of 14	Soil Boring Logs

TOTAL BILL OF MATERIAL

PAY ITEM	UNIT	STAGE 1	STAGE 2	TOTAL
Porous Granular Embankment	Cu. Yd.	546	686	1,232
Structure Excavation	Cu. Yd.	890	991	1,881
Concrete Structures	Cu. Yd.	360.7	453.7	814.4
* Form Liner Textured Surface (Special)	Sq. Ft.	1,489	1,766	3,255
Reinforcement Bars, Epoxy Coated	Pound	64,830	83,470	148,300
Bar Splicers	Each	191		191
Name Plates	Each	1		1
Geocomposite Wall Drain	Sq. Yd.	215	270	485
* Pipe Underdrains for Structures 4"	Foot.	174	196	370
* Graffiti Removal (Special)	Sq. Yd.	162	234	396
* Anti-Graffiti Coating	Sq. Ft.	1,668	1,946	3,614
* Steel Railing (Special)	Foot	89	73	162
* Architectural Lettering	L. Sum	0.25	0.25	0.5

\* See Special Provisions

GENERAL NOTES

- Reinforcement bars shall conform to the requirements of ASTM A706 Gr. 60. See Special Provision.
- Reinforcement bars designated (E) shall be epoxy coated.
- All exposed concrete edges shall have a 3/4" x 45 deg. Chamfer, except where shown otherwise. Chamfer on vertical edges shall be continued a minimum of one foot below finished ground level.
- Reinforcement bending details shall be in accordance with the latest Manual of Standard Practice for Detailing Reinforced Concrete Structures, ACI 315.
- Reinforcement bar bending dimensions are out to out.
- Cover from face of concrete to face of reinforcement bars shall be 3 inches for surfaces cast against earth and 2 inches for all other surfaces unless otherwise shown.
- The cost of Water Seals and PJF is included in the cost of Concrete Structures unless noted otherwise.
- Backfill shall be placed simultaneously against both side walls of the structure. The maximum differential in fill height on either side shall be two feet.
- Reinforcement bar lap splices shall be Class C. Top bars so placed that more than 12 inches of concrete is cast below the reinforcement shall be lapped for 1.4 x basic lap. Reinforcement bar splices shall be in accordance with the following table unless shown otherwise on the drawing.

Bar Size	Basic Lap	1.4 Basic Lap
#4	1'-8"	2'-5"
#5	2'-2"	3'-0"
#6	2'-7"	3'-7"
#7	3'-5"	4'-10"
#8	4'-6"	6'-4"
#9	5'-9"	8'-1"
#10	7'-3"	10'-3"
#11	9'-0"	12'-7"

**GENERAL NOTES, INDEX OF SHEETS  
AND TOTAL BILL OF MATERIAL  
MULTI-USE PATH UNDER  
IL 25/STEARNS ROAD  
F.A.P. 360 - SEC. 06-00214-15-BR  
KANE COUNTY  
STATION 916+09.93  
STRUCTURE NO. 045-3173**

DESIGNED	AAY
CHECKED	AJK
DRAWN	VH
CHECKED	HMA/DMC

▲ Addendum #1 - 6/5/09

**benesch**

alfred benesch & company  
Engineers • Surveyors • Planners  
205 North Michigan Avenue, Suite 2400  
Chicago, Illinois 60601  
312-565-0450  
Job # 3944