

HOT-MIX ASPHALT SCHEDULE

Location	Remarks (End Location)	Length	Proposed Surface		Bit Materials Prime Coat (2 Applications) Ton	Agg Prime Coat Ton	Polymerized Level Binder, (HM) N70 (10 ton/mile) Ton	Polymerized Level Binder, (MM) N70 Ton	Hot-Mix Asphalt Surf. Cse. Mix "C", N50 Ton	Hot-Mix Asphalt Binder Cse., IL-19.0, N70 Ton	Polymerized Hot-Mix Asphalt Surf. Cse. Mix "D", N70 Ton	Hot-Mix Asphalt Shoulders 5 1/2" Sq Yd
			Width	Sq Yd								
IL 72 Mainline												
Sta 1782 + 34.4 - 1782 + 84.4	Butt Joint	50	26'	144.6	0.08	0.22	0.1	10.1			12.1	
Sta 1782 + 84.4 - 1786 + 8.2	West Leg	323.8	35.5' & Var	2051.4	1.17	3.08	0.6	143.6			172.3	
Sta 1786 + 36.0 - 1788 + 81.2	East Leg	245.2	26' & Var	1627.6	0.93	2.44	0.5	113.9			136.7	
Sta 1788 + 81.2 - 1789 + 31.2	Butt Joint	50	26'	144.3	0.08	0.22	0.1	10.1			12.1	
IL 251 Mainline												
Sta 780 + 86.0 - 784 + 24.5	Milled Section	338.5	28.8'	931.1	0.53	1.40	0.6	65.2			78.2	
Sta 784 + 24.5 - 784 + 74.5	50' Taper	50	28.8'	135.4	0.08	0.20	0.1	9.5			11.4	
Sta 784 + 74.5 - 787 + 25.0	South Leg	250.5	28.8' & Var	698.3	0.40	1.05	0.5	48.9			58.7	
Sta 787 + 25.0 - 789 + 93.0	North Leg	268	27.4' & Var	796.3	0.46	1.19	0.5	55.7			66.9	
Sta 789 + 93.0 - 790 + 43.0	Butt Joint	50	27.4'	151.4	0.09	0.23	0.1	10.6			12.7	
IL 72 & IL 251 Widening												
Sta 1782 + 84.4 - 1786 + 9.1	NW Return	324.7	Varies	426.1	0.24	0.64				214.8		
Sta 1783 + 31.4 - 1786 + 9.1	SW Return	277.7	Varies	409.0	0.23	0.61				206.1		
Sta 1786 + 35.0 - 1787 + 64.4	NE Return	129.4	Varies	359.4	0.21	0.54				181.1		
Sta 1786 + 35.0 - 1788 + 18.0	SE Return	183	Varies	334.7	0.19	0.50				168.7		
IL 72 Shoulder												
Sta 1781 + 75.3 - 1782 + 84.4	Shldr - LT	109.1	4' - 9.5'	79.4	0.02				11.1			79.4
Sta 1782 + 84.4 - 1785 + 99.6	Shldr - LT	315.2	2' - 8'	221.1	0.06				31.0			221.1
Sta 1782 + 84.4 - 1785 + 22.0	Shldr - RT	237.6	2.6' - 8'	189.7	0.05				26.6			189.7
Sta 1786 + 44.8 - 1788 + 81.2	Shldr - LT	236.4	4' - 8'	205.4	0.06				28.8			205.4
Sta 1786 + 43.3 - 1788 + 81.2	Shldr - RT	237.9	4' - 8'	165.5	0.05				23.2			165.5
Sta 1788 + 81.2 - 1789 + 31.2	Shldr - RT	50	8' - 4'	36.0	0.01				5.0			36.0
Sta 1788 + 81.2 - 1789 + 31.2	Shldr - RT	50	8' - 4'	32.9	0.01				4.6			32.9
IL 251 Shoulder												
Sta 781 + 5.8 - 784 + 24.5	Shldr - LT	318.7	6' & Var	212.2	0.06				29.7			212.2
Sta 781 + 5.8 - 784 + 24.5	Shldr - RT	318.7	6' & Var	213.2	0.06				29.8			213.2
Sta 784 + 24.5 - 784 + 74.5	Shldr - LT	50	6' & Var	35.2	0.01				4.9			35.2
Sta 784 + 24.5 - 784 + 74.5	Shldr - RT	50	6' & Var	34.0	0.01				4.8			34.0
Sta 784 + 74.5 - 786 + 1.9	Shldr - LT	127.4	6' & Var	93.3	0.03				13.1			93.3
Sta 784 + 74.5 - 786 + 26.6	Shldr - RT	152.1	6' & Var	117.5	0.03				16.5			117.5
Sta 788 + 28.7 - 789 + 93.0	Shldr - LT	164.3	8'	152.6	0.04				21.4			152.6
Sta 788 + 57.6 - 789 + 93.0	Shldr - RT	135.4	8'	119.4	0.03				16.7			119.4
Sta 789 + 93.0 - 790 + 43.0	Shldr - RT	50	8' - 4'	36.2	0.01				5.1			36.2
Sta 789 + 93.0 - 790 + 43.0	Shldr - RT	50	8' - 4'	36.1	0.01				5.1			36.1
GRAND TOTAL					5.3	12.3	3.1	467.6	277.2	770.7	561.2	1979.7