

SCHEDULE OF QUANTITIES

HOT-MIX ASPHALT (SHEET 2 OF 4)

NORTHBOUND RAMPS

	STATION	WIDTH AT LOCATION (FOOT)	TO	STATION	WIDTH AT LOCATION (FOOT)	LENGTH (FOOT)	AVERAGE WIDTH (FOOT)	AREA (SQ YD)	INSIDE SHOULDER WIDTH AT LOCATION (FOOT)	OUTSIDE SHOULDER WIDTH AT LOCATION (FOOT)	SHOULDER AREA (SQ YD)	BINDER THICKNESS (INCH)	SURFACE THICKNESS (INCH)	SHOULDER THICKNESS (INCH)	* BITUMINOUS MATERIALS (PRIME COAT) 40600100 (GALLON)	AGGREGATE (PRIME COAT) 40600300 (TON)	POLYMERIZED HOT-MIX ASPHALT BINDER COURSE, IL-19.0, FG, N90 40603243 (TON)	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N90 40603545 (TON)	HOT-MIX ASPHALT SHOULDERS 48203100 (TON)	
NORTHBOUND C.H. 12 RAMPS																				
TRANSITION	C.H. 12 B	11+68.00	16.0	12+13.00	16.0	45.00	16.0	80.0	4.0	6.0	50.0	0.00	1.50	1.50	13.0	0.2	0.0	6.7	4.2	
TRANSITION	C.H. 12 B	12+13.00	16.0	12+43.00	16.0	30.00	16.0	53.3	4.0	6.0	33.3	0.00	2.00	2.00	8.7	0.1	0.0	6.0	3.7	
TRANSITION	C.H. 12 B	12+43.00	16.0	12+80.50	16.0	37.50	16.0	66.7	4.0	6.0	41.7	1.63	1.50	3.13	21.7	0.3	6.1	5.6	7.3	
	C.H. 12 B	12+80.50	16.0	18+97.00	16.0	616.50	16.0	1,096.0	0.0	6.0	411.0	2.25	1.50	3.75	301.4	4.4	138.1	92.1	86.3	
	C.H. 12 B	18+97.00	18.0	27+47.27	1.0	850.27	9.5	897.5	0.0	6.0	566.8	2.25	1.50	3.75	292.9	3.6	113.1	75.4	119.0	
	GORE	12+80.50	27.0	17+97.00	4.0	516.50	-	0.0	0.0	0.0	653.9	0.00	0.00	3.75	130.8	0.0	0.0	0.0	137.3	
	GORE	17+97.00	4.0	18+97.00	2.0	100.00	3.0	33.3	0.0	0.0	0.0	2.25	1.50	0.00	6.7	0.1	4.2	2.8	0.0	
	C.H. 12 C	0+00.00	1.0	2+97.00	17.0	297.00	9.0	297.0	0.0	6.0	198.0	2.25	1.50	3.75	99.0	1.2	37.4	24.9	41.6	
	C.H. 12 C	2+97.00	16.0	6+60.50	16.0	363.50	16.0	646.2	0.0	6.0	242.3	2.25	1.50	3.75	177.7	2.6	81.4	54.3	50.9	
TRANSITION	C.H. 12 C	6+60.50	16.0	6+98.00	16.0	37.50	16.0	66.7	4.0	6.0	41.7	1.63	1.50	3.13	21.7	0.3	6.1	5.6	7.3	
TRANSITION	C.H. 12 C	6+98.00	16.0	7+28.00	16.0	30.00	16.0	53.3	4.0	6.0	33.3	0.00	2.00	2.00	8.7	0.1	0.0	6.0	3.7	
TRANSITION	C.H. 12 C	7+28.00	16.0	7+73.00	16.0	45.00	16.0	80.0	4.0	6.0	50.0	0.00	1.50	1.50	13.0	0.2	0.0	6.7	4.2	
	GORE	2+97.00	1.0	3+97.00	6.0	100.00	3.5	38.9	0.0	0.0	0.0	2.25	1.50	0.00	7.8	0.2	4.9	3.3	0.0	
	GORE	3+97.00	6.0	6+60.50	19.0	263.50	-	0.0	0.0	0.0	364.3	0.00	0.00	3.75	72.9	0.0	0.0	0.0	76.5	
NORTHBOUND C.H. 8 RAMPS																				
TRANSITION	C.H. 8 B	9+31.00	16.0	9+76.00	16.0	45.00	16.0	80.0	4.0	6.0	50.0	0.00	1.50	1.50	13.0	0.2	0.0	6.7	4.2	
TRANSITION	C.H. 8 B	9+76.00	16.0	10+06.00	16.0	30.00	16.0	53.3	4.0	6.0	33.3	0.00	2.00	2.00	8.7	0.1	0.0	6.0	3.7	
TRANSITION	C.H. 8 B	10+06.00	16.0	10+43.50	16.0	37.50	16.0	66.7	4.0	6.0	41.7	1.63	1.50	3.13	21.7	0.3	6.1	5.6	7.3	
	C.H. 8 B	10+43.50	16.0	13+70.00	16.0	326.50	16.0	580.4	0.0	6.0	217.7	2.25	1.50	3.75	159.6	2.3	73.1	48.8	45.7	
	C.H. 8 B	13+70.00	18.0	22+00.00	1.0	830.00	9.5	876.1	0.0	6.0	553.3	2.25	1.50	3.75	285.9	3.5	110.4	73.6	116.2	
	GORE	10+43.50	27.0	12+70.00	4.0	226.50	-	0.0	0.0	0.0	202.4	0.00	0.00	3.75	40.5	0.0	0.0	0.0	42.5	
	GORE	12+70.00	4.0	13+70.00	2.0	100.00	3.0	33.3	0.0	0.0	0.0	2.25	1.50	0.00	6.7	0.1	4.2	2.8	0.0	
	C.H. 8 C	0+00.00	1.0	3+07.00	17.0	307.00	9.0	307.0	0.0	6.0	204.7	2.25	1.50	3.75	102.3	1.2	38.7	25.8	43.0	
	C.H. 8 C	3+07.00	16.0	6+60.50	16.0	353.50	16.0	628.4	0.0	6.0	235.7	2.25	1.50	3.75	172.8	2.5	79.2	52.8	49.5	
TRANSITION	C.H. 8 C	6+60.50	16.0	6+98.00	16.0	37.50	16.0	66.7	4.0	6.0	41.7	1.63	1.50	3.13	21.7	0.3	6.1	5.6	7.3	
TRANSITION	C.H. 8 C	6+98.00	16.0	7+28.00	16.0	30.00	16.0	53.3	4.0	6.0	33.3	0.00	2.00	2.00	8.7	0.1	0.0	6.0	3.7	
TRANSITION	C.H. 8 C	7+28.00	16.0	7+73.00	16.0	45.00	16.0	80.0	4.0	6.0	50.0	0.00	1.50	1.50	13.0	0.2	0.0	6.7	4.2	
	GORE	3+07.00	1.0	4+07.00	6.0	100.00	3.5	38.9	0.0	0.0	0.0	2.25	1.50	0.00	7.8	0.2	4.9	3.3	0.0	
	GORE	4+07.00	6.0	6+98.00	20.0	291.00	-	0.0	0.0	0.0	362.9	0.00	0.00	3.75	72.6	0.0	0.0	0.0	76.2	
															TOTALS:	2,111.0	24.3	714.0	533.1	945.5

* APPLICATION RATE FOR BITUMINOUS MATERIALS (PRIME COAT) IS 0.1 GAL/SQ YD FOR EACH COAT.