

# SCHEDULE OF QUANTITIES

## HOT-MIX ASPHALT (SHEET 4 OF 4)

### SOUTHBOUND RAMPS

	STATION	WIDTH AT LOCATION (FOOT)	TO	STATION	WIDTH AT LOCATION (FOOT)	LENGTH (FOOT)	AVERAGE WIDTH (FOOT)	AREA (SQ YD)	INSIDE SHOULDER WIDTH AT LOCATION (FOOT)	OUTSIDE SHOULDER WIDTH AT LOCATION (FOOT)	SHOULDER AREA (SQ YD)	BINDER THICKNESS (INCH)	SURFACE THICKNESS (INCH)	SHOULDER THICKNESS (INCH)	* BITUMINOUS MATERIALS (PRIME COAT) 40600100 (GALLON)	AGGREGATE (PRIME COAT) 40600300 (TON)	POLYMERIZED HOT-MIX ASPHALT BINDER COURSE, IL-19.0, FG, N90 40603243 (TON)	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N90 40603545 (TON)	HOT-MIX ASPHALT SHOULDERS 48203100 (TON)	
<b>SOUTHBOUND C.H. 12 RAMPS</b>																				
	C.H. 12 A	0+00.00		3+28.00	17.0	328.00	9.0	328.0	0.0	6.0	218.7	2.25	1.50	3.75	109.3	1.3	41.3	27.6	45.9	
	C.H. 12 A	3+28.00		6+57.50	16.0	329.50	16.0	585.8	0.0	6.0	219.7	2.25	1.50	3.75	161.1	2.3	73.8	49.2	46.1	
TRANSITION	C.H. 12 A	6+57.50		6+95.00	16.0	37.50	16.0	66.7	4.0	6.0	41.7	1.63	1.50	3.13	21.7	0.3	6.1	5.6	7.3	
TRANSITION	C.H. 12 A	6+95.00		7+25.00	16.0	30.00	16.0	53.3	4.0	6.0	33.3	0.00	2.00	2.00	8.7	0.1	0.0	6.0	3.7	
TRANSITION	C.H. 12 A	7+25.00		7+70.00	16.0	45.00	16.0	80.0	4.0	6.0	50.0	0.00	1.50	1.50	13.0	0.2	0.0	6.7	4.2	
	GORE	3+28.00		4+28.00	7.0	100.00	4.0	44.4	0.0	0.0	0.0	2.25	1.50	0.00	8.9	0.2	5.6	3.7	0.0	
	GORE	4+28.00		6+57.50	20.0	229.50	-	0.0	0.0	0.0	351.7	0.00	0.00	3.75	70.3	0.0	0.0	0.0	73.9	
TRANSITION	C.H. 12 D	10+38.00		10+83.00	16.0	45.00	16.0	80.0	4.0	6.0	50.0	0.00	1.50	1.50	13.0	0.2	0.0	6.7	4.2	
TRANSITION	C.H. 12 D	10+83.00		11+13.00	16.0	30.00	16.0	53.3	4.0	6.0	33.3	0.00	2.00	2.00	8.7	0.1	0.0	6.0	3.7	
	C.H. 12 D	11+13.00		11+50.50	16.0	37.50	16.0	66.7	4.0	6.0	41.7	1.63	1.50	3.13	21.7	0.3	6.1	5.6	7.3	
	C.H. 12 D	11+50.50		16+58.00	16.0	507.50	16.0	902.2	0.0	6.0	338.3	2.25	1.50	3.75	248.1	3.6	113.7	75.8	71.1	
	C.H. 12 D	16+58.00		23+95.61	1.0	737.61	9.5	778.6	0.0	6.0	491.7	2.25	1.50	3.75	254.1	3.1	98.1	65.4	103.3	
	GORE	11+50.50		15+58.00	2.0	407.50	-	0.0	0.0	0.0	340.0	0.00	0.00	3.75	68.0	0.0	0.0	0.0	71.4	
	GORE	15+58.00		16+58.00	2.0	100.00	2.0	22.2	0.0	0.0	0.0	2.25	1.50	0.00	4.4	0.1	2.8	1.9	0.0	
<b>SOUTHBOUND C.H. 8 RAMPS</b>																				
	C.H. 8 A	0+00.00		3+02.00	17.0	302.00	9.0	302.0	0.0	6.0	201.3	2.25	1.50	3.75	100.7	1.2	38.1	25.4	42.3	
	C.H. 8 A	3+02.00		5+90.50	16.0	288.50	16.0	512.9	0.0	6.0	192.3	2.25	1.50	3.75	141.0	2.1	64.6	43.1	40.4	
TRANSITION	C.H. 8 A	5+90.50		6+28.00	16.0	37.50	16.0	66.7	4.0	6.0	41.7	1.63	1.50	3.13	21.7	0.3	6.1	5.6	7.3	
TRANSITION	C.H. 8 A	6+28.00		6+58.00	16.0	30.00	16.0	53.3	4.0	6.0	33.3	0.00	2.00	2.00	8.7	0.1	0.0	6.0	3.7	
TRANSITION	C.H. 8 A	6+58.00		7+03.00	16.0	45.00	16.0	80.0	4.0	6.0	50.0	0.00	1.50	1.50	13.0	0.2	0.0	6.7	4.2	
	GORE	3+02.00		4+02.00	6.0	100.00	3.5	38.9	0.0	0.0	0.0	2.25	1.50	0.00	7.8	0.2	4.9	3.3	0.0	
	GORE	4+02.00		5+90.50	20.0	188.50	-	0.0	0.0	0.0	235.0	0.00	0.00	3.75	47.0	0.0	0.0	0.0	49.3	
TRANSITION	C.H. 8 D	8+28.00		8+73.00	16.0	45.00	16.0	80.0	4.0	6.0	50.0	0.00	1.50	1.50	13.0	0.2	0.0	6.7	4.2	
TRANSITION	C.H. 8 D	8+73.00		9+03.00	16.0	30.00	16.0	53.3	4.0	6.0	33.3	0.00	2.00	2.00	8.7	0.1	0.0	6.0	3.7	
TRANSITION	C.H. 8 D	9+03.00		9+40.50	16.0	37.50	16.0	66.7	4.0	6.0	41.7	1.63	1.50	3.13	21.7	0.3	6.1	5.6	7.3	
	C.H. 8 D	9+40.50		12+34.00	16.0	293.50	16.0	521.8	0.0	6.0	195.7	2.25	1.50	3.75	143.5	2.1	65.7	43.8	41.1	
	C.H. 8 D	12+34.00		21+04.00	1.0	870.00	9.5	918.3	0.0	6.0	580.0	2.25	1.50	3.75	299.7	3.7	115.7	77.1	121.8	
	GORE	9+40.50		11+34.00	2.0	193.50	-	0.0	0.0	0.0	169.1	0.00	0.00	3.75	33.8	0.0	0.0	0.0	35.5	
	GORE	11+34.00		12+34.00	2.0	100.00	2.0	22.2	0.0	0.0	0.0	2.25	1.50	0.00	4.4	0.1	2.8	1.9	0.0	
															TOTALS:	1,875.7	22.4	651.5	491.4	802.9

\* APPLICATION RATE FOR BITUMINOUS MATERIALS (PRIME COAT) IS 0.1 GAL/SQ YD FOR EACH COAT.

### SUMMARY

	BITUMINOUS MATERIALS (PRIME COAT) 40600100 (GALLON)	AGGREGATE (PRIME COAT) 40600300 (TON)	POLYMERIZED HOT-MIX ASPHALT BINDER COURSE, IL-19.0, FG, N90 40603243 (TON)	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N90 40603545 (TON)	HOT-MIX ASPHALT SHOULDERS 48203100 (TON)
NB RURAL TOTAL:	22,454.1	274.5	8,633.8	5,873.7	9,158.8
NB RURAL ROUNDED:	22,460.0	280.0	8,640.0	5,880.0	9,160.0
SB RURAL TOTAL:	22,304.2	272.7	8,578.4	5,836.8	9,094.9
SB RURAL ROUNDED:	22,310.0	280.0	8,580.0	5,840.0	9,100.0
TOTAL:	44,770.0	560.0	17,220.0	11,720.0	18,260.0

### INCIDENTAL HOT-MIX ASPHALT

LOCATION	STATION	AREA (SQ YD)	THICKNESS (IN)	BITUMINOUS MATERIALS (PRIME COAT) 40800010 (GALLONS)	AGGREGATE (PRIME COAT) 40800030 (TONS)	INCIDENTAL HMA SURFACING 40800050 (TONS)
MEDIAN CROSSOVER	432+40.17	264.8	3.75	26.5	0.5	55.6
ROUNDED TOTAL:				30.0	1.0	60.0