

FAU 9760 (US 45) PAVEMENT RESURFACING SCHEDULE

LOCATION STATION TO STATION	LENGTH	ROADWAY WIDTH	AGG. SHOULDER WIDTH	ROADWAY AREA	HOT-MIX ASP. SURF. REMOV. 3/4"	HOT-MIX ASP. SURF. REMOV. 2 1/4"	TEMP RAMP	POLY. HOT-MIX ASP. SUR. CSE., MIX. D. N105 (1 1/2")	POLY. LEVELING BINDER (MM) N90 (3/4")	BITUMINOUS MATERIAL (PRIME COAT)	AGG. WEDGE SHOULDER, TY. B	FOR INFORMATIONAL PURPOSE ONLY										
												(FT)	(FT)	(FT)	(SQ YD)	(SQ YD)	(SQ YD)	(SQ YD)	(TON)	(TON)	(LBS)	(TON)
												FAU 9760 (US 45) - STA. 1060+67 TO STA. 1137+25 (URBAN LIMITS)										
	1060+67.00	TO	1082+30.00	2163	26	2.0	6249	6249		22	528	263	4218	42								
	1082+30.00	TO	1084+05.00	175	34		661	661			56	28	446									
Lt.	1082+30.00	TO	1084+05.00	175		2.0								2								
Rt.	1082+30.00	TO	1085+18.00	288		2.0								3								
	1084+05.00	TO	1085+18.00	113	49		615	615			52	26	415									
	1085+18.00	TO	1098+72.00	1354	56		8425	8425			720	354	5687									
	1098+72.00	TO	1105+20.00	648	62		4464	4464			375	188	3013									
	1105+20.00	TO	1107+00.00	180	55		1100	1100			93	47	743									
	1107+00.00	TO	1109+07.00	207	48		1104	1104			93	47	745									
	1109+07.00	TO	1110+03.20	96	62		663	663			56	28	447									
Eq. Sta. 1110+03.20 (bk.) = Sta. 1110+00.00 (ah.)																						
	1110+00.00	TO	1131+26.00	2126	62		14646	14645		52	1231	616	9886									
	1131+26.00	TO	1134+47.00	321	62		2211				190	93	1493									
	1134+47.00	TO	1137+25.00	278	62		1,915	1915		104	161	81	1293									
FAU 9760 TOTALS								7,525	32,316	178	3555	1771	28,386	47								

US 45 SIDEROADS RESURFACING SCHEDULE

LOCATION STATION TO STATION	EDGE OF PAV' T.	15' BK. FROM EP.	SURFACE TYPE	ROADWAY AREA	INCIDENTAL HOT-MIX ASP. SUR.	BITUMINOUS MATERIALS (PRIME COAT)	FOR INFORMATIONAL PURPOSE ONLY				
							(FT)	(FT)	(SQ YD)	(TON)	(LBS)
							FAU 9760 - STA. 1060+67 to STA. 1137+25 (Urban Limits)				
Urban Side Roads											
Lt.	Triplet St.	1065+42.00	51	24	Oil & Chip	63	11	92			
TOTALS								11	92		

• FAU 9760 (US 45)