



1. ALL SIGNING SHALL BE IN ACCORDANCE WITH THE APPLICABLE PROVISIONS OF THE STATE OF ILLINOIS "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION ADOPTED JANUARY 1, 2012", "THE QUALITY STANDARD FOR WORK ZONE TRAFFIC CONTROL DEVICES ADOPTED 2004", THE DETAILS IN THESE PLANS, THE LATEST EDITION OF THE STATE OF ILLINOIS "MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES", THE SPECIAL PROVISIONS FOR TRAFFIC CONTROL AND PROTECTION.
2. THE ENGINEER SHALL BE NOTIFIED IN WRITING AT LEAST THREE WEEKS PRIOR TO THE DAY THE DETOUR IS TO BE IN EFFECT. THE ENGINEER SHALL DETERMINE THE HOUR OF CLOSURE, THE ENGINEER WILL CONTACT THE APPROPRIATE LOCAL AGENCIES AND INTERESTED PARTIES.
3. THE CONTRACTOR SHALL SUPPLY TO THE ENGINEER THE NAMES AND TELEPHONE NUMBERS OF HIS REPRESENTATIVES ON THE CONSTRUCTION SITE AND HIS REPRESENTATIVE RESPONSIBLE FOR THE DETOUR SIGNING PRIOR TO THE START OF THE WORK. THE CITY OF ROLLING MEADOWS REPRESENTATIVE FOR THIS DETOUR IS: MR. FRED VOGT; DIRECTOR OF PUBLIC WORKS, 847-963-0500.
4. IF REQUESTED BY THE CONTRACTOR IN WRITING AT LEAST THREE WEEKS PRIOR TO THE DAY THE DETOUR IS TO BE IN EFFECT, THE ENGINEER WILL FIELD LOCATE THE POSITIONS OF ANY SIGNS.
5. LONGITUDINAL DIMENSIONS SHOWN ON THESE PLANS MAY BE ADJUSTED TO FIT FIELD CONDITIONS, WITH THE APPROVAL OF THE ENGINEER.
6. THE ROAD SHALL NOT BE CLOSED UNTIL ALL SIGNING IS ERECTED IN ACCORDANCE WITH THE DETOUR PLAN AND INSPECTED AND APPROVED BY THE ENGINEER.
7. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ENSURING THAT ALL BARRICADES, SIGNS, LIGHTS, AND OTHER DEVICES INSTALLED BY HIM ARE IN PLACE AND OPERATING 24 HOURS EACH DAY INCLUDING SUNDAYS AND HOLIDAYS DURING THE TIME THE DETOUR IS IN EFFECT.
8. THE TRAFFIC CONTROL SHOWN ON THE DETOUR PLAN IS THE MINIMUM NECESSARY TO ENSURE THIS ROAD CLOSURE. THE CONTRACTOR SHALL MAKE ALL CHANGES IN TRAFFIC CONTROL THAT IS DEEMED NECESSARY BY THE ENGINEER. ADDITIONS AND DELETIONS OF TRAFFIC CONTROL FOR THIS DETOUR SHALL BE CONSIDERED INCIDENTAL TO THE PAY ITEM "TRAFFIC CONTROL AND PROTECTION."
9. ALL EXISTING SIGNING THAT IS NOT APPLICABLE WHILE THE DETOUR IS IN EFFECT SHALL BE COMPLETELY COVERED BY THE CONTRACTOR, IN A MANNER APPROVED BY THE ENGINEER.
10. ALL DETOUR SIGNING SHALL BE POST MOUNTED IF THE ROAD CLOSURE IS TO EXCEED FOUR (4) CALENDAR DAYS.
11. ALL DETOUR SIGNING EXCEPT REGULATORY SIGNS SHALL HAVE BLACK LEGENDS ON FLUORESCENT ORANGE SHEETING AND STANDARD BLACK BORDERS. THE FLUORESCENT ORANGE REFLECTIVE SHEETING SHALL MEET THE REQUIREMENTS OF ARTICLE 1084.02 OF THE STANDARD SPECIFICATIONS. ALL DETOUR SIGNING SHALL BE NEW OR LIKE NEW CONDITION OF THE SIGNS. THE ENGINEER SHALL BE THE SOLE JUDGE OF THE CONDITION OF THE SIGNS.
12. THE SIZES OF ALL SIGNS NOT SPECIFIED IN THESE PLANS SHALL BE AS REQUIRED BY THE ILLINOIS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.
13. AS A MINIMUM, ALL AMBER FLASHING LIGHTS THAT ARE REQUIRED FOR THIS DETOUR SHALL MEET THE REQUIREMENTS FOR TYPE A-LOW INTENSITY FLASHING LIGHTS IN ARTICLE 1084.01 OF THE STANDARD SPECIFICATIONS. ALL LIGHTS SHALL OPERATE DURING THE HOURS OF DARKNESS. ONLY LIGHTS THAT HAVE BEEN APPROVED BY THE ILLINOIS DEPARTMENT OF TRANSPORTATION SHALL BE USED.
14. WHEN REQUIRED THE MINIMUM DIMENSIONS OF THE ORANGE WARNING FLAGS SHOWN IN THESE PLANS ARE 18" X 18".
15. ALL BARRICADES SHALL HAVE REFLECTORIZED STRIPING ON BOTH SIDES OF THE BARRICADES. THE TYPE III BARRICADES USED AT THE POINT OF CLOSURE TO THRU TRAFFIC SHALL NOT EXCEED 8 FEET IN WIDTH EACH, FOR A SINGLE APPROACH LANE.
16. THE ROAD NAME SIGN SHALL HAVE A BLACK LEGEND ON FLUORESCENT ORANGE REFLECTIVE SHEETING. THE SIGN BLANK SHALL BE A 9" X VARIABLE OR A 12" X VARIABLE WITH DESIGN SERIES C LETTERS. THE CAPITAL LETTERS SHALL BE 6" WITH 5" LOWER CASE.
17. DURING NON-WORKING HOURS AT THE POINT OF ROAD CLOSURE TO ALL TRAFFIC THE CONTRACTOR SHALL PROVIDE A MEANS TO RESTRAIN THE BARRICADES FROM EASY MOVEMENT BY VANDALS. THE CHOSEN METHOD SHALL BE APPROVED BY THE ENGINEER.
18. CONSTRUCTION EQUIPMENT SHALL NOT BE PARKED WITHIN 25 FT BEHIND THE TYPE III BARRICADES. IN ANY EVENT ARTICLE 701.04 OF THE STANDARD SPECIFICATIONS SHALL APPLY.
19. THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING THE VISIBILITY OF ALL DETOUR AND CONSTRUCTION SIGNING, INCLUDING BRUSHING BACK VEGETATION IF DEEMED NECESSARY BY THE ENGINEER.
20. THE ENGINEER SHALL BE NOTIFIED AT LEAST TWO (2) HOURS BEFORE THE ROAD IS TO BE OPENED TO TRAFFIC. THE ENGINEER WILL CONTACT THE APPROPRIATE LOCAL AGENCIES AND INTERESTED PARTIES.
21. THE TEMPORARY DETOUR ROAD SHALL BE BARRICADED ONCE DETOUR IS REMOVED.
22. BRIDGE MAY BE CLOSED FOR NO LONGER THAN 60 DAYS.

### LEGEND

|  |  |   |   |  |
|--|--|---|---|--|
| <br><b>SOUTH</b><br>M3-3-2412<br>24"x12"   | <br><b>CARRIAGE WAY DR.</b><br>6" BLACK LETTERS ON ORANGE BACKGROUND SPECIAL | <br><b>NORTH</b><br>M3-7-2412<br>24"x12"          | <br><b>DETOUR</b><br>M4-9R<br>30"x21"             | <br><b>DETOUR</b><br>M4-9L<br>30"x21"            |
| ①  | ②  | ③   | ④   | ⑤  |
| <br><b>DETOUR</b><br>M4-9<br>30"x21"   | <br><b>DETOUR</b><br>M4-9<br>30"x21"   | <br><b>DETOUR AHEAD</b><br>W20-2<br>48"x48"       | <br><b>ROAD CLOSED 500 FT</b><br>W20-3<br>48"x48" | <br><b>ROAD CLOSED AHEAD</b><br>W20-3<br>48"x48" |
| ⑥  | ⑦  | ⑧   | ⑨   | ⑩  |
| <br><b>END DETOUR</b><br>M4-8a<br>24"x18"  | <br><b>DETOUR</b><br>M4-9<br>30"x21"   | <br><b>TWO-WAY TRAFFIC</b><br>W6-3 (0)<br>36"x36" | <br><b>STOP</b><br>R1-1<br>48"x48"                | <br><b>ROAD CLOSED</b><br>R11-2<br>48"x30"       |
| ⑫  | ⑬  | ⑭   | ⑮   | ⑯  |
| TYPE III BARRICADE<br>DIRECTION OF DETOURED TRAFFIC<br>WORK ZONE                               |  |   |   |  |
| <br><b>CARRIAGE WAY DR. CLOSED AT SALT CREEK</b><br>6" BLACK LETTERS ON ORANGE BACKGROUND<br>⑰ |  |   |   |  |

|  |                      |                |                |   |   |                              |                 |                |                    |                 |
|--|----------------------|----------------|----------------|---|---|------------------------------|-----------------|----------------|--------------------|-----------------|
| FILE NAME<br>N:\ROLLINGMEADOWS\932622\DETOUR.DWG | USER NAME<br>prazlan | DESIGNED<br>JA | REVISED<br>--- | <b>STATE OF ILLINOIS<br/>DEPARTMENT OF TRANSPORTATION</b>           | <b>CARRIAGE WAY DRIVE<br/>DETOUR NOTES AND PLAN</b> | F.A.U. RTE<br>10-00101-00-BR | SECTION<br>CROK | COUNTY<br>COOK | TOTAL SHEETS<br>34 | SHEET NO.<br>13 |
| PLOT SCALE<br>NONE                               |                      |                |                | CONTRACT NO. 63787<br>FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT |   |                              |                 |                |                    |                 |
| PLOT DATE<br>4/1/2013                            |                      |                |                | SCALE: N.T.S. SHEET NO. ___ OF ___ SHEETS STA. ___ TO STA. ___      |   |                              |                 |                |                    |                 |