

HMA PAVEMENT			
LOCATION	HMA BASE COURSE	HMA SURFACE* COURSE	INCIDENTAL HMA SURFACING
	10 1/2" SQ YD	MIX "D", N70 TON	TON
STA. 205+00 TO STA. 207+31.82	1480	125	
STA. 209+16.17 TO STA. 213+80	2987	251	
STA. 213+81 RT - CE			6.5
STA. 213+67 RT - TEMP ST I			63
STA. 214+32 LT - TEMP CE ST II			18.5
TOTAL	4467	376	88

\* POLYMERIZED

PORTLAND CEMENT CONCRETE DRIVEWAY PAVEMENT		
LOCATION	PORTLAND CEMENT CONCRETE DRIVEWAY, 6 INCH	PORTLAND CEMENT CONCRETE DRIVEWAY, 8 INCH
	SQ YD	SQ YD
STA. 209+78 LT - PE	117	
STA. 212+08 RT - CE		76
STA. 212+70 RT - CE		58
STA. 213+36 LT - CE		90
TOTAL	117	224

DRIVEWAY PAVEMENT REMOVAL	
LOCATION	QUANTITY
	SQ YD
STA. 209+78 LT - PE	117
STA. 212+08 RT - CE	102
STA. 212+70 RT - CE	72
STA. 213+36 LT - CE	92
TOTAL	383

COMBINATION CURB AND GUTTER REMOVAL	
LOCATION	QUANTITY
	FOOT
STA. 205+00 TO STA. 206+50 LT	150
STA. 207+25 TO STA. 207+77 LT	52
STA. 208+48 TO STA. 208+78 LT	30
STA. 210+10 TO STA. 210+80 LT	81
STA. 211+06 TO STA. 213+80 LT	286
STA. 205+00 TO STA. 206+50 RT	150
STA. 207+74 TO STA. 208+25 RT	51
STA. 208+94 TO STA. 209+25 RT	31
STA. 210+10 TO STA. 213+37 RT	327
STA. 214+20 TO STA. 214+45 LT (ST II TEMP ACCESS)	25
TOTAL	1183

STORM SEWER REMOVAL					
LOCATION	STORM SEWER REMOVAL 12"	STORM SEWER REMOVAL 15"	STORM SEWER REMOVAL 42"	REMOVING MANHOLES	REMOVING INLETS
	FOOT	FOOT	FOOT	EACH	EACH
STA. 209+02, 37' RT TO STA. 210+22, 31' RT			121		
STA. 209+83, 25' RT TO STA. 209+83, 31' RT	6				
STA. 0+41, 16' LT TO STA. 0+59, 16' LT (REED)	19				
STA. 0+41, 16' LT TO STA. 0+41, 15' RT (REED)	31				
STA. 0+58, 14' RT TO STA. 0+42, 15' RT (REED)		16			
STA. 0+42, 16' RT TO STA. 0+42, 26' RT (REED)		10			
STA. 209+83, 31' RT (5' DIA)				1	
STA. 0+41, 16' LT (REED)					1
STA. 0+41, 15' RT (REED)					1
TOTAL	56	26	121	1	2

PIPE CULVERT REMOVAL	
LOCATION	QUANTITY
	FOOT
STA. 208+71, 46' LT TO STA. 208+95, 46' LT	24
TOTAL	24

COMBINATION CONCRETE CURB & GUTTER, TYPE B-6.24	
LOCATION	QUANTITY
	FOOT
STA. 205+00 TO STA. 207+09.82 LT	210
STA. 208+92.17 TO STA. 210+79.92 LT	208
STA. 211+05.93 TO STA. 213+80 LT	249
STA. 205+00 TO STA. 207+62.82 RT	263
STA. 209+50.17 TO STA. 213+37 RT	387
STA. 214+20 TO STA. 214+45 LT	25
TOTAL	1342

SIDEWALK REMOVAL	
LOCATION	QUANTITY
	SQ FT
STA. 205+00 TO STA. 207+75 LT	1093
STA. 208+45 TO STA. 209+67 LT	520
STA. 209+88 TO STA. 210+74 LT	340
STA. 211+10 TO STA. 213+12 LT	791
STA. 213+58 TO STA. 213+80 LT	81
STA. 214+20 TO STA. 214+45 LT (ST II TEMP ACCESS)	97
STA. 205+75 TO STA. 208+30 RT	977
STA. 208+97 TO STA. 211+88 RT	1153
STA. 212+30 TO STA. 212+49 RT	63
STA. 212+87 TO STA. 213+59 RT	275
TOTAL	5390

MANHOLES TO BE ADJUSTED	
LOCATION	QUANTITY
	FOOT
STA. 205+84, 20' LT.	1
STA. 213+31, 21' LT.	1
TOTAL	2

DETECTOR LOOP					
LOCATION	DETECTOR LOOP, TYPE 1	HANDHOLE	UNDERGROUND CONDUIT, PVC, 1 1/2" DIA.	UNDERGROUND CONDUIT, PVC 2" DIA.	ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 2C
	FOOT	EACH	FOOT	FOOT	FOOT
STA. 204+98 TO STA. 205+85 LT				87	87
STA. 205+85 TO STA. 207+24 LT			140		140
STA. 205+85 LT	72	1			
STA. 207+24 LT	37	1			
STA. 205+05 RT	147				
STA. 207+35.5 LT	52				
TOTAL	308	2	140	87	227

DETECTABLE WARNINGS	
LOCATION	QUANTITY
	SQ FT
STA. 210+65 LT	14
STA. 211+18 LT	14
STA. 213+54 RT	10
TOTAL	38