

F. A. P. ATEL	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
575	14 RS-4	HILL	33	2
STA.		TO STA.		
FED. ROAD DIST. NO. 1		BALANCE	FED. AID PROJECT	

INDEX OF SHEET

SHEET NO.	DESCRIPTION
1	COVER SHEET
2	INDEX OF SHEETS, STATE STANDARDS AND GENERAL NOTES
3-4	SUMMARY OF QUANTITIES
5-7	TYPICAL SECTIONS AND MIXTURE REQUIREMENT TABLE
8-11	ROADWAY AND PAVEMENT MARKING PLANS
12-14	DETECTOR LOOP REPLACEMENT PLANS
15-22	TRAFFIC SIGNAL MODERNIZATION PLANS
23	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING
24	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT
25	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT
26	BUTT JOINT AND HMA TAPER DETAILS
27	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS
28	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)
29	DISTRICT ONE TYPICAL PAVEMENT MARKINGS
30	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC)
31	PAVEMENT MARKINGS LETTERS AND SYMBOLS FOR TRAFFIC STAGING
32	ARTERIAL ROAD INFORMATION SIGN
33	DETECTOR ONE DETECTOR LOOP INSTALLATION DETAIL FOR ROADWAY RESURFACING

LIST OF STANDARDS

000001-04	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
442201-02	CLASS C AND D PATCHES
482011-02	BIT. SHOULDER STRIPS/ SHLDS. WITH RESURFACING OR WIDENING AND RESURFACING PROJECTS
701201-02	LANE CLOSURE, 2-L,2-W, DAY ONLY FOR SPEEDS ≥ 45MPH
701301-02	LANE CLOSURE, 2-L,2-W, SHORT TIME OPERATIONS
701306-01	LANE CLOSURE, 2-L,2-W SLOW MOVING OPERATIONS-DAY ONLY FOR SPEEDS ≥ 45
701311-02	LANE CLOSURE, 2-L,2W MOVING OPERATIONS-DAY ONLY
701701-04	URBAN LANE CLOSURES, MULTILANE INTERSECTION
702001-06	TRAFFIC CONTROL DEVICES

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED)

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES IN THE VILLAGE OF PLAINFIELD.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 40 MM (1 1/2 INCHES) WHERE THE SPEED LIMIT IS 80 KM/H (45 MPH) OR LESS AND 25 MM (1 INCH) WHERE THE SPEED LIMIT IS GREATER THAN 80 KM/H (45 MPH). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 75 MM (3 INCHES) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HOT-MIX ASPHALT TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MS. CORA MATHIS AREA TRAFFIC FIELD ENGINEER AT (815) 485-6475 OR (847) 715-8422 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKING.

THE CONTRACTOR SHALL CONTRACT THE DISTRICT ONE ARTERIAL TRAFFIC CONTROL SUPERVISOR @ (847) 705-4470 A MINIMUM 72 HOURS PRIOR TO BEGINNING WORK.

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION

**US ROUTE 30
INDEX OF SHEETS, STATE STANDARDS &
GENERAL NOTES**

SCALE: VERT. 1"=50'
HORIZ. 1"=50'
DATE 4/2/2007

DRAWN BY
CHECKED BY