RTE. SECTION COUNTY TOTAL SHEETS NO.
317 (44.45) RS-5. PEORIA 82 80 (46-1) RS-7. 45-(RB,RB-2,BR)[Direction parallel to —Tooth mark centerline General notes: 1. Coldmilling shall consist of two processes: Cutting with carbide teeth mounted on a rotating drum, and planing with a moldboard mounted immediately behind the cutting drum. 2. Other similar patterns will be acceptable if they consist of a smooth, flat, planed surface interspersed with a pattern of discontinuous longitudinal striations. Area between tooth marks planed by moldboard ±0.5(0.02) PLAN ഥ Area cut by PROVISION, tooth 15(%) TO 20(¾) Area planed by moldboard -Area planed by moldboard 350(14) R min.-DESIGNER NOTE
1. INCLUDE DISTRICT SPECIAL -Area cut by tooth 57(2.3) ±0.5(0.02) Existing bituminous surfacing left after cold milling Existing bituminous -surfacing left after cold milling SECTION B-B PROJECTED PERPENDICULAR TO CENTERLINE All dimensions are in millimeters (inches) unless otherwise noted. ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT CADD STANDARD BITUMINOUS SURFACE REMOVAL (COLD MILLING) SECTION A-A CADD STD NO. 440001-D4 SCALE: NOT DRAWN TO SCALE DATE **DATE** CHECKED BY

DGN-ONLY■

440001-D4