

DETECTABLE WARNINGS

STA. 301+10, 55' LT TO
STA. 301+15, 65' LT
10 SQ. FT.

SIDEWALK REMOVAL
STA. 301+10.16 56.00' LT TO
STA. 301+42, 61.15' LT
227 SQ. FT.

P.C.C. SIDEWALK, 5"
STA. 301+10.16 56.00' LT TO
STA. 301+15.28, 61.15' LT
17 SQ. FT.

CONTRACTOR SHALL DEPRESS
THE END OF THE CURB

HMA SURFACE REMOVAL, VARIABLE DEPTH
STA. 301+15.44, 65.38' LT TO
STA. 301+25.62, 53.48' LT
24 SQ. YD.

P.C.C. SIDEWALK, 5"
STA. 301+33.11 42.02' LT TO
STA. 301+42.79, 36.11' LT
45 SQ. FT.

**FILL SIDEWALK AREA WITH
REMOVAL AGGREGATE BASE
COURSE TYPE B**

PAVEMENT REMOVAL
STA. 301+60, 35' LT TO
STA. 301+72, 37' LT
16 SQ. YD.

P.C.C. SIDEWALK, 5"
STA. 301+60, 35' LT TO
STA. 301+72, 37' LT
144 SQ. FT.

**2" AGGREGATE SURFACE COURSE, TYPE B (CA 10)
AT EACH CAMPSITE (TYPICAL)**

INSTALL CONCRETE PARKING BLOCKS
STA. 301+50.86, 43.69' LT TO
STA. 301+73.00, 30.00' LT
2 EACH

TIMBER CURB REMOVAL
STA. 301+50.86, 43.69' LT TO
STA. 301+73.00, 30.00' LT
42 FOOT

V.E.C. CONTROL POINT #74
N: 590591.87
E: 2529674.49
ELEVATION: 501.99
DESCRIPTION: PK NAIL

V.E.C. CONTROL POINT #70
N: 590506.82
E: 2529532.93
ELEVATION: 503.04
DESCRIPTION: PK NAIL

DETECTABLE WARNINGS
STA. 301+37.88, 45.00' LT TO
STA. 301+33.11, 42.00' LT
10 SQ. FT.

PAINT PAVEMENT MARKING LINE, 6"
STA. 301+21.75, 49.00' LT TO
STA. 301+36.06, 45.94' LT
60 FEET

SIDEWALK REMOVAL
STA. 300+87.56, 14.00' LT TO
STA. 300+95.50, 18.46' LT
55 SQ. FT.

P.C.C. SIDEWALK, 5"
STA. 300+87.56, 14.00' LT TO
STA. 300+95.50, 18.46' LT
55 SQ. FT.

PAVEMENT REMOVAL
STA. 301+41.16, 41.70' RT TO
STA. 301+52.06, 49.27' RT
8.1 SQ. YDS.

EXIST. CURVE C80
PI STA. = 302+51.20
 $\Delta = 21^\circ 32' 16''$ (RT)
D = 28° 38' 52"
R = 200.00'
T = 38.04'
L = 75.18'
E = 3.59'
P.C. STA. = 302+13.16
P.T. STA. = 302+88.34






EARTH EXCAVATION (SPECIAL)
STA. 300+49, 20' LT TO
STA. 301+21, 51' RT
7 CU. YD.

CONCRETE CURB AND GUTTER, TYPE B 6.12
STA. 300+49, 20' LT TO
STA. 301+21, 51' LT
164 FOOT

V.E.C. CONTROL POINT #301
N: 590410.63
E: 2529561.98
ELEVATION: 502.95
DESCRIPTION: PIPE

REMOVE AND REINSTALL PARKING BLOCKS
STA. 300+49.00, 81.00' RT TO
STA. 300+94.60, 2.00' LT
17 EACH

TOPSOIL FURNISH AND PLACE VARIABLE DEPTH
STA. 300+49.00, 81.00' RT
STA. 301+10.72, 51.63' LT
146 SQ. YD.

-  - PAVEMENT REMOVAL
-  - HMA SURFACE REMOVAL
-  - SIDEWALK REMOVAL
-  - DETECTABLE WARNINGS
-  - EARTH EXCAVATION (SPECIAL)

FILE NAME =
#FILE#

USER NAME = #USER#
PLOT SCALE = #SCALE#
PLOT DATE = #DATE#

DESIGNED - R.H.D.	REVISED -
DRAWN - J.T.T.	REVISED -
CHECKED - R.H.D.	REVISED -
DATE - 4/4/12	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**WASHINGTON COUNTY CONSERVATION AREA
SHADY REST ALIGNMENT 1**

SCALE: 1" = 20' SHEET NO. 61 OF 112 SHEETS STA. 300+49 TO STA. 306+50

SECTION	COUNTY	TOTAL SHEET NO.
	WASHINGTON	112
		61

CONTRACT NO. 46223
ILLINOIS FED. AID PROJECT

JOB NO. 200-081-1 VASCANELLES ENGINEERING CORP. DESIGN FIRM REGISTRATION NUMBER 194-002107