

MIDLAND STANDARD ENGINEERING & TESTING, INC.

BORING LOG

SHEET 1 OF 1

PROJECT Algonquin Bypass Retaining Wall - IL. Route 31 DATE 3/17/09
 ROUTE FAP 339/ILL 31 BORED BY CD
 SECTION 96-00209-00-PV STATION 89+00 to 94+00 CHECKED BY WJW

COUNTY <u>McHenry</u>				WATER LEVEL DURING DRILLING <u>none</u>			
BORING <u>RW-66</u>				GROUND WATER AT COMPLETION <u>dry</u>			
STATION <u>89+75</u>				Depth	N/6"	Qu	W
OFFSET <u>23' L of CL</u>						tsf	%
GROUND SURFACE EL. <u>744.6</u>				Ft			
12-1/4" Bituminous Concrete over 6-3/4" Crushed Limestone Base Course							
Dark Brown and Grey Silty Clay LOAM, A-6: FILL							
Brown Silty Clay LOAM, A-6							
742.1							
5							
2							
5							
6							
8							
11							
10							
7							
10							
15							
8							
9							
10							
15							
7							
9							
15							
20							

N-Standard Penetration Test- Blows per foot to drive 2 inch
 O.D. Split Spoon Sampler 12 inches with 140 lbs. hammer falling 30 inches

Qu- Unconfined Compressive Strength (tsf)
 W- Water Content-percentage of oven dry weight (%)

Type failure: B- Bulge Failure
 S- Shear Failure
 E- Estimated Value
 P-Penetrometer

MIDLAND STANDARD ENGINEERING & TESTING, INC.

BORING LOG

SHEET 1 OF 1

PROJECT Algonquin Bypass Retaining Wall - IL. Route 31 DATE 3/17/09
 ROUTE FAP 339/ILL 31 BORED BY CD
 SECTION 96-00209-00-PV STATION 89+00 to 94+00 CHECKED BY WJW

COUNTY <u>McHenry</u>				WATER LEVEL DURING DRILLING <u>5.0'</u>			
BORING <u>RW-67</u>				GROUND WATER AT COMPLETION <u>6.1'</u>			
STATION <u>90+80</u>				Depth	N/6"	Qu	W
OFFSET <u>23' L of CL</u>						tsf	%
GROUND SURFACE EL. <u>746.8</u>				Ft			
13" Bituminous Concrete over 8" Crushed Limestone Base Course							
Brown Clay LOAM, A-6							
746.8							
5							
6							
5							
6							
5							
10							
9							
10							
15							
8							
10							
15							
7							
11							
15							
8							
12							
14							

N-Standard Penetration Test- Blows per foot to drive 2 inch
 O.D. Split Spoon Sampler 12 inches with 140 lbs. hammer falling 30 inches

Qu- Unconfined Compressive Strength (tsf)
 W- Water Content-percentage of oven dry weight (%)

Type failure: B- Bulge Failure
 S- Shear Failure
 E- Estimated Value
 P-Penetrometer

MIDLAND STANDARD ENGINEERING & TESTING, INC.

BORING LOG

SHEET 1 OF 1

PROJECT Algonquin Bypass Retaining Wall - IL. Route 31 DATE 3/16/09
 ROUTE FAP 339/ILL 31 BORED BY CD
 SECTION 96-00209-00-PV STATION 89+00 to 94+00 CHECKED BY WJW

COUNTY <u>McHenry</u>				WATER LEVEL DURING DRILLING <u>none</u>			
BORING <u>RW-68</u>				GROUND WATER AT COMPLETION <u>dry</u>			
STATION <u>91+60</u>				Depth	N/6"	Qu	W
OFFSET <u>23' L of CL</u>						tsf	%
GROUND SURFACE EL. <u>748.2</u>				Ft			
12-1/2" Bituminous Concrete over 6-1/2" Crushed Limestone Base Course							
Brown and Dark Grey SAND and GRAVEL, A-1: FILL							
Brown Silty Clay LOAM, A-6							
746.2							
5							
4							
3							
2							
10							
9							
11							
15							
3							
3							
7							
9							
10							
15							
5							
8							
11							
15							
5							
9							
12							
15							
7							
10							
12							
10							
13							
9							
11							
13							
20							

N-Standard Penetration Test- Blows per foot to drive 2 inch
 O.D. Split Spoon Sampler 12 inches with 140 lbs. hammer falling 30 inches

Qu- Unconfined Compressive Strength (tsf)
 W- Water Content-percentage of oven dry weight (%)

Type failure: B- Bulge Failure
 S- Shear Failure
 E- Estimated Value
 P-Penetrometer

I:\2154\cad\sheet\Roadway\20-STR\Structures & Walls\06-Wall A\0562507-60F72-08-BL.dgn 4/22/2012 4:22:21 PM



DRAWN	-	M. LANGE
DESIGNED	-	M. LANGE
CHECKED	-	G. HATLESTAD
DATE	-	5/3/2012

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

BORING LOGS I
WALL A; IL RTE 31
STRUCTURE NO. 056-2507
 SHEET NO. WA8 OF WA9 SHEETS

O.R. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
0003	18A-2	MCHENRY	825	592
CONTRACT NO. 60F72				
ILLINOIS FED. AID PROJECT				